

BATTERIES & CHARGERS

Nickel Cadmium/Nickel Metal Hydride Chargers

Detailed product specifications are available on: us.100y.com.tw



FEATURES

- Input electrical source: AC120V 60Hz 5W
- Output electrical source: DC2. 8V 320mA/140mAx2
- Environment temperature: 0~35°C

Part No.	Product No.	Manufacturer	Description
31127	HH198	Panasonic	Panasonic Automatic Shut Down Charger



SCOTT_QUICK CHARGER

Part No.	Product No.	Description
35794	HH208	SCOTT_QUICK CHARGER



FEATURES

- Secures battery to ensure precise placement
- Easier to hold and grip
- Dependable, long-lasting energizer® power

Part No.	Product No.	Manufacturer	Description
36566	HH210	Energizer	Mini pocket charger AA2500*4



FEATURES

- Charges up to 4 AA or AAA nickel-metal hydride (NiMH) batteries at a time
- 6-hour charge time
- Input: AC100~240V, 50/60Hz 8W
- Output: 5. 6VDC 360mA (4AA NiMH)
2. 8VDC 160mA (2AAA NiMH)

Part No.	Product No.	Manufacturer	Description
47728	HH242	DURACELL	Duracell NiMH AA/AAA Battery Charger



JCHSC-108-2300



JCHSC-108-800

FEATURES

- Output voltage: DC 5. 3V
- Output current: 600mA
- Input voltage: AC100~240V 50/60HZ
- Usage life: 1 year

Part No.	Product No.	Manufacturer	Description
22090	JCHSC-108-2300	SANYODENKI	MALIBA_Battery Quick Charger
22091	JCHSC-108-800	SANYODENKI	MALIBA_Battery Quick Charger



FEATURES

- Ultra high performance
- Individual minus delta voltage cut off
- Individual safety timer.
- Individual temperature sensor
- Trickle charge after full charge
- Bad battery detection
- Alkaline and primary battery detection
- No memory effect
- Safety guaranteed
- Environmentally friendlier
- Charges 1 to 4 pcs of NiMH/NiCd AA or AAA
- World wide usage (AC100~240V)
- 4xLed light charging indicator
- 4 cell are charged independently

Part No.	Product No.	Manufacturer	Description
23918	MPB-935	GP	GP_Power Bank AA 2100mAh (SMART-2)



FEATURES

- Ultra high performance
- 4 cell are charged independently

Part No.	Product No.	Manufacturer	Description
16457	MPB-989	GP	GP_Power Bank 1600mAh (For AA/AAA/9V Nickel Hydride And Nickel Metal Hydride Battery)



FEATURES

- Charger: Input voltage: AC100V~240V 50/60Hz
Charge current: 3-565mA x4 3-1275mA x2 4-310mA x2
- Battery: Voltage: DC1. 2V
Tolerance: 2500mAh (Min. 2300mAh)
- Working temperature: 0°C~40

Part No.	Product No.	Manufacturer	Description
36551	N-M57S	SANYO	SANYO_Nickel Cadmium/Nickel Metal Hydride Chargers

