

# BATTERIES & CHARGERS

## Lead Acid Chargers

Detailed product specifications are available on: [us.100y.com.tw](http://us.100y.com.tw)



### FEATURES

- Signal voltage: 110V~220V 50HZ/60HZ
- Input current: 8A
- Output voltage: DC-12V~24V
- Output current: DC-15A
- Output power: 450W
- Dimension: 277x215x172 (mm)

Part No.	Product No.	Description	Voltage	Volt./Current(out)
47297	FEB-12/24V-15A	Smart Battery Charger	110Vin	12/24V 15A
47237	FEB-12/24V-15A-220V	Smart Battery Charger	220Vin	12/24V 15A



### FEATURES

- Signal voltage: 110V~220V 50HZ/60HZ
- Input current: 10A
- Output voltage: DC-12V~24V
- Output current: DC-20A
- Output power: 600W
- Dimension: 277x215x172 (mm)
- Suitable battery: 12V/24V/100AH~200AH

Part No.	Product No.	Description	Voltage	Volt./Current(out)
47298	FEB-12/24V-20A	Smart Battery Charger	110Vin	12/24V 20A
47308	FEB-12/24V-20A-220V	Smart Battery Charger	220Vin	12/24V 20A



### FEATURES

- Signal voltage: 110V~220V 50HZ/60HZ
- Input current: 5A
- Output voltage: DC-12V~24V
- Output current: DC-8A
- Output power: 180W
- Dimension: 238x180x142 (mm)

Part No.	Product No.	Description	Voltage	Volt./Current(out)
47296	FEB-12/24V-8A	Smart Battery Charger	110Vin	12/24V 8A
47306	FEB-12/24V-8A-220V	Smart Battery Charger	220Vin	12/24V 8A



### FEATURES

- Input: AC-100~120V 50/60Hz
- Output: DC-12V 6A
- Dimension: 140\*116\*96
- AC/DC fuse in it

Part No.	Product No.	Description	Voltage	Volt./Current(out)
8777	MD12-6	Microcomputer Battery Charger	110V/120V	12Vdc/6A



RV-12V-6A-110V



VC-12V-6A

### FEATURES

- Signal voltage: 110V~220V 50HZ/60HZ
- Input current: 3A
- Output voltage: DC-12V
- Output current: DC-6A
- Output power: 90W
- Suitable battery: 12V/4AH~60AH
- Usage temperature: 0~40
- Enviroment wet: 20%~85%

Part No.	Product No.	Description	Voltage	Volt./Current(out)
47711	RV-12V-6A-110V	General Automobiles Battery Charger	110V	12V/3A
14397	VC-12V-6A	Microcomputer Battery Charger	110V	12V/8A max.



### FEATURES

- Signal voltage: 110V~220V 50HZ/60HZ
- Input current: 5A
- Output voltage: DC-24V
- Output current: DC-6A
- Output power: 180W
- Suitable battery: 24V/4AH~60AH
- Usage temperature: 0~40
- Enviroment wet: 20%~85%

Part No.	Product No.	Description	Voltage	Volt./Current(out)
19099	VC-24V-6A	Microcomputer Battery Charger	110Vin	24V/8A max.

## Battery Holders, Snaps And Clip Coin Cell Battery Holders

Detailed product specifications are available on: [us.100y.com.tw](http://us.100y.com.tw)



Size: DIA BY 2.0mm to 3.2mm thick cells

Part No.	Product No.	Description
12916	BH-001-PBSR	Coin Cell Battery Holder (Only for CR2032)

