



# CABLES / WIRES & ACCESSORIES

## Belden\_RS-232 / RS-485 Low Capacitance Cables

Detailed product specifications are available on: [us.100y.com.tw](http://us.100y.com.tw)



**DESCRIPTION:**

24AWG Stranded (7x32) TC conductors, semi-rigid PVC insulation, twisted, overall Beldfoil, shield (100% coverage), 24AWG stranded TC drain wire, PVC jacket

**PHYSICAL CHARACTERISTICS:**

- CONDUCTOR:**
- Number of Pairs: 2
  - Total Number of conductors: 4
  - AWG: 24
  - Stranding: 7x32
  - Conductor Material: TC-Tinned copper

Part No.	Product No.	Manufacture	Description	Lengths/Reel	No. of Pairs
36767	Belden 9503	Belden	Belden_RS-232/ RS-485 Low Capacitance Cable	1000ft(305M)/R	3



**DESCRIPTION:**

24AWG stranded (7x32) tinned copper conductors, twisted pairs, polyethylene insulated, overall 100% Beldfoil® shield plus a 90% tinned copper braid shield, 24 AWG (7x32) tinned copper drain wire, PVC jacket

**PHYSICAL CHARACTERISTICS:**

- CONDUCTOR:**
- Number of Pairs: 2
  - Total Number of conductors: 4
  - AWG: 24
  - Stranding: 7x32
  - Conductor Material: TC-Tinned copper



Part No.	Product No.	Manufacture	Description	Lengths/Reel	No. of Pairs
28258	Belden 9842	Belden	Belden_Paired-Low Capacitance EIA RS-485 Cable	1000Ft(305M)/R	2P4C



**DESCRIPTION:**

24AWG stranded (7x32) tinned copper conductors, semi-rigid PVC insulation, overall Beldfoil® shield (100% coverage)+TC braid shield (65% coverage), drain wire, PVC jacket

**PHYSICAL CHARACTERISTICS:**

- CONDUCTOR:**
- Number of Conductors: 6
  - Total Number of conductors: 6
  - AWG: 24
  - Stranding: 7x32
  - Conductor Material: TC-Tinned copper



Part No.	Product No.	Manufacture	Description	Lengths/Reel	No. of Pairs
29787	Belden-9611-0601000	Belden	Belden_RS-232/ RS-485 Low Capacitance Cable	1000ft/R	6 Conductor



**DESCRIPTION:**

24AWG stranded (7x32) tinned copper conductors, twisted pairs, polyethylene insulated ,overall 100% Beldfoil® shield plus a 90% tinned copper braid shield, 24AWG (7x32) tinned copper drain wire, PVC jacket

**PHYSICAL CHARACTERISTICS:**

- CONDUCTOR:**
- Number of Pairs: 3
  - Total Number of conductors: 6
  - AWG: 24
  - Stranding: 7x32
  - Conductor Material: TC-Tinned copper



Part No.	Product No.	Manufacture	Description	Lengths/Reel	No. of Pairs
29788	Belden-9843-0601000	Belden	Belden_RS-232/ RS-485 Low Capacitance Cable	1000ft/R	3 Pair



**DESCRIPTION:**

24AWG stranded (7x32) TC conductors, Datalene® insulation, overall Beldfoil® (100% coverage)+TC braid shield (65% coverage), drain wire, PVC jacket

**PHYSICAL CHARACTERISTICS:**

- CONDUCTOR:**
- Number of Conductors: 6
  - Total Number of conductors: 6
  - AWG: 24
  - Stranding: 7x32
  - Conductor Material: TC-Tinned copper



Part No.	Product No.	Manufacture	Description	Lengths/Reel	No. of Pairs
29715	Belden-9931-0601000	Belden	Belden_RS-232/RS-423 Low Capacitance Cable	1000ft/R	6 Conductor
29791	Belden-9933-0601000	Belden	Belden_RS-232/RS-423 Low Capacitance Cable	1000ft/R	8 Conductor



**DESCRIPTION:**

24AWG stranded (7x32) tinned copper conductors, conductors cabled, semi-rigid PVC insulation, overall Beldfoil® shield (100% coverage), 24AWG stranded tinned copper drain wire, PVC jacket

**PHYSICAL CHARACTERISTICS:**

- CONDUCTOR:**
- Number of Conductors: 3
  - Total Number of conductors: 3
  - AWG: 24
  - Stranding: 7x32
  - Conductor Material: TC-Tinned copper



Part No.	Product No.	Manufacture	Description	Lengths/Reel	No. of Pairs
36742	Belden 9533	Belden	Belden_RS-232/ RS-485 Low Capacitance Cable	1000ft(305M)/R	3

