



CABLES / WIRES & ACCESSORIES

Belden_RS-232 / RS-485 Low Capacitance Cables

Detailed product specifications are available on: us.100y.com.tw



DESCRIPTION:
24AWG stranded (7x32) tinned copper conductors, conductors cabled, semi-rigid PVC insulation, overall Beldfoil® shield (100% coverage), 24AWG stranded tinned copper drain wire, PVC jacket

PHYSICAL CHARACTERISTICS: **BeldenCable™**
CONDUCTOR:
 ● Number of Conductors: 4
 ● Total Number of conductors: 4
 ● AWG: 24
 ● Stranding: 7x32
 ● Conductor Material: TC-Tinned copper

Part No.	Product No.	Manufacture	Description	Lengths/Reel	No. of Pairs
36747	Belden 9534	Belden	Belden_RS-232/ RS-485 Low Capacitance Cable	1000ft(305M)/R	4



DESCRIPTION:
24AWG stranded (7x32) tinned copper conductors, conductors cabled, semi-rigid PVC insulation, overall Beldfoil® shield (100% coverage), 24AWG stranded tinned copper drain wire, PVC jacket

PHYSICAL CHARACTERISTICS: **BeldenCable™**
CONDUCTOR:
 ● Number of Conductors: 5
 ● Total Number of conductors: 5
 ● AWG: 24
 ● Stranding: 7x32
 ● Conductor Material: TC-Tinned copper

Part No.	Product No.	Manufacture	Description	Lengths/Reel	No. of Pairs
36751	Belden 9535	Belden	Belden_RS-232/ RS-485 Low Capacitance Cable	1000ft(305M)/R	5



DESCRIPTION:
24AWG stranded (7x32) tinned copper conductors, conductors cabled, semi-rigid PVC insulation, overall Beldfoil® shield (100% coverage), 24AWG stranded tinned copper drain wire, PVC jacket

PHYSICAL CHARACTERISTICS: **BeldenCable™**
CONDUCTOR:
 ● Number of Conductors: 6
 ● Total Number of conductors: 6
 ● AWG: 24
 ● Stranding: 7x32
 ● Conductor Material: TC-Tinned copper

Part No.	Product No.	Manufacture	Description	Lengths/Reel	No. of Pairs
36755	Belden 9536	Belden	Belden_RS-232/ RS-485 Low Capacitance Cable	1000ft(305M)/R	6



DESCRIPTION:
24AWG stranded (7x32) tinned copper conductors, conductors cabled, semi-rigid PVC insulation, overall Beldfoil® shield (100% coverage), 24AWG stranded tinned copper drain wire, PVC jacket

PHYSICAL CHARACTERISTICS: **BeldenCable™**
CONDUCTOR:
 ● Number of Conductors: 15
 ● Total Number of conductors: 15
 ● AWG: 24
 ● Stranding: 7x32
 ● Conductor Material: TC-Tinned copper

Part No.	Product No.	Manufacture	Description	Lengths/Reel	No. of Pairs
36759	Belden 9541	Belden	Belden_RS-232/ RS-485 Low Capacitance Cable	1000ft(305M)/R	15

Belden_RS-422 CAD/CAM Cables

Detailed product specifications are available on: us.100y.com.tw



DESCRIPTION:
24AWG stranded (7x32) TC conductors, Datalene® insulation, twist pairs, overall Beldfoil® (100% coverage) +TC braid shield (65% coverage), 24AWG stranded TC drain wire, PVC jacket

BeldenCable™

Part No.	Product No.	Manufacturer	Description	Lengths/Reel	No. of Pairs
36295	BELDEN 8102	Belden	Belden_RS-422 CAD/CAM Cable	1000Ft(305M)/R	2
36716	BELDEN 8103	Belden	Belden_RS-422 CAD/CAM Cable	1000Ft(305M)/R	3
36723	BELDEN 8104	Belden	Belden_RS-422 CAD/CAM Cable	1000Ft(305M)/R	4
36737	BELDEN 8105	Belden	Belden_RS-422 CAD/CAM Cable	1000Ft(305M)/R	5



DESCRIPTION:
24AWG stranded (7x32) tinned copper conductors, twisted pairs, individually shielded with 100% Beldfoil®, 24AWG stranded wire tinned copper drain wire Datalene® insulation, overall Beldfoil®, shield pul 65% tinned copper braid shield, PVC jacket

BeldenCable™

Part No.	Product No.	Manufacturer	Description	Lengths/Reel	No. of Pairs
8595	BELDEN 8162	Belden	Belden_RS-422 CAD/CAM	1000Ft(305M)/R	2P4C
8596	BELDEN 8163	Belden	Belden_RS-422 CAD/CAM	1000Ft(305M)/R	3P6C
8597	BELDEN 8164	Belden	Belden_RS-422 CAD/CAM Cable	1000Ft(305M)/R	4P8C

