



CABLES / WIRES & ACCESSORIES

Local Area Network (LAN) Cables Twisted Pair

Detailed product specifications are available on: us.100y.com.tw



SPACIFICATION:
24AWG stranded copper wire

APPLICATION:

- Voice
- T1
- 10Base-T (IEEE802. 3)
- Fast Ethernet (IEEE802. 3u)
- 100Vg-AnyLAN (IEEE802. 12)
- Token Ring (IEEE802. 5)
- TP-PMD (ANSI X3T9. 5)
- 100Base-T Ethernet (IEEE802. 5)
- 155/622 Mps ATM
- 1000Base-T
- 550MTz Broadband Vedio

Part No.	Product No.	Description	AWG	No. of Pairs	Length/Reel	Spec.
12064	NET-CBL-PRO305-6	Cat.6 4 Pair Unshielded Wire	24	4P8C	305M/R	Cat.6 4 Pair UTP(Solid)



DESCRIPTION:

- 24AWG stranded copper wire
- PVC or low smoke innocuity jacket
- Pass the standard of UL, CSA PCC FT4/ETL, ISO/IEC-11801 and En50173

Detailed product specifications are available on: us.100y.com.tw



Part No.	Product No.	Manufacturer	Description	AWG	No. of Pairs	Length/Reel	Spec.
17508	4101181048-02	DINTEK	Cat.5E 4P UTP Cable	24	4P8C	(100M)/R	CM, CEC CM



DESCRIPTION:

Conductor: Horizontal Cable: 1x24AWG (1x0.5mm) solid copper or Patch Cable 7x34AWG (7/0.16mm) standard coppers
 Insulation: polyolefin
 Color Code: Pair 1: White/Blue&Blue, Pair2: White/Orange&Orange
 Pair3: White/Green&Green, Pair4: White/Brown&Brown
 Shield: Drain wire and aluminum-mylar tape
 Jacket: Low smoke Non-Halogen (LSNH) compound, Nominal OD: 5.7mm
 Standards: UL444/CSA-C22. 2 NO. 214 Type CM ISO/IEC-11801, Horizontal Cable (solid copper)
 ISO/IEC-11801, Patch Cable (stranded coppers)

Part No.	Product No.	Description	AWG	No. of Pairs	Length/Reel	Spec.
2969	DS-L5E-3	STP 4P8C Cat.5e	24	4P8C	305M/R	TIA/EIA-568A




DESCRIPTION:

- HDPE plastic isolation
- Copper conductor
- PVC jacket, high security
- EIA/TIA 568A, ISO/IEC11801 CAT. 5e, UL/CSA Ft4
- Transmission speed: 100Mbps.

Detailed product specifications are available on: us.100y.com.tw

Part No.	Product No.	Description	AWG	No. of Pairs	Length/Reel	Spec.
14137	IBM-25L4231	IBM-CAT 5+ 4UTP,CMR,Gray	24	4P8C	1000F(305M)/R	CM, CEC CM
14135	NET-CBL-PRO100	CAT.5E Twisted Pair Cable	24	4P8C	(100M)/R	CM, CEC CM
35592	NET-CBL-PRO100/6	CAT.6 Twisted Pair			(100M)/R	CM, CEC CM
13187	NET-CBL-PRO305/5e	Cat.5e UTP Cable CM	24	4P8C	(305M)/R	UTP Cat.5e
34398	NET-CBL-PRO305R	Cat.5e UTP Cable CM	24		(305M)/R	UTP Cat.5e



DESCRIPTION:

- FR-PVC jacket, (LSZH) jacket, TPE jacket
- 24AWG solid conductor
- polyethylene insulation

Part No.	Product No.	Description	AWG	No. of Pairs	Length/Reel	Spec.
17454	NET-CBL-PRO305B	Cat.5e UTP Cable	24	4P8C	(305M)/R	CM, CEC CM
18015	NET-CBL-PRO50	Cat.5e UTP Cable CM	24	4P8C	(50M)/R	CM, CEC CM
16216	Outdoor CAT.5e	Outdoor CAT.5e #24/8C	24	8C	305M/R	CAT.5e PE Waterproof and Sunproof

