



CABLES / WIRES & ACCESSORIES

SUMITOMO Heat-Shrinkable Tubing, SUMITUBE F32

Detailed product specifications are available on: us.100y.com.tw



BASIC PROPERTIES:

Materials: cross-linked, flexible, flame-retardant polyolefin resin
 Shrink temperature: 90°C min
 Shrink ratio: 50% min (Radial change)
 Longitudinal change: - (5±5) %
 Continuous operating temperature: -55 to 125°C

APPLICATIONS:

Insulation protection and reinforcement of terminations and joints of electric wires
 Color identification and bundling of electric wires
 Insulation and protection of resistances and capacitors



Part No.	Product No.	Manufacturer	Description	W*T(mm)	Inside Diameter (mm)	Length/Reel	Color	Wall Thickness (mm)	Temp. (°C)
3011	F32-1	SUMITOMO	Heat-Shrinkable Tubing, SUMITUBE F32	1*0.2	0.50	200M/R	Black	0.33	125°C
13819	F32-1	SUMITOMO		1.0*0.2		200M/R			125°C
3012	F32-1.5	SUMITOMO	Heat-Shrinkable Tubing, SUMITUBE F32	1.5*0.2	0.75	200M/R	Black	0.36	125°C
29154	F32-1/8INCH	SUMITOMO	Heat-Shrinkable Tubing, SUMITUBE F32	1/8**0.25	1/8 Inch	50M/R	Black	1/16 Inch	125°C
3019	F32-10	SUMITOMO	Heat-Shrinkable Tubing, SUMITUBE F32	10*0.25	5.0	50M/R	Black	0.56	125°C
17088	F32-10-W	SUMITOMO	Heat-Shrinkable Tubing, SUMITUBE F32	10*0.25	5.0	50M/R	White	0.56	125°C
3020	F32-12	SUMITOMO	Heat-Shrinkable Tubing, SUMITUBE F32	12*0.25	6.0	50M/R	Black	0.56	125°C
13360	F32-13	SUMITOMO	Heat-Shrinkable Tubing, SUMITUBE F32	13*0.3	6.5	50M/R	Black	0.69	125°C
3021	F32-15	SUMITOMO	Heat-Shrinkable Tubing, SUMITUBE F32	15*0.3	7.5	50M/R	Black	0.69	125°C
3013	F32-2	SUMITOMO	Heat-Shrinkable Tubing, SUMITUBE F32	2*0.2	1.0	200M/R	Black	0.44	125°C
28227	F32-2-Yellow	SUMITOMO	Heat-Shrinkable Tubing, SUMITUBE F32	2*0.2	1.0	200M/R	Yellow	0.44	125°C
3014	F32-2.5	SUMITOMO	Heat-Shrinkable Tubing, SUMITUBE F32	2.5*0.25	1.25	200M/R	Black	0.44	125°C
9096	F32-2.5-White	SUMITOMO	Heat-Shrinkable Tubing, SUMITUBE F32	2.5*0.25	1.25	200M/R	White	0.44	125°C
9098	F32-2.5-Red	SUMITOMO	Heat-Shrinkable Tubing, SUMITUBE F32	2.5*0.25	1.25	200M/R	Red	0.44	125°C
9095	F32-2.5- Yellow	SUMITOMO	Heat-Shrinkable Tubing, SUMITUBE F32	2.5*0.25	1.25	200M/R	Yellow	0.44	125°C
9097	F32-2.5- Gerren	SUMITOMO	Heat-Shrinkable Tubing, SUMITUBE F32	2.5*0.25	1.25	200M/R	Green	0.44	125°C
9094	F32-2.5-Blue	SUMITOMO	Heat-Shrinkable Tubing, SUMITUBE F32	2.5*0.25	1.25	200M/R	Blue	0.44	125°C
3022	F32-20	SUMITOMO	Heat-Shrinkable Tubing, SUMITUBE F32	20*0.35	10.0	50M/R	Black	0.77	125°C
3023	F32-25	SUMITOMO	Heat-Shrinkable Tubing, SUMITUBE F32	25*0.4	12.5	50M/R	Black	0.87	125°C
3015	F32-3	SUMITOMO	Heat-Shrinkable Tubing, SUMITUBE F32	3*0.25	1.5	200M/R	Black	0.44	125°C
35098	F32-3- Yellow	SUMITOMO	Heat-Shrinkable Tubing, SUMITUBE F32	3*0.25	1.5	200M/R	Black	0.44	125°C
3016	F32-3.5	SUMITOMO	Heat-Shrinkable Tubing, SUMITUBE F32	3.5*0.25	1.75	200M/R	Black	0.44	125°C
9101	F32-3.5- White	SUMITOMO	Heat-Shrinkable Tubing, SUMITUBE F32	3.5*0.25	1.75	200M/R	White	0.44	125°C
9103	F32-3.5- Red	SUMITOMO	Heat-Shrinkable Tubing, SUMITUBE F32	3.5*0.25	1.75	200M/R	Red	0.44	125°C
9100	F32-3.5- Yellow	SUMITOMO	Heat-Shrinkable Tubing, SUMITUBE F32	3.5*0.25	1.75	200M/R	Yellow	0.44	125°C
9102	F32-3.5- Gerren	SUMITOMO	Heat-Shrinkable Tubing, SUMITUBE F32	3.5*0.25	1.75	200M/R	Green	0.44	125°C
9099	F32-3.5- Blue	SUMITOMO	Heat-Shrinkable Tubing, SUMITUBE F32	3.5*0.25	1.75	200M/R	Blue	0.44	125°C
16778	F32-30	SUMITOMO	Transparent Heat-Shrinkable Tubing, SUMITUBE F32	30*0.5	15	50M/R	Black	0.87	125°C
39213	F32-30RD	SUMITOMO	Transparent Heat-Shrinkable Tubing, SUMITUBE F32	30*0.5	15	50M/R	Red	0.87	125°C
27936	F32-4	SUMITOMO	Heat-Shrinkable Tubing, SUMITUBE F32	4*0.25	2	200M/R	Black	0.44	125°C
3017	F32-5	SUMITOMO	Heat-Shrinkable Tubing, SUMITUBE F32	5.0*0.25	2.5	100M/R	Black	0.56	125°C
27946	F32-6	SUMITOMO	Heat-Shrinkable Tubing, SUMITUBE F32	6*0.25	3mm	100M/R	Black	0.56mm	125°C
3018	F32-7	SUMITOMO	Heat-Shrinkable Tubing, SUMITUBE F32	7.0*0.25	3.5	50M/R	Black	0.56	125°C
28930	F32-8	SUMITOMO	Heat-Shrinkable Tubing, SUMITUBE F32	8*0.35	10.0	50M/R	Black	0.77	125°C

- For detail of these and many more similar products, please go to our website.
- We also provide service of reserving product for you

Centenary Materials

Waiting for your phone call



021-54151736



T E L : Taiwan: 886-3-5753170
 F A X : Taiwan: 886-3-5753172
 E-mail : Taiwan: us_sale@100y.com.tw

Shenzhen: 86-755-83298787
 Shenzhen: 86-755-83640655
 Shenzhen: 100y@163.com

Shanghai: 86-21-54151736
 Shanghai: 86-21-64605107
 Shanghai: 100y-1@163.com