

CABLES / WIRES & ACCESSORIES

Wall Heat Shrinkable Tube

Detailed product specifications are available on: us.100y.com.tw



APPLICATIONS:

Insulation protection and reinforcement of terminations and joints of electric wires, antiseptis and rust prevention of mental, the symbol of wire. etc

COLOR:

Black, Red, Blue, White, Yellow, Green, Clear, could produce other colors for your demands

Part No.	Product No.	Description	mm	Length/Reel	color	Temp. (°C)
16075	ψ1.0mm-Black	Thin Heat-Shrinkable Tubing	0.5~0.9	200M	Black	125°C
16096	ψ10.0mm-Black	Thin Heat-Shrinkable Tubing	5.0~9.0	100M	Black	125°C
16097	ψ15.0mm-Black	Heat-Shrinkable Tubing	7.5~14.8	100M	Black	125°C
16076	ψ2.0mm-Black-300V	Thin Heat-Shrinkable Tubing	1.0~1.8mm	200M	Black	125°C
30453	ψ2.0mm-Black-600V	Heat-Shrinkable Tubing	1.0~1.8mm	200M	Black	125°C
16080	ψ2.0mm-Blue	Heat-Shrinkable Tubing	1.0~1.8	200M	Blue	125°C
16078	ψ2.0mm-Yellow	Heat-Shrinkable Tubing	1.0~1.8	200M	Yellow	125°C
16077	ψ2.0mm-Red	Heat-Shrinkable Tubing	1.0~1.8	200M	Red	125°C
16079	ψ2.0mm-Green	Heat-Shrinkable Tubing	1.0~1.8	200M	Green	125°C
16098	ψ20.0mm-Black	Heat-Shrinkable Tubing	10.0~19.0	100M	Black	125°C
16088	ψ3.0mm-Black	Thin Heat-Shrinkable Tubing	1.5~2.7	200M	Black	125°C
16981	ψ30.0mm- Black	Heat-Shrinkable Tubing	15~29	50M	Black	125°C
16092	ψ5.0mm-Green	Heat-Shrinkable Tubing	2.5~4.5	100M	Green	125°C
16090	ψ5.0mm-Red	Heat-Shrinkable Tubing	2.5~4.5	100M	Red	125°C
16091	ψ5.0mm- Yellow	Heat-Shrinkable Tubing	2.5~4.5	100M	Yellow	125°C
16093	ψ5.0mm- Blue	Heat-Shrinkable Tubing	2.5~4.5	100M	Blue	125°C
16982	ψ50.0mm- Black	Heat-Shrinkable Tubing	25~49	25M	Black	125°C
16094	ψ8.0mm-Black	Thin Heat-Shrinkable Tubing	4.0~7.2	100M	Black	125°C

SUMITOMO Heat-Shrinkable Tubing, SUMITUBE V



BASIC PROPERTIES:

Materials: Flexible, flame-retardent, polyvinyl chloride resin
 Shrink ratio: 50%min (Radial change)
 Longitudinal change: -30%min
 Continuous operating: -30 to 105°C temperature

APPLICATIONS:

- Insulation, protection and reinforce of terminations and joints of electric wires
- Fixing and protection of cable lables
- Insulation and protection of resistances and capacitors



Part No.	Product No.	Manufacturer	Description	W*T(mm)	Inside Diameter (mm)	Length/Reel	Color	Wall Thickness (mm)
8988	V-1.5	SUMITOMO	Heat-Shrinkable Tubing, SUMITUBE V	1.5*0.15	0.75	100M/R	Transparent	0.33
13189	V-15	SUMITOMO	Heat-Shrinkable Tubing, SUMITUBE V	15.0*0.25	7.5	50M/R	Transparent	0.69
14371	V-2	SUMITOMO	Heat-Shrinkable Tubing, SUMITUBE V	2*0.15	1.00	100M/R	Transparent	0.33
8989	V-2.5	SUMITOMO	Transparent Heat-Shrinkable Tubing, SUMITUBE V	2.5*0.15	1.25	100M/R	Transparent	0.33
13800	V-25	SUMITOMO	Heat-Shrinkable tubings, SUMITUBE V	25*0.25	12.5	50M/R	Transprent	0.77
8990	V-3	SUMITOMO	Heat-Shrinkable Tubing, SUMITUBE V	3.0*0.15	1.50	100M/R	Transparent	0.33
8991	V-5	SUMITOMO	Transparent Heat-Shrinkable Tubing, SUMITUBE V	5.0*0.15	2.50	50M/R	Transparent	0.44
8992	V-7	SUMITOMO	Heat-Shrinkable Tubing, SUMITUBE V	7.0*0.15	3.50	50M/R	Transparent	0.44

Heat-Shrinkable Tubing, SUMITUBE A

PHYSICAL:

- Tensile strength: 1.0min
- Elongation: 200min
- Specific gravity: 0.92
- Water absorption: 0.1max
- Longitudinal shrinkage: 15max

COLOR:

Black/ Brown/ Red/ Orange/ Yellow/ Green/ Blue/ violet/ Grey/ White/ Clear



Part No.	Product No.	Description	W*T(mm)	Inside Diameter (mm)	Length/Reel	Color	Wall Thickness (mm)
40153	A-1	Heat-Shrinkable Tubing, SUMITUBE A	1.3*0.2	0.6	200M/R	Transparent	0.4±0.1
14576	A-10	Heat-Shrinkable Tubing, SUMITUBE A	10*0.25	6.0	50M/R	Transparent	0.5±0.1
13218	A-15	Heat-Shrinkable Tubing, SUMITUBE A	15*0.3	10	50M/R	Transparent	0.6±0.1
40184	A-2	Heat-Shrinkable Tubing, SUMITUBE A	2*0.2	1.3	200M/R	Transparent	0.4±0.1
39659	A-2.5	Heat-Shrinkable Tubing, SUMITUBE A	2.5*0.2	1.5	200M/R	Transparent	0.4±0.1
34392	A-20	Heat-Shrinkable Tubing, SUMITUBE A	20*0.3	13.0	50M/R	Transparent	0.6±0.1



T E L : Taiwan: 886-3-5753170
 F A X : Taiwan: 886-3-5753172
 E-mail : Taiwan: us_sale@100y.com.tw

Shenzhen: 86-755-83298787
 Shenzhen: 86-755-83640655
 Shenzhen: 100y@163.com

Shanghai: 86-21-54151736
 Shanghai: 86-21-64605107
 Shanghai: 100y-1@163.com