



CABLES / WIRES & ACCESSORIES

UL1015 (Stranded) Hook-Up Wire

Detailed product specifications are available on: us.100y.com.tw



DESCRIPTION:

- Solid, tinned or bare copper conductor, 28~9 AWG
- Color-coded PVC insulation
- Rated temperature: 105°C
- Rated voltage: 600volts
- Uniform thickness of wire to ensure easy stripping and cutting
- Resistant to acids, oils, alkalis, moisture and fungus
- Passes UL VW-1&CSA Ft1 vertical flame test
- OS-1 is available

Part No.	Product No.	Description	No./mm	Length/Reel	AWG	ohm/kft	Color	Insu. Thick. (mils)
8711	1015-12-A1	UL1015 (Stranded) Hook -up Wire	65/0.255	305M/R	12	1.65	Red	30
8712	1015-12-C1	UL1015 (Stranded) Hook -up Wire	65/0.255	305M/R	12	1.65	Yellow	30
8713	1015-12-D1	UL1015 (Stranded) Hook -up Wire	65/0.255	305M/R	12	1.65	Green	30
13085	1015-12-H1	UL1015 (Stranded) Hook -up Wire	65/0.255	305M/R	12	1.65	White	30
8714	1015-12-I1	UL1015 (Stranded) Hook -up Wire	65/0.255	305M/R	12	1.65	Black	30
8715	1015-14-A1	UL1015 (Stranded) Hook -up Wire	41/0.255	305M/R	14	2.62	Red	30
8716	1015-14-C1	UL1015 (Stranded) Hook -up Wire	41/0.255	305M/R	14	2.62	Yellow	30
8724	1015-14-D2	UL1015 (Stranded) Hook -up Wire	41/0.255	305M/R	14	2.62	Green	30
8725	1015-14-I1	UL1015 (Stranded) Hook -up Wire	41/0.255	305M/R	14	2.62	Black	30
24662	1015-14-W	UL1015 (Stranded) Hook -up Wire	41/0.255	305M/R	14	2.62	White	30
16447	1015-16-G/Y	UL1015 (Stranded) Hook -up Wire	26/0.254	305M/R	16	4.18	Green	30mils 0.76mm
34557	1015-16-P	UL1015 (Stranded) Hook -up Wire	26/0.254	305M/R	16	4.18	Red	30mils 0.76mm
33066	1015-16-Y	UL1015 (Stranded) Hook -up Wire	26/0.254	305M/R	16	4.18	Yellow	30mils 0.76mm
33064	1015-16-R	UL1015 (Stranded) Hook -up Wire	26/0.254	305M/R	16	4.18	Purple	30mils 0.76mm
8726	1015-18-A2	UL1015 (Stranded) Hook -up Wire	34/0.18	610M/R	18	6.64	Red	30
18600	1015-18-BL	UL1015 (Stranded) Hook-up Wire	34/0.18	610M/R	18	6.64	Blue	30
8728	1015-18-C2	UL1015 (Stranded) Hook -up Wire	34/0.18	610M/R	18	6.64	Yellow	30
2288	1015-18-D2	UL1015 (Stranded) Hook -up Wire	34/0.18	610M/R	18	6.64	Green	30
8729	1015-18-H2	UL1015 (Stranded) Hook -up Wire	34/0.18	610M/R	18	6.64	White	30
8730	1015-18-I2	UL1015 (Stranded) Hook -up Wire	34/0.18	610M/R	18	6.64	Black	30
14334	1015-18-G	UL1015 (Stranded) Hook -up Wire	34/0.18	610M/R	18	6.64	Gray	30
14333	1015-18-B	UL1015 (Stranded) Hook -up Wire	34/0.18	610M/R	18	6.64	Brown	30
8731	1015-20-A2	UL1015 (Stranded) Hook -up Wire	21/0.18	610M/R	20	10.5	Red	30
18326	1015-20-BL	UL1015 Multicore Hook-up Wire	21/0.18	610M/R	20	10.5	Blue	30
8732	1015-20-C2	UL1015 (Stranded) Hook -up Wire	21/0.18	610M/R	20	10.5	Yellow	30
8733	1015-20-D2	UL1015 (Stranded) Hook -up Wire	21/0.18	610M/R	20	10.5	Green	30
8734	1015-20-I2	UL1015 (Stranded) Hook -up Wire	21/0.18	610M/R	20	10.5	Black	30
14607	1015-22-B	UL1015 (Stranded) Hook -up Wire	17/0.16	610M/R	22	16.7	Black	0.79mm
18742	1015-22-BL	UL1015 (Stranded) Hook-up Wire	17/0.16	610M/R	22	16.7	Blue	0.79mm
24928	1015-22-C2	UL1015 (Stranded) Hook-up Wire	17/0.16	610M/R	22	16.7	Yellow	0.79mm
18741	1015-22-G	UL1015 (Stranded) Hook-up Wire	17/0.16	610M/R	22	16.7	Green	0.79mm
14606	1015-22-R	UL1015 (Stranded) Hook -up Wire	17/0.16	610M/R	22	16.7	Red	0.79mm
14609	1015-24-B	UL1015 (Stranded) Hook -up Wire	11/0.16	610M/R	24	29.3	Black	0.79mm
14608	1015-24-R	UL1015 (Stranded) Hook -up Wire	11/0.16	610M/R	24	29.3	Red	0.79mm
14649	MPVC1218106261	PVC Hook-up Wire	12/0.18	3280Ft/R	20		Blue	

UL 1283 Hook-Up Wire

Detailed product specifications are available on: us.100y.com.tw

UL1283 (Stranded) Hook-Up Wire



- Conductor: -24 thru 6 AWG
-Solid stranded or Topcoat, bare or tinned copper conductor per ASTM B-33
- Insulation: color coded PVC, Temperature: -40°C to +105°C (*UL1011 -40°C to +80°C)
- Applications: Hook up wire
- Appliance wiring
- point to point wiring
- Internal wiring of meters panels, electrical and electronic equipment

Part No.	Product No.	Description	Length/Reel	Color	AWG
40613	1283-6-Black	UL1283 (Stranded) Hook -up Wire 【ROHS】	100M/R	Black	6

If you have something about our product, please call us.
We will give you best service

[Http://us.100y.com.tw/](http://us.100y.com.tw/)

Centenary Materials

Waiting for your phone call



T E L : Taiwan: 886-3-5753170
F A X : Taiwan: 886-3-5753172
E-mail : Taiwan: us_sale@100y.com.tw

Shenzhen: 86-755-83298787
Shenzhen: 86-755-83640655
Shenzhen: 100y@163.com

Shanghai: 86-21-54151736
Shanghai: 86-21-64605107
Shanghai: 100y-1@163.com