

CABLES / WIRES & ACCESSORIES

2 Conductors Stranded Speaker Cable

Detailed product specifications are available on: us.100y.com.tw



- Conductor with highly pure OFC conductor
- Insulation with high density foam PE
- High density OFC braiding coverage to cut down inductance and capacitance
- Soft and highly flexible PVC jacket



- Configuration: (27/0.11*7)*2F
- OD: 3.8*7.6mm
- Material: OCC
- Length: 100Y
- Application: car, wiring



- Configuration: (720.1*7)*2F
- OD: 5.5*14.5mm
- Material: OCC
- Length: 100Y
- Application: upgrade speaker cable



- Configuration: [(4/0.04*10S+30/0.01C)*7]*2F
- OD: 5.6*13.6mm
- Material: silver foil aluminum
- Length: 100M/R

Part No.	Product No.	Manufacturer	Description	No. / mm	Length/Reel
8868	100*2F-Red/Black	SINYU	Colored 2 Conductors Stranded Speaker Cable	100C/0.14	67.5M/R
8866	30*2F- Red/Black	SINYU	Colored 2 Conductors Stranded Speaker Cable	30C/0.14	67.5M/R
8867	50*2F- Red/Black	SINYU	Colored 2 Conductors Stranded Speaker Cable	50C/0.14	67.5M/R
9145	DC-112		SPK-200 Low Capacitance 2Conductors Stranded Speaker Cable	200/0.12	100Y(91.44M)/R
9146	DC-122		HI-Fi Low Capacitance 2Conductors Stranded Speaker Cable	505/0.12	100Y(91.44M)/R
11254	DC-132		Silver Foil Low Capacitance 2Conductors Stranded Speaker Cable		50M/R

Optical Cable Fibre Optic Cable

Detailed product specifications are available on: us.100y.com.tw



Fiber optic is specification designed to use in a wide range of operating conditions and they will not optically or mechanically deteriorate once installed

Part No.	Product No.	Description	FIBER DIA(mm)	O.D.(mm)	Length/Reel	Color	Coaxial
17419	LFE-100-1	Fibre Optic Cable	1.0	2.2mm	1000M	Black	1
17205	LFS-075-01-G	Fibre Optic Cable	0.75		2700M/Reel	Green	1

Test Lead Wires Standard Test Lead Wires


Detailed product specifications are available on: us.100y.com.tw



- Size OD: 3.0mm
- Clarification: 300V 0.5A

Part No.	Product No.	Description	Color	Length/Reel	No./mm	Size OD
8861	Ammeter wire-Red-20/0.12mm	Stranded Test Lead Wires	Red	500Y(457.2M) / R	20/0.12mm	3.0mm
8863	Ammeter wire -Yellow-20/0.12mm	Stranded Test Lead Wires	Yellow	500Y(457.2M) / R	20/0.12mm	3.0mm
8862	Ammeter wire -Black-20/0.12mm	Stranded Test Lead Wires	Black	500Y(457.2M) / R	20/0.12mm	3.0mm
8864	Ammeter wire -Green-20/0.12mm	Stranded Test Lead Wires	Green	500Y(457.2M) / R	20/0.12mm	3.0mm
8865	Ammeter wire -Blue-20/0.12mm	Stranded Test Lead Wires	Blue	500Y(457.2M) / R	20/0.12mm	3.0mm

Braid Wire & Copper Wire & Tinsel Wire Flat Copper Braid Wire



- Tinned copper wire
- Electric current the same with 6AWG conduct
- Pliability and operability

Part No.	Product No.	Manufacturer	Description	Nominal W (CM)	Length (M)
7065	25-4.6L	3M	Electrical Grounding Braid	12.7mm	4.57M
30656	I-90B		Flat Copper Braid	4mm	200M/R
38848	I-90C		Flat Copper Braid	15mm	100M/R
40277	I-95B		Flat Copper Braid 24/15/0.12T	15mm	100M/R
15514	I-T-1/2		Flat Copper Braid	1/2"	152M
15515	I-T-1/4		Flat Copper Braid	1/4"	100M

