

CAPACITORS

Solid Tantalum Capacitors Dipped Tantalum Capacitors

Detailed product specifications are available on: us.100y.com.tw



TAP is a professional grade device manufactured with a flame retardant coating and featuring low leakage current and impedance, very small physical sizes, and exceptional temperature stability. It is designed and conditioned to operate to +125°C and is available loose or taped and reeled for auto insertion. The 15 case size with wide capacitance and working voltage ranges means the TAP can accommodate almost any application



Part No.	Product No.	Manufacturer	Description	Capacitance uF	Voltage DCV	Tolerance(±)	Size: D*L (mm)
15175	47uF±20% 16V		Dipped Tantalum Capacitor	47uF	16V	±20%	
40852	6.8uF±20% 35V		Dipped Tantalum Capacitor	6.8uF	35V	±20%	
6361	CB0J107M1EBB		Dipped Tantalum Capacitor P:2.54mm	100uF	6.3V	±20%	P:2.54mm
3810	CB1A107M2EBB		Dipped Tantalum Capacitor P:5.08mm	100uF	10V	±20%	P:5.08mm
32122	CB1V105M1ABB		Dipped Tantalum Capacitor	1uF	35V	±20%	
6360	CT22UM16VBV		Dipped Tantalum Capacitor	22uF	16V	±20%	
32690	TAP104K050SCS	AVX	Dipped Tantalum Capacitor	0.1uF	50V	±10%	
4664	TAP104M035SCS	AVX	Dipped Tantalum Capacitor	0.1uF	35V	±20%	
15170	TAP105M025SCS	AVX	Dipped Tantalum Capacitor	1uF	25V	±20%	
6371	TAP105M035SCS	AVX	Dipped Tantalum Capacitor	1uF	35V	±20%	
6370	TAP105M050SCS	AVX	Dipped Tantalum Capacitor	1uF	50V	±20%	
4461	TAP106K016SCS	AVX	Dipped Tantalum Capacitor	10uF	16V	±10%	
13386	TAP106K035SCS	AVX	Dipped Tantalum Capacitor	10uF	35V	±10%	
32121	TAP106M016SCS	AVX	Dipped Tantalum Capacitor	10uF	16V	±20%	
15174	TAP106M025SCS	AVX	Dipped Tantalum Capacitor	10uF	25V	±20%	5.5*9(H)mm
3784	TAP106M035SCS	AVX	Dipped Tantalum Capacitor	10uF	35V	±20%	
15172	TAP106M050SCS	AVX	Dipped Tantalum Capacitor	10uF	50V	±20%	8.5*12.5(H)mm
23941	TAP107M006SCS	AVX	Dipped Tantalum Capacitor	100uF	6.3V	±20%	
2828	TAP224M035SCS	AVX	Dipped Tantalum Capacitor	0.22uF	35V	±20%	
6369	TAP225K025SCS	AVX	Dipped Tantalum Capacitor	2.2uF	25V	±10%	
6365	TAP225M035SCS	AVX	Dipped Tantalum Capacitor	2.2uF	35V	±20%	
15171	TAP226M025SCS	AVX	Dipped Tantalum Capacitor	22uF	25V	±20%	6*10(H)mm
15173	TAP226M050SCS	AVX	Dipped Tantalum Capacitor	22uF	50V	±20%	9.5*16(H)mm
24037	TAP227K016CCS	AVX	AVX_Dipped Tantalum Capacitor	220uF	16V	±10%	
37190	TAP227M010SCS	AVX	Dipped Tantalum Capacitor	220uF	10V	±20%	
6215	TAP334M035SCS	AVX	Dipped Tantalum Capacitor	0.33uF	35V	±20%	
6368	TAP335K016SCS	AVX	Dipped Tantalum Capacitor	3.3uF	16V	±10%	
39607	TAP336K016SCS	AVX	Dipped Tantalum Capacitor	33uF	16V	±10%	
6362	TAP336M016SCS	AVX	Dipped Tantalum Capacitor	33uF	16V	±20%	
6216	TAP474K035SCS	AVX	Dipped Tantalum Capacitor	0.47uF	35V	±10%	
4460	TAP475K016SCS	AVX	Dipped Tantalum Capacitor	4.7uF	16V	±10%	
6363	TAP476K016SCS	AVX	Dipped Tantalum Capacitor	47uF	16V	±10%	
6364	TAP476K035SCS	AVX	Dipped Tantalum Capacitor	47uF	35V	±10%	
22601	TAP476M016SCS	AVX	Dipped Tantalum Capacitor	47uF	16V	±20%	
6217	TAP684M035SCS	AVX	Dipped Tantalum Capacitor	0.68uF	35V	±20%	
6367	TAP685M016SCS	AVX	Dipped Tantalum Capacitor	6.8uF	16V	±20%	
6366	TAP685M035SCS	AVX	Dipped Tantalum Capacitor	6.8uF	35V	±20%	

NEC_SMD Tantalum Capacitors

Detailed product specifications are available on: us.100y.com.tw



FEATURES:

- Lead-free type. In conformity to RoHS
- Offer a range of small, high-capacity models
- Succeeded to the technology plus outstanding performance



Part No.	Product No.	Manufacturer	Description	Capacitance	Tolerance(±)	Voltage	Case(L*W1*H*L1*W2*K)	Pes./Reel
16709	47uF/16V-C	NEC	SMD Tantalum Capacitor	47uF	±10%	16V	C	500
16716	68uF/10V-C	NEC	SMD Tantalum Capacitor	68uF	±20%	10V	C	500 Pes /R
40116	TEESVB20J476M8R	NEC	SMD Tantalum Capacitor=NRS476M06R8	47uF	±20%	6.3V	B	2000
38439	TEESVB21C106M8R	NEC	SMD Tantalum Capacitor=NRS106M16R8	10uF	±20%	16V	B	2000
37821	TEESVB21E475M8R	NEC	SMD Tantalum Capacitor=NRS475M25R8	4.7uF	±20%	25V	B	2000/R
19492	TEESVB21E475M8R	NEC	SMD Tantalum Capacitor=NRS475M25R8	4.7uF	±20%	25V	B	2000/R
40405	TEESVC0J227M12R	NEC	SMD Tantalum Capacitor	220uF	±20%	6.3V	C	500
14509	TEESVD1A107M12R	NEC	SMD Tantalum Capacitor =NRD107M10R12	100uF	±20%	10V	D	500/R

