



# COMPUTER ACCESSORIES

## Parallel Printer Cables

Detailed product specifications are available on: [us.100y.com.tw](http://us.100y.com.tw)



Suitable for computer-parallel printer cables  
2 D-SUB 25PIN female, 1 D-SUB 25PIN male

Part No.	Product No.	Description	M/F,M/M,F/F
6816	GC-25M/2*25F	Parallel Printer Cable	25M-25F+25F




### TECHNICAL INFORMATION

- Cable type: SCSI external cable
- Cable length: 0.35M
- Total connectors: 2
- Connector: 1x50pin HD D-Sub (HD-50) -male  
1x50pin centronics-male
- Cable grade/rating/specifics: 28AWG stranded tinned coppers
- Platform support: PC/Mac
- Conductor: gold plated copper
- Jacket: flextec PVC

Part No.	Product No.	Description	Length (M)	M/F,M/M,F/F
15122	S-1-2-0.35	Parallel Printer Cable (SCSI)	0.35M	50M/50M

## RGB Video Cables

Detailed product specifications are available on: [us.100y.com.tw](http://us.100y.com.tw)



### FEATURES

- Connector: BW3 male to 4 BNC male
- Constructed of premium grade double-shielded video cable
- Five 75 Ohm impedance-matched internal coax lines for red, green, blue, sync and ground
- 125°C foil shielding; 90% tinned copper braid shielding
- Ferrites protect against EMI/RFI interference
- Accommodates cable runs up to 100ft without a booster (in most cases)



### DESCRIPTION

15HD (HD15) male to 5BNC female RGB/HV cable  
Premium signal breakout cable RGB+HV. Allow direct conversion of a 5-BNC, RGB+HV cable to DB 15HD connector for HDTV, video projector applications. True 75 ohm connectors and cable for accurate video & sync signal transfers. 1.8M in length

Part No.	Product No.	Description	Length (M)	M/F,M/M,F/F
8548	BC35121-1.8MN30	SUN MONITOR CABLE 13W3M/BNC*4		
6037	H15M-5BNC-1.8M	RGB Video Cable	1.8M	3 Row 15 M -5pcs BNC

## USB Cables

Detailed product specifications are available on: [us.100y.com.tw](http://us.100y.com.tw)




### MECHANICAL

- |                  |  |   |
|------------------|--|---|
| Vibration random | EIA364-28 condition<br>V Test letter A or<br>longer duration | No discontinuity of<br>1 us                       |
| Physical shock   | No discontinuity of 1<br>us or longer duration               | EIA 364-27 condition<br>H                         |
| Durability       | >1500 cycles   | EIA 364-09  |
| Mating force 1   | 36 Newtons maximum   | EIA 364-13  |
| Unmation force 1 | 0 Newtons minimum  | EIA 364-13  |
| Cable retention  | Cable shall not dislode<br>from cable crimp                  | Apply axial load of<br>25 Newtons to the<br>cable |

### ELECTRICAL

- |                         |                     |
|-------------------------|---------------------|
| Termination resistance  | 30MΩ maximum        |
| Insulation esistance    | 1000MΩ minimum      |
| Dielectric withstanding | 750V AC at sealevel |

Part No.	Product No.	Manufacturer	Description	Length (M)	M/F,M/M,F/F
7665	U-A/A-B-1.8	HJ	USB A-Type Cable	1.8M	M/M
27799	U-A/A-B-10	HJ	USB A-Type Cable	10M	M/M
24006	U-A/AF-B-1.8	HJ	USB A-Type Extension Cable	1.8M	M/F
23425	U-A/B-B-1.8	HJ	USB A/B-Type Cable	1.8M	M/M
17027	U-A/MI4P-BL-1.8-2.0	HJ	Mini Usb Cable 2.0	1.8M	M/M
17920	U-A/MI5P-BL-1.8		USB Cable	1.8M	AM/MI5P



### SPECS

Color: black  
Compatibility: connect your USB printer, scanner, drive adapter  
Internal/ external: external  
Length: 1.8M 3M

### Cable

Environment: USB devices  
Grade/ Rating/ Specifics: 20AWG  
Material/ Characteristics: gold plated copper contacts  
foil and braid shield; double shielded  
24K gold plated corrosion-proof connectors  
undermold shield; molded strain relief

Part No.	Product No.	Manufacturer	Description	Length (M)	M/F,M/M,F/F
17630	U-A/AF-B-3M	HJ	USB A-Type Cable	3M	M/F
27949	UA-0402-00	HJ	USB A-Type Extension Cable	3M	M/F

