



## COMPUTER ACCESSORIES

### D-Sub 9-25-Pin Serial Adaptors

Detailed product specifications are available on: [us.100y.com.tw](http://us.100y.com.tw)



GC-13W3M/15F

This adapter is used to connect a vga monitor to a sun's video port  
One end is 13W3 male  
The other end is DB 15 high density female (3 rows of pins)

#### KEY FEATURES

Whether you need to convert existing DB 9 ports to DB 25 or vice versa, this is an inexpensive alternative to buying new cables



GC-9F25F

#### SPECIFICATION

Connectors  
1xDB 9 female  
1xDB 25 female  
Type: D-sub adaptor

Material  
Plug · material: brass, gold flash  
Contact · shell: sheet metal, tin-plated  
Insulator material: polyester resin, glass  
and fiber reinforced

Color: beige jacket  
Contact material: N/A  
Thumbscrews: 4-40 thread on both sides

#### Electrical

Current rating: 1Amp  
Dielectric withstanding voltage: AC 500V min for 1  
minute

Insulation resistance: 1000M ohms min (@ 500V DC)  
Contact resistance: 15M ohms max. mated  
Working temperature: -55Deg. C to +105Deg. C



GC-9F25M

DB9 female to DB25 male  
Adapter-DB9 female to DB25 male-serial adaptor

#### KEY FEATURES

This serial adaptor features a male DB9 on one side & a female DB25 on the other

#### SPECIFICATION

Connectors  
1xDB 9 female  
1xDB 9 female  
Color: Beige

Material  
Plug : brass  
Contact : gold flash  
Shell: sheet metal, tin plated  
Insulator material: polyester resin, glass  
and fiber reinforced

Color: beige jacket  
Contact material: N/A  
Thumbscrews: 4-40 thread on both sides

#### Electrical

Current rating: 1Amp  
Dielectric withstanding voltage: AC 500V min for 1  
minute

Insulation resistance: 1000M ohms min (@ 500V DC)  
Contact resistance: 15M ohms max. mated  
Working temperature: -55Deg. C to +105Deg. C

#### KEY FEATURES

Whether you need to convert existing DB 9 ports to DB 25 or vice versa, this is an inexpensive alternative to buying new cables



GC-9M25F

#### SPECIFICATION

Connectors  
1xDB 9 female  
1xDB 25 female  
Type: D-sub adaptor

Material  
Plug · material: brass, gold flash  
Contact · shell: sheet metal, tin-plated  
Insulator material: polyester resin, glass  
and fiber reinforced

Color: beige jacket  
Contact material: N/A  
Thumbscrews: 4-40 thread on both sides

#### Electrical

Current rating: 1Amp  
Dielectric withstanding voltage: AC 500V min for 1  
minute

Insulation resistance: 1000M ohms min (@ 500V DC)  
Contact resistance: 15M ohms max. mated  
Working temperature: -55Deg. C to +105Deg. C

Part No.	Product No.	Description
6853	GC-13W3M/15F	DB13W3M/HD15F Adaptor
8149	GC-9F25F	D-Sub 9-25-Pin Serial Adaptor
8148	GC-9F25M	D-Sub 9-25-Pin Serial Adaptor
2551	GC-9M25F	D-Sub 9-25-Pin Serial Adaptor
8306	GC-9M25M	D-Sub 9-25-Pin Serial Adaptor

### Patch Box + RS 232 Tester

Detailed product specifications are available on: [us.100y.com.tw](http://us.100y.com.tw)



The check tester will help you avoid expensive repair calls by showing you simple interface problem which you can repair yourself. In seconds it will target the status of line 2, 3, 4, 5, 6, 8, 11, 19 and 20. It includes male to female DB15 connectors



- DB 25 male/female
- Monitors RN 2, 3, 4, 5, 6, 8 and 20
- Monitors lines: TD, RTS, DSR, CD, RD, CTS and DTR
- Seven tri-state (2 color) LEDs
- No external power required



Part No.	Product No.	Description	Type
5292	GC-25CK	RS232-18 CHECK TEST Adaptor	
5291	GC-25JB	JUMPER BOX Adaptor	25M/F
5293	GC-25MT	RS232-7 MINI TEST Adaptor	25M/25F
5322	GC-25MW	Jumper/Wiring Adaptor	25M/F

