2.54mm Terminal with Wire

Detailed product specifications are available on: us. 100y. com. tw

SPECIFICATION

- Withstand current: 1A (USE AWG 24#1007 UL Wire)
- Withstand voltage: AC 250V

Part No.	Product No.	Description	Pin
7711	3194-10	2.54mm 5003 Terminal Cable40CM	10P
7706	3194-12	2.54mm 5003 Terminal Cable 40CM	12P
7705	3194-2	2.54mm 5003 Terminal Cable 40CM	2P
8372	3194-3	2.54mm 5003 Terminal Cable 40CM	3P
8373	3194-4	2.54mm 5003 Terminal Cable 40CM	4P
12761	3194-5	2.54mm 5003 Terminal Cable 40CM	5P
9111	3194-6	2.54mm 5003 Terminal Cable 40CM	6P
9112	3194-7	2.54mm 5003 Terminal Cable 40CM	7P
9113	3194-8	2.54mm 5003 Terminal Cable 40CM	8P
28255	3194-9	5003 Terminal with Wire	9P

SPECIFICATION

- Suitable wire: AWG 28#-22#
- Temperature range: -25°C ~ +85°C
- Rated voltage: 250V AC. DC
- Rated current: 3A AC. DC
- Contact resistance: ≤0. 01Ω
- Insulated resistance: ≥1000MΩ
- Withstand voltage: 1000V. /min, AC/minute

Part No.	Product No.	Description	Pin
35132	F03-10P-250E*2	#26 2.54mm 25cm Terminal Cable	10P
15916	F03-12P-400E*2	#26 2.54mm 40cm Terminal Cable	12P
14447	F11-03P-450D*2	#24 XH 3P 45CM Twin Head	3P
14448	F11-07P-450D*2	#24 XH 7P 45CM Twin Head	7P
23283	F11-12P-450D	AWG24/45CM 9001Connector + Terminal Cable	12P
23653	F11-12P-450D*2	#24 XH 2P 45CM Twin Head	12P
14449	F11-16P-450D*2	#24 XH 16P 45CM Twin Head	16P
39126	P0924-BF06/XHD01	AWG24/12CM 9001Connector + Terminal Cable	6P

SPECIFICATION

- Suitable wire: AWG 28#-22#
- Temperature range: -25°C ~ +85°C
- Rated voltage: 250V AC. DC
- Rated current: 3A AC. DC
- Contact resistance: ≤0. 01Ω
- Insulated resistance: ≥1000MΩ
- Withstand voltage: 1000V. /min, AC/minute

Part No.	Product No.	Description	Pin
7520	F11-02P-450D	AWG24/45CM 9001Connector + Terminal Cable	2P
9141	F11-03P-450D	AWG24/45CM 9001Connector + Terminal Cable	3P
10629	F11-04P-450D	AWG24/45CM 9001zConnector + Terminal Cable	4P
7518	F11-05P-450D	AWG24/45CM 9001Connector + Terminal Cable	5P
12059	F11-06P-450D	AWG24/45CM 9001Connector + Terminal Cable	6P
9979	F11-07P-450D	AWG24/45CM 9001 Connector + Terminal Cable	7P
10627	F11-08P-450D	AWG24/45CM 9001Connector + Terminal Cable	8P
12058	F11-10P-450D	AWG24/45CM 9001Connector + Terminal Cable	10P
23283	F11-12P-450D	AWG24/45CM 9001Connector + Terminal Cable	12P

SPECIFICATION

- Insulator material: Nylon 66(UL 94V-0)
- Wire range: AWG #28~#22
- Rated voltage: 250V
- Rated current: 1A
- Contact resistance: ≤0. 01Ω
- Insulation resistance: ≥1000MΩ
- Withstanding voltage: 1000V. AC
- Temp range for usage: -25~85°C
- Relative humidity: 93%+40°
- P. C board thickness: 1. 6mm

Part No.	Product No.	Description	Pin
14302	F29-10P/2.54 8P	#26 PH10P With 8P/2.54 8P wire	8P

- Rated voltage: AC 250V
- Rated current: 1A

Color:

Part No.	Product No.	Description
12420	I16-B1-450	2.54mm Terminal Cable
12421	I16-B2-450	#26 2.54mm Terminal Cable 45CM double-edged white,black,red,yellow,green,grey,blue ,coffee,purple