



# (Nylon, Vinyl)-Insulated Straight Butt Splice Connectors

Detailed product specifications are available on: [us.100y.com.tw](http://us.100y.com.tw)



Wire range A. W. G. mm <sup>2</sup>	ITEM NO.	Dimension inch (mm)		MATERIAL
		L		
22-16 A. W. G. 0.5-1.5 mm <sup>2</sup>	BNYF1	0.992 25.20		COPPER PLATE



Part No.	Product No.	Manufacturer	Description	Color	L*d1*D	Cable	Conn. Material	°C/Volt/A	Insulation Material
4967	BNYF1	KST	NYLON-INSULATED BUTT SPLICE CONNECTORS	Red	25.2*1.7*4	16-22AWG(0.5-1.5mm)	Copper	105°C/600V/19A	Nylon
4973	BNYF2	KST	NYLON-INSULATED BUTT SPLICE CONNECTORS	Blue	25.2*2.3*4.5	14-16AWG(1.5-2.5mm)	Copper	105°C/600V/27A	Nylon
4976	BNYF5	KST	NYLON-INSULATED BUTT SPLICE CONNECTORS	Yellow	28*3.4*6.3	12-10AWG(4-6mm2)	Copper	105°C/600V/48A	Nylon



Wire range A. W. G. mm <sup>2</sup>	ITEM NO.	Dimension inch (mm)		MATERIAL
		L		
22-16 A. W. G. 0.5-1.5 mm <sup>2</sup>	BVS1	0.953 24.20		Brass plate
16-14 A. W. G. 1.5-2.5 mm <sup>2</sup>	BVS2	0.953 24.20		Brass plate
12-10 A. W. G. 4.6 mm <sup>2</sup>	BVS5	1.024 26.00		Brass plate



Part No.	Product No.	Manufacturer	Description	Color	L*d1*D	Cable	Conn. Material	°C/Volt/A	Insulation Material
4274	BVS1	KST	VINYL-INSULATED BUTT SPLICE CONNECTORS(COPPER TUBULAR)	Red	24.2*1.7*4mm	22-16AWG(0.5-1.5mm2)	Brass	75°C/300V/10A	Vinyl
7760	BVS2	KST	VINYL-INSULATED BUTT SPLICE CONNECTORS(COPPER TUBULAR)	BLUE	24.2*2.3*4.5mm	16-14 AWG(1.5-2.5mm2)	Brass	75°C/300V/15A	Vinyl
11185	BVS5	KST	VINYL-INSULATED BUTT SPLICE CONNECTORS(COPPER TUBULAR)	Yellow	26*3.4*6.3	12-10AWG(4-6mm2)	Brass	75°C/300V/15A	Vinyl



Wire range A. W. G. mm <sup>2</sup>	ITEM NO.	Dimension inch (mm)		MATERIAL
		L		
22-16 A. W. G. 0.5-1.5 mm <sup>2</sup>	WBNY1	1.220 31.00		COPPER TUBULAR



Part No.	Product No.	Manufacturer	Description	Insulation Color	L*d1*D	Cable	Conn. Material	°C/Volt/A	Insulation Material
6460	WBNY1	KST	NYLON-INSULATED WINDOW BUTT SPLICE CONNECTORS	Red	31*1.8*4.0	22-16AWG(0.5-1.5mm2)	Copper Tubular	105°C/600V/19A	Nylon
6447	WBNY5	KST	NYLON-INSULATED WINDOW BUTT SPLICE CONNECTORS	Yellow	41*3.6*6.2	12-10AWG(4-6mm2)	Copper Tubular	105°C/600V/48A	Nylon

# PC-Insulated Bullet Splice Connectors

Detailed product specifications are available on: [us.100y.com.tw](http://us.100y.com.tw)



Wire range A. W. G. mm <sup>2</sup>	ITEM NO.	Dimension inch (mm)			MATERIAL
		L			
22-16 A. W. G. 0.5-1.5 mm <sup>2</sup>	BNITF1	0.984 25.00			COPPER TUBULAR



Part No.	Product No.	Manufacturer	Description	Insulation Color	Size L*d1*D(mm)	Cable No.	Conn. Material	°C/Volt/A
6444	BNITF1-CLEAR	KST	PC-INSULATED (FLARED) BUTT SPLICE CONNECTORS	Red	25*1.7*4	22-16AWG(0.5-1.5mm2)	Copper	125°C/600V/19A



Wire range A. W. G. mm <sup>2</sup>	ITEM NO.	Dimension inch (mm)			MATERIAL
		L	D	d1	
16-14 A. W. G. 1.5-2.5 mm <sup>2</sup>	BNITF2	0.984 25.00	0.177 4.50	0.091 2.30	COPPER TUBULAR



Part No.	Product No.	Manufacturer	Description	Insulation Color	Size L*d1*D(mm)	Cable No.	Conn. Material	°C/Volt/A
37627	BNITF2-CLEAR	KST	INSULATED SPLICE CONNECTORS	BLUE	25*2.3*4.5	16-14AWG(1.5-2.5mm2)	Copper	125°C/600V/27A

