



Mid-Way Wire Connectors


Detailed product specifications are available on: us.100y.com.tw



Material: KW-1, KW-6: Nylon66 UL94V-2
KW-2, 3, 4, 5: PP



Part No.	Product No.	Manufacturer	Description	Cable No.	Insulation Color	Package	Insulation Material
35131	KW-11	KSS	Mid-WayWire Connector	16-14AWG	BLUE	100Pcs/Packing	PP



Item No.	Wire combination	A	B	C
KW-3	22AWG-18AWG	19.4	8.1	12.6
KW-4	18AWG-14AWG	19.5	8.2	13
KW-5	12AWG-10AWG	11	20	15



Part No.	Product No.	Manufacturer	Description	Cable No.	Insulation Color	Package	Insulation Material
15893	KW-3		Mid-WayWire Connector	18-22AWG(1.25mm2)	Red	100Pcs/Packing	PP
14305	KW-4	KSS	Mid-WayWire Connector	18-14AWG(2mm2)	Blue	100Pcs/Packing	PP
13729	KW-5	KSS	Mid-WayWire Connector	12-10AWG(5.5mm2)	Yellow	100Pcs/Packing	PP



- Features: moisture resistant seal
- Operating temperature: -40~140°C
-40~285°F
- UL, CSA, or CE Certified: n/a
- Solid wire only



Connector	Type Connector	Special Features	Maximum Insulation O. D.		Cable type			
			Metric (mm)	Inches	PIC-unfilled and PIC-filled		Pulp or paper	
					AWG	Metric (mm)	AWG	Metric (mm)
Butt splicing		Gel-filled Polycarbonate	1.52	0.060	22-26	0.7-0.4	22-26	0.7-0.4

Part No.	Product No.	Manufacturer	Description	Cable No.	Package
8266	UY	3M	Mid-WayWire Connector For Communication	22-26AWG	(100Pcs/Box)



- Features: RUS Listed, full featured
- Operating temperature: -40~140°C
-40~285°F
- UL, CSA, or CE Certified: n/a
- Solid wire only




Connector	Type Connector	Special Features	Maximum Insulation O. D.		Cable type			
			Metric (mm)	Inches	PIC-unfilled and PIC-filled		Pulp or paper	
					AWG	Metric (mm)	AWG	Metric (mm)
Butt splicing		Gel-filled Polypropelene RUS Listed	2.08	0.082	19-26	0.9-0.4	N/A	N/A

Part No.	Product No.	Manufacturer	Description	Cable No.	Package
14980	UY2	3M	Mid-WayWire Connector For Communication	19-26AWG(0.9-0.4mm)Solid wire	(100Pcs/Box)

Solderless Terminal & Connector Vinyl, Nylon-Insulated Close End Terminals

Detailed product specifications are available on: us.100y.com.tw



Wire range A. W. G. mm ²	Item No		Dimension inch (mm)
	Brazed seam	Butted seam	
26-22 A. W. G 0.2-0.5mm ²		PTNY0.5-9	0.055 1.40



Part No.	Product No.	Manufacturer	Description	Insulation Color	L	d	Insulation Material	°C/Volt/A
6462	PTNY0.5-9	KST	Pin Terminal	Yellow	18L*1.0d1*2.2D	26-22AWG(0.2-0.5mm2)	Nylon	105°C/600V



Part No.	Product No.	Manufacturer	Description	Insulation Color	L	d	Insulation Material	°C/Volt/A
29757	PTNY5-13	KST	Pin Terminal	Yellow	27L*3.4d1*6.4D	12-10AWG(4-6mm2)	Nylon	105°C/600V

