




Vinyl, Nylon-Insulated Lipped Blade Terminal- Eyelets


Detailed product specifications are available on: us.100y.com.tw



Wire range A. W. G. Mm ²	Item No		Dimension ^{Inch/mm}						
	Brazed seam	Butted seam	W	F	L	E	D	d1	T
16-14 A. W. G. 1.5-2.5mm ²	DBVBS2-18	DBVS2-18	0.75 2.0	.709 18.0	1.094 27.8	.394 10.0	.177 4.5	.091 2.3	.031 0.8
12-10 A. W. G. 4-6mm ²	DBVB5-14	DBV5-14	0.177 4.5	.551 14.0	1.063 27.0	.512 13.0	.248 6.3	.134 3.4	.039 1.0



Part No.	Product No.	Description	Insulation Color	Insulation Material	°C/Volt/A	L*W*d1*D	Cable No.
6492	DBV5-14	VINYL-Insulated Blade Terminal	Yellow	Vinyl	75°C/600V/48A	27*4.5*3.4*6.3	12-10AWG(4-6mm2)
11869	DBVS2-18	VINYL-Insulated Blade Terminal	Blue	Vinyl	75°C/600V/27A	27.8*2.0*2.3*4.5	16-14AWG(1.5-2.5mm2)




Wire range A. W. G. Mm ²	Item No		Dimension ^{Inch/mm}								
	Brazed seam	Butted seam	W	F	L	E	D	d1	A	T	
22-16 A. W. G. 0.5-1.5mm ²	LBVB1-3	LBV1-3	0.118 3.0	.661 16.8	1.071 27.2	.394 10.0	.157 4.0	.067 1.7	.083 2.1	.030 0.75	
16-14 A. W. G. 1.5-2.5mm ²	LBVB2-3	LBV1-3	.118 3.0	.661 16.8	1.071 27.2	.394 10.0	4.5 11.7	.091 2.3	.083 2.1	.031 0.8	
12-10 A. W. G. 4-6mm ²	LBVB5-3	LBV5-3	.118 3.0	.677 17.2	1.189 30.2	.512 13.0	.248 6.3	1.34 3.4	0.94 2.4	.039 1.0	



Part No.	Product No.	Description	Insulation Color	Insulation Material	°C/Volt/A	L*W*d1*D	Cable No.
6473	LBV1-3	VINYL-Insulated Blade Terminal	Red	Vinyl	75°C/600V/19A	27.2*3.0*1.7*4.0	22-16AWG(0.5-1.5mm2)
6477	LBV2-3	VINYL-Insulated Blade Terminal	Blue	Vinyl	75°C/600V/27A	27.2*3.0*2.3*4.5	16-14AWG(1.5-2.5mm2)
6475	LBV5-3	VINYL-Insulated Blade Terminal	Yellow	Vinyl	75°C/600V/48A	30.2*3.0*3.4*6.3	12-10AWG(4-6mm2)


Vinyl, Nylon Insulated Male+ Female Disconnect

Detailed product specifications are available on: us.100y.com.tw




Wire range A. W. G. mm ²	Item No.	NEMA TAB	DIMENSION ^{Inch/mm}						FIG
			W	F	L	B	D	T	
26-22A. W. G. 0.2-0.5mm ²	FDD0.5-110(5)	0.20x.110 (0.5x2.8)	.126 3.2	.252 6.4	.630 16.0	.031 8.0	.110 2.8	.010 0.25	1

Part No.	Product No.	Description	Insulation Color	Size L*W*C*D	Cable No.	Fully / Half	°C/Volt/A	Insulation Material	Type
6465	FDD0.5-110(5)	75°C VINYL-FULLY INSULATED FEMALE DISCONNECTORS	Yellow	16*3.2*C1.0mm	26-22AWG(0.2-0.5mm2)	Half	75°C/300V	Vinyl	Female



Wire range A. W. G. mm ²	Item No.	NEMA TAB	DIMENSION ^{Inch/mm}					
			W	F	L	B	D	T
22-16A. W. G. 0.5-1.5mm ²	FDD1-250	0.32x.250 (0.8x6.35)	.260 6.6	.287 7.3	.819 20.8			.016 0.4

Part No.	Product No.	Description	Insulation Color	Size L*W*C*D	Cable No.	Fully / Half	°C/Volt/A	Insulation Material	Type
6468	FDD1-250G	VINYL-Insulated Double Crimp Female Disconnect	Red	20.8*6.6*1.7mm	22-16AWG 0.5~1.5mm2	Half	75°C	Vinyl	Gold Plated Female Terminal



Wire range A. W. G. mm ²	Item No.	NEMA TAB	DIMENSION ^{Inch/mm}					
			W	F	L	B	D	T
22-16A. W. G. 0.5-1.5mm ²	FDNYD1-110(8)	0.32x.110 (0.8x2.8)	.126 3.2	.252 6.4	.768 19.5	.433 11.0	.157 4.0	.012 0.3
	FDNYD1-187(8)	0.32x.187 (0.8x4.75)	.197 5.0	.256 6.5	.795 20.2			.016 0.4

Part No.	Product No.	Manufacturer	Description	Insulation Color	Size L*W*C*D	Cable No.	Fully / Half	°C/Volt/A	Insulation Material	Type
12906	FDNYD1-110(8)	KST	105°C NYLON-FULLY INSULATED FEMALE DISCONNECTORS 16AWG 10A	Red	19.5*3.2*1.7	22-16AWG(0.5-1.5mm2)	Fully	105°C/300V/10A	Nylon	female
27122	FDNYD1-187(8)	KST	105°C NYLON-FULLY INSULATED FEMALE DISCONNECTORS 16AWG 10A	Red	20.2*5*1.7*4	22-16AWG(0.5-1.5mm2)	Fully	105°C/300V/10A	Nylon	female

