





Vinyl, Nylon Insulated Male+ Female Disconnect

Detailed product specifications are available on: us.100y.com.tw




Wire range A. W. G. mm ²	ITEM NO.	NEMA TAB	DIMENSION ^{Inch} / _{mm}							FIG
			W	F	L	B	D	T		
22-16A. W. G. 0.5-1.5mm ²	FDFN1-250	0.32x.250 (0.8x6.35)	.260 6.6	.287 7.3	.866 22.0	.433 11.0	.157 4.0	.016 0.4	1	
	MDFN1-250		.250 6.35	.303 7.7	.906 23.0				2	
16-14A. W. G. 1.5-2.5mm ²	FDFN2-250	0.32x.250 (0.8x6.35)	.260 6.6	.287 7.3	.866 22.0	.433 11.0	.177 4.5	.016 0.4	1	
	MDFN2-250		.250 6.35	.303 7.7	.945 24.0				2	

Part No.	Product No.	Description	Insulation Color	Size L*W*C*D	Cable No.	Fully / Half	°C/Volt/A	Insulation Material	Type
8294	FDFN1-250-CLEAR	105°C NYLON-FULLY INSULATED FEMALE DISCONNECTORS 16AWG	Red	22*6.6*1.7mm	22-16AWG(0.5-1.5mm2)	Fully	105°C/300V	Nylon	Female
5620	FDFN2-250	105°C Nylon-INSULATED DOUBLE CRIMP FEMALE DISCONNECTORS	Blue	22*6.6*2.3mm	16-14AWG(1.5-2.5mm2)	Fully	105°C	Nylon-Fully	Female
10752	MDFN1-250-CLEAR	Nylon Fully Insulated Male Disconnecter	Light Red	23mm	22-16AWG(0.5-1.25m m ²)	Fully	105°C	Nylon-Fully	Male
10750	MDFN2-250-CLEAR	NYLON-FULLY INSULATED FEMALE DISCONNECTORS	Ligh Blue	24*6.35	16-14AWG(1.5-2.5m m ²)	Fully	105°C/300V	Nylon	Male



Wire range A. W. G. mm ²	ITEM NO.	NEMA TAB	DIMENSION ^{Inch} / _{mm}							FIG
			W	F	L	B	D	T		
22-16A. W. G. 0.5-1.5mm ²	FDFN1-250	0.32x.250 (0.8x6.35)	.260 6.6	.287 7.3	.866 22.0	.433 11.0	.157 4.0	.016 0.4	1	
	MDFN1-250		.250 6.35	.303 7.7	.906 23.0				2	
16-14A. W. G. 1.5-2.5mm ²	FDFN2-250	0.32x.250 (0.8x6.35)	.260 6.6	.287 7.3	.866 22.0	.433 11.0	.177 4.5	.016 0.4	1	
	MDFN2-250		.250 6.35	.303 7.7	.945 24.0				2	
22-10A. W. G. 4-6mm ²	FDFN5-250	0.32x.250 (0.8x6.35)	.260 6.6	.287 7.3	.945 24.0	.512 13.0	.248 6.3	.016 0.4		
	MDFN5-250		.250 6.35	.303 7.7	.984 25.0					

Part No.	Product No.	Description	Insulation Color	Size L*W*C*D	Cable No.	Fully / Half	°C/Volt/A	Insulation Material	Type
6497	FDFN1-250	105°C Nylon Fully Insulated Female Disconnecter	Red	22.5*6.6*1.7mm	22-16AWG(0.5-1.5mm2)	Fully	105°C/300V	Nylon	Female
6449	FDFN2-250	105°C NYLON-FULLY INSULATED FEMALE DISCONNECTORS 14AWG	Blue	23*6.6*2.3mm	16-14AWG(1.5-2.5mm2)	Fully	105°C/300V	Nylon	Female
6499	FDFN5-250	105°C Nylon -Fully Insulated Female Disconnecter 10AWG 24A (100Pcs/Packing)	Yellow	23*6.6*3.4mm	12-10AWG(4-6mm2)	Fully	105°C/300V/24A	Nylon	Female
6439	MDFN1-250	NYLON-FULLY INSULATED FEMALE DISCONNECTORS	Red	0.250*0.032/6.35*0.8	22-16AWG(0.5-1.5mm2)	Fully	105°C/300V	Nylon	Male
6453	MDFN2-250	NYLON-FULLY INSULATED FEMALE DISCONNECTORS	Blue	24.5*6.35	16-14AWG(1.5-2.5mm2)	Fully	105°C/300V	Nylon	Male
6445	MDFN5-250	NYLON-FULLY INSULATED FEMALE DISCONNECTORS	Yellow	24.5*6.35	12-10AWG(4-6mm2)	Fully	105°C/300V	Nylon	Male



Wire range A. W. G. mm ²	Item No.	NEMA TAB	DIMENSION ^{Inch} / _{mm}						
			W	F	L	B	D	T	
22-16A. W. G. 0.5-1.5mm ²	FDFV1-250	0.32x.250 (0.8x6.35)	.260 6.6	.287 7.3	.866 22.0	.413 10.5	.154 3.9	.016 0.4	
16-14A. W. G. 1.5-2.5mm ²	FDFV2-250	0.32x.250 (0.8x6.35)	.260 6.6	.287 7.3	.866 22.0	.413 10.5	.177 4.5	.016 0.4	
12-10A. W. G. 1.5-2.5mm ²	FDFV5-250	0.32x.250 (0.8x6.35)	.260 6.6	.287 7.3	.957 24.3	.492 12.5	.217 5.5	.016 0.4	

Part No.	Product No.	Description	Insulation Color	Size L*W*C*D	Cable No.	Fully / Half	°C/Volt/A	Insulation Material	Type
7828	FDFV1-250	VINYL-Fully Insulated Female Disconnecter	RED	22*6.6*1.7mm	22-16 AWG 0.5-1.5mm2	Fully	75°C/300V	Vinyl-Fully	Female
7827	FDFV2-250	VINYL-FULLY INSULATED FEMALE DISCONNECTORS	Blue	22*6.6*2.3mm	16-14AWG(1.5-2.5mm2)	Fully	75°C/300V	Vinyl-Fully	Female
9105	FDFV5-250	75°C VINYL-FULLY INSULATED FEMALE DISCONNECTORS 10AWG 24A	Yellow	24.3*6.6*3.4mm	12-10AWG(4-6mm2)	Fully	75°C/300V/24A	Vinyl	Female



- Maximum electrical rating: 105°C 600VOLTS MAX
- Insulation material: Nylon
- Terminal material: copper



Part No.	Product No.	Manufacturer	Description	Insulation Color	Size L*W*C*D	Cable No.	Fully / Half	°C/Volt/A	Insulation Material
41489	RNYS2-4	KST	INSULATION MATERIAL: NYLON	BLUE	2 0.4*6.6*4.5mm2	16-14AWG	Half	150°C	NYLON

