




Vinyl, Nylon Insulated Male+ Female Disconnect




Detailed product specifications are available on: us.100y.com.tw

Wire range A. W. G. mm ²	Item No.	NEMA TAB	DIMENSION ^{Inch} mm						
			W	F	L	B	D	T	
22-16A. W. G. 0.5-1.5mm ²	MDV1-110(5)	0.20x.110 (0.5x2.8)	.110 2.8	.256 6.5	.728 18.5	.394 10.0	.157 4.0	.012 0.3	
	MDV1-187(5)	0.20x.187 (0.5x4.75)	.189 4.8	.256 6.5	.748 19.0				.020 0.5
	MDV1-250	0.32x.250 (0.8x6.35)	.250 6.35	.303 7.7	.827 21.0				
16-14A. W. G. 1.5-2.5mm ²	MDV2-187(5)	0.20x.187 (0.5x4.75)	.189 4.8	.256 6.5	.748 19.0	.394 10.0	.177 4.5	.012 0.3	
	MDV2-250	0.32x.250 (0.8x6.35)	.250 6.35	.303 7.7	.748 19.0				.016 0.4
12-10A. W. G. 4-6mm ²	MDV5-250	0.32x.250 (0.8x6.35)	.250 6.35	.303 7.7	.925 24.0	.512 13.0	.217 5.5	.016 0.4	

Part No.	Product No.	Description	Insulation Color	Size L*W*C*D	Cable No.	Fully/ Half	°C/Volt/A	Insulation Material	Type
12967	MDV1-110(5)	VINYL-FULLY INSULATED FEMALE DISCONNECTORS	RED	18.5*2.8mm	22-16AWG(0.5-1.5mm2)	Half	75°C	Vinyl	Male
12963	MDV1-187(5)	VINYL-FULLY INSULATED MALE DISCONNECTORS	RED	19*4.8mm	22-16AWG(0.5-1.5mm2)	Half	75°C	Vinyl	Male
8296	MDV1-250	VINYL-Insulated Male Disconnecter	RED	21*6.35mm	22-16AWG(0.5-1.5mm2)	Half	75°C	Vinyl	Male
12965	MDV2-187(5)	VINYL-FULLY INSULATED MALE DISCONNECTORS	BLUE	19*4.8	16-14AWG(1.5-2.5mm2)	Half	75°C	Vinyl	Male
11183	MDV2-250	VINYL-INSULATED DOUBLE CRIMP FEMALE DISCONNECTORS	Blue	21*6.35mm	16-14AWG(1.5-2.5mm2)	Half	75°C	Vinyl	Male
10741	MDV5-250	VINYL Insulated Male Disconnecter	Yellow	24*6.35mm	12-10AWG(4-6mm2)	Half	75°C	Vinyl	Male

Vinyl, Nylon-Insulated Flange Spade Terminals




Detailed product specifications are available on: us.100y.com.tw

Wire range A. W. G. mm ²	ITEM NO.		Stud size d2	DIMENSION ^{Inch} mm								
	Brazed seam	Butted seam		W	F	L	E	D	d1	A	T	
22-16A. W. G. 0.5-1.5mm ²	FSVB1-4	FSV1-4	#8	.169 4.3	.295 7.5	.201 5.1	.748 19.0	.394 10.0	.157 4.0	.067 1.7	.059 1.5	.030 0.75
	FSVB1-5	FSV1-5	#10	.209 5.3	.295 7.5	.201 5.1	.748 19.0					
16-14A. W. G. 1.5-2.5mm ²	FSVB2-4	FSV2-4	#8	.169 4.3	.295 7.5	.205 5.2	.768 19.5	.394 10.0	.177 4.5	.091 2.3	.059 1.5	.031 0.8

Part No.	Product No.	Description	Insulation Color	SizeL*W*d2	Cable No.	Fully / Half	°C/Volt/A	Insulation Material
4913	FSV1-4	VINYL-Insulated Flange Spade Terminals	RED	19*7.5*#8	22-16AWG(0.5-1.5mm2)	Half	75°C	VINYL
4912	FSV1-5	VINYL-Insulated Flange Spade Terminals	RED	19*7.5*#10	22-16AWG(0.5-1.5mm2)	Half	75°C	VINYL
2963	FSV1-5	VINYL-Insulated Flange Spade Terminals	RED	19*7.5*#10	22-16AWG(0.5-1.5mm2)	Half	75°C	VINYL
4914	FSV2-4	VINYL-Insulated Flange Spade Terminals	BLUE	19.5*7.5*#8	16-14AWG(1.5-2.5mm2)	Half	75°C	VINYL

Vinyl, Nylon-Insulated Spade Terminals



Detailed product specifications are available on: us.100y.com.tw

Wire range A. W. G. mm ²	ITEM NO.		Stud size d2	DIMENSION ^{Inch} mm							
	Brazed seam	Butted seam		W	F	L	E	D	d1	T	
22-16A. W. G. 0.5-1.5mm ²	SVBS1-3.7	SVS1-3.7	#6	.146 3.7	.323 8.2	.256 6.5	.827 21.0	.394 10.0	.157 4.0	.067 1.7	.030 0.75
	SVBM1-4	SVM1-4	#8	.169 4.3	.283 7.2						
	SVBL1-5	SVL1-5	#10	.209 5.3	.374 9.5						
16-14A. W. G. 1.5-2.5mm ²	SVBS2-3.7	SVS2-3.7	#6	.146 3.7	.224 5.7	.256 6.5	.827 21.0	.394 10.0	.177 4.5	.091 2.3	.031 0.8
	SVBM2-4	SVM2-4	#8	.169 4.3	.283 7.2						
	SVBL2-5	SVL2-5	#10	.209 5.3	.366 9.3						
12-10A. W. G. 4-6mm ²	SVB5-5	SV5-5	#10	.209 5.3	.283 7.2	.276 7.0	1.004 25.5	.512 13.0	.248 6.3	.134 3.4	.039 1.0
	SVBL5-6	SVL5-6	1/4	.252 6.4	.472 12.0	.472 12.0	1.240 31.5				

Part No.	Product No.	Description	Insulation Color	Size L*W*d2	Cable No.	Fully / Half	°C/Volt/A	Insulation Material
4910	SV5-5	VINYL-Insulated Spade Terminals	YELLOW	25.5*9*#10	12-10AWG(4-6mm2)	Half	75°C	VINYL
4908	SVL1-5	VINYL-Insulated Spade Terminals	RED	21*9.5*#10	22-16AWG(0.5-1.5mm2)	Half	75°C	VINYL
4909	SVL2-5	VINYL-Insulated Spade Terminals	BLUE	21*9.3*#10	16-14AWG(1.5-2.5mm2)	Half	75°C	VINYL
4911	SVL5-6	VINYL-Insulated Spade Terminals	YELLOW	31.5*12*1/4	12-10AWG(4-6mm2)	Half	75°C	VINYL
4907	SVM1-4	VINYL-Insulated Spade Terminals	RED	21*7.2*#8	22-16AWG(0.5-1.5mm2)	Half	75°C	VINYL
4260	SVM2-4	VINYL-Insulated Spade Terminals	BLUE	21*7.2*#8	16-14AWG(1.5-2.5mm2)	Half	75°C	VINYL
17751	SVM2-4-YELLOW	VINYL-Insulated Spade Terminals	YELLOW	21*7.2*#8	16-14AWG(1.5-2.5mm2)	Half	75°C	VINYL
5626	SVS1-3.7	VINYL-Insulated Spade Terminals	RED	21*5.7*#6	22-16AWG(0.5-1.5mm2)	Half	75°C	VINYL
4286	SVS2-3.7	VINYL-Insulated Spade Terminals	BLUE	21*5.7*#6	16-14AWG(1.5-2.5mm2)	Half	75°C	VINYL

