




Uninsulated Male/Female Disconnect

Detailed product specifications are available on: us.100y.com.tw




Wire range A. W. G. mm ²	ITEM NO.	DIMENSION mm				
		W	F	L	B	C
22-16A. W. G. 0.5-1.5mm ²	FDN1-110(5)	3.86	6.32	13.6	5.21	1.7
	FDN1-187(5)	5.0	6.4	15	5.0	1.7
	FDN1-250	6.6	7.3	16	5.2	1.7
16-14A. W. G. 1.5-2.5mm ²	FDN2-110(5)	3.2	6.5	13.6	5.14	2.3
	FDN2-187(5)	5.0	6.4	15	5.06	2.3
	FDN2-250	5.0	6.4	16	5.06	2.3

Part No.	Product No.	Description	Material	Size L*W	Cable No.	Type
8766	FDN1-110(5)	Uninsulated Female Disconnect	Copper	W3.2	22-16AWG(0.5-1.5mm2)	Female
7944	FDN1-187(5)	Uninsulated Female Disconnect	Copper	W5.0mm	22-16AWG(0.5-1.5mm2)	Female
4263	FDN1-250	Uninsulated Female Disconnect	Copper	W6.6mm	22-16AWG(0.5-1.5mm2)	Female
12181	FDN2-110(5)	Uninsulated Female Disconnect	Copper	W3.2mm	16-14AWG(1.5-2.5mm2)	Female
7832	FDN2-187(5)	Uninsulated Female Disconnect	Copper	W5.0mm	16-14AWG(1.5-2.5mm2)	Female
7830	FDN2-250	Uninsulated Female Disconnect	Copper	W6.6mm	16-14AWG(1.5-2.5mm2)	Female

Uninsulated Flange Spade Terminal

Detailed product specifications are available on: us.100y.com.tw



Wire range A. W. G. mm ²	ITEM NO.		STUD SIZE		DIMENSION Inch mm						
	BRAZED SEAM	BUTTED SEAM	d2	W	F	L	E	D	d1	T	
22-16A. W. G. 0.5-1.5mm ²	SNBS1-3.7	SNS1-3.7	#6	.146 3.7	.323 5.7	.256 6.5	.630 16.0	.189 4.8	.134 3.4	.067 1.7	.030 0.75
	SNBM1-4	SNM1-4	#8	.169 4.3	.283 7.2						
	SNBL1-5	SNL1-5	#10	.209 5.3	.374 9.5						
16-14A. W. G. 1.5-2.5mm ²	SNBS2-3.7	SNS-3.7	#6	.146 3.7	.224 5.7	.256 6.5	.630 16.0	.189 4.8	.161 4.1	.091 2.3	.031 0.8
	SNBM2-4	SNM2-4	#8	.169 4.3	.283 7.2						
	SNBL2-5	SNL2-5	#10	.209 5.3	.366 9.3						
14-12A. W. G. 2.5-4mm ²	SNB3-4	SN3-4	#8	.169 4.3	.315 8.0	.276 7.0	.720 18.3	.236 6.0	.199 5.0	.188 3.0	.039 1.0
	SNB3-5	SN3-5	#10								
12-10A. W. G. 4-6mm ²	SNBL5-4	SNL5-4	#8	.169 4.3	.354 9.0	.276 7.0	.728 18.5	.236 6.0	.220 5.6	.134 3.4	.039 1.0
	SNBL5-5	SN5-5	#10	.209 5.3	.354 9.0						
	SNBL5-6	SN5-6	1/4	.252 6.4	.472 12.0						

Part No.	Product No.	Description	Material	L*W*D*d1*d2 (mm)	Cable No.	Ampere
8299	SNB3-4	Uninsulated Flange Spade Disconnect	Copper	18.3*8.0*5.0*3.0*4.3	14-12AWG(2.5-4mm2)	37A
10481	SNB3-5	Uninsulated Flange Spade Disconnect	Copper	18.3*8.0*5.0*3.0*5.3	14-12AWG(2.5-4mm2)	37A
4265	SNB5-5	Uninsulated Flange Spade Disconnect	Copper	18.5*9.0*5.6*3.4*5.3	12-10AWG(4-6mm2)	48A
10482	SNBL1-5	Uninsulated Flange Spade Disconnect	Copper	16*9.5*3.4*1.7*5.3	22-16AWG(0.5-1.5mm2)	19A
7988	SNBL2-5	Uninsulated Flange Spade Disconnect	Copper	16*9.3*4.1*2.3*5.3	16-14AWG(1.5-2.5mm2)	27A
10455	SNBL5-4	Uninsulated Flange Spade Disconnect	Copper	18.5*9.0*5.6*3.4*4.3	12-10AWG(4-6mm2)	48A
7954	SNBL5-6	Uninsulated Flange Spade Disconnect	Copper	24.5*12*5.6*3.4*6.4	12-10AWG(4-6mm2)	48A
5520	SNBM1-4	Uninsulated Flange Spade Disconnect	Copper	16*7.2*3.4*1.7*4.3	22-16AWG(0.5-1.5mm2)	19A
8301	SNBM2-4	Uninsulated Flange Spade Disconnect	Copper	16*7.2*4.1*2.3*4.3	16-14AWG(1.5-2.5mm2)	27A
5623	SNBS1-3.7	Uninsulated Flange Spade Disconnect	Copper	16*5.7*3.4*1.7*3.7	22-16AWG(0.5-1.5mm2)	19A
2861	SNBS2-3.7	Uninsulated Flange Spade Disconnect	Copper	16*5.7*4.1*2.3*3.7	16-14AWG(1.5-2.5mm2)	27A
17829	Y1.25-4	Uninsulated Flange Spade Disconnect			22-16AWG	
17830	Y2-4	Uninsulated Flange Spade Disconnect			16-14AWG	
17831	Y3.5-5	Uninsulated Flange Spade Disconnect			14-12AWG	
17880	Y5.5-5	Uninsulated Flange Spade Disconnect			12-10AWG	
17932	Y8-5	Uninsulated Flange Spade Disconnect		24*12*5.3	8AWG(10mm)	

