




Uninsulated Ring Terminal- Eyelets

Detailed product specifications are available on: us.100y.com.tw




Item NO.	Stud size	L*W*D*d1*d2 (mm)	Wire size	
			AWG	mm ²
R80-12	13mm	24.5*23*24*19*13	3/0	95
R100-12	13mm	21*28.5*21*17*12.5	4/0	120
R125-12	13mm	24.5*23*24*19*13	--	--

Part No.	Product No.	Description	L*W*D*d1*d2 (mm)	Cable No.
15089	R100-12	Uninsulated Ring Terminal	21*28.5*21*17*12.5	4AWG/120mm ²
15090	R125-12	Uninsulated Ring Terminal	24.5*23*24*19*13	
31275	R2-6	Uninsulated Ring Terminal		16-14AWG/1.5-2.5mm ²
15088	R80-12	Uninsulated Ring Terminal	21*22*18.5*15*13	3/0AWG/95mm ²



Wire range A. W. G. mm ²	ITEM NO.		STUD SIZE		DIMENSION ^{Inch} / _{mm}						
	BRAZED SEAM	BUTTED SEAM	d2		W	F	L	E	D	d1	T
22-16A. W. G. 0.5-1.5mm ²	RNBS1-3.7	RNS1-3.7	#6	.146 3.7	.216 5.5	.197 5.0	.492 12.5	.189 4.8	.134 3.4	.067 1.7	.030 0.75
	RNBL1-4	RNL1-4	#8	.169 4.3	.315 8.0	.276 7.0	.622 15.8				
	RNB1-5	RN1-5	#10	.209 5.3	.252 6.4	.433 11.0	.858 21.8				
	RNB1-6	RN1-6	1/4	.457 11.6	.433 11.0	.858 21.8					
16-14A. W. G. 1.5-2.5mm ²	RNBS2-3.7	RNS2-3.7	#6	.146 3.7	.260 6.6	.189 4.8	.504 12.8	.189 4.8	.161 4.1	.091 2.3	.031 0.8
	RNBL2-4	RNL2-4	#8	.169 4.3	.335 8.5	.307 7.8	.661 16.8				
	RNBS2-5	RNS2-5	#10	.209 5.3							
14-12A. W. G. 2.5-4mm ²	RNB3-4	RN3-4	#8	.169 4.3	.315 8.0	.303 7.8	.709 18.0	.236 6.0	.201 5.1	.114 2.9	.039 1.0
	RNBS3-5	RNS3-5	#10	.209 5.3							
12-10A. W. G. 4-6mm ²	RNBL5-4	RNL5-4	#8	.169 4.3	.374 9.5	.358 9.1	.772 19.6	.236 6.0	.220 5.6	.134 3.4	.039 1.0
	RNB5-5	RN5-5	#10	.209 5.3							
	RNB5-8	RN5-8	5/16	.331 8.4	.591 15.0	.531 13.5	1.063 27.0				
8A. W. G. 8mm ²	RNBS8-6		1/4	.252 6.4	.472 12.0	.366 9.3	.937 23.8	.337 8.5	.283 7.2	.177 4.5	.047 1.2
4A. W. G. 22mm ²	RNB22-10		3/8	.413 10.5	.650 16.5	.531 13.5	1.319 33.5	.472 12.0	.453 11.5	.303 7.7	.067 1.7

Part No.	Product No.	Description	Ampere	L*W*D*d1*d2 (mm)	Cable No.	Material
10471	RNB1-5	Uninsulated Ring Terminal	19A	15.8*8.0*3.4*1.7*5.3	22-16AWG(0.5-1.5mm ²)	Copper
11199	RNB1-6	Uninsulated Ring Terminal	19A	21.8*11.6*3.4*1.7*6.4	22-16AWG(0.5-1.5mm ²)	Copper
16616	RNB14-8	Uninsulated Ring Terminal	88A	14.2*16.0*9*5.65*8.4	6AWG(14mm ²)	Copper
12290	RNB22-10	Uninsulated Ring Terminal	115A	33.5*16.5*11.5*7.7*10.5	4AWG(22mm ²)	Copper
10473	RNB3-4	Uninsulated Ring Terminal	37A	18*8.0*5.1*2.9*4.3	14-12AWG(2.5-4mm ²)	Copper
2860	RNB5-5	Uninsulated Ring Terminal	48A	19.6*9.5*5.6*3.4*5.3	12-10AWG(4-6mm ²)	Copper
10475	RNB5-8	Uninsulated Ring Terminal	48A	27*15*5.6*3*4*8.4	12-10AWG(4-6mm ²)	Copper
35272	RNB8-8	Uninsulated Ring Terminal	62A	29.2*15*7.2*4.5*8.4	8AWG(8mm ²)	Copper
4546	RNBL1-4	Uninsulated Ring Terminal	19A	15.8*8.0*3.4*1.7*4.3	22-16AWG(0.5-1.5mm ²)	Copper
10453	RNBL2-4	Uninsulated Ring Terminal	27A	16.8*8.5*4.1*2.3*4.3	16-14AWG(1.5-2.5mm ²)	Copper
4267	RNBL5-4	Uninsulated Ring Terminal	48A	19.6*9.5*5.6*3*4*4.3	12-10AWG(4-6mm ²)	Copper
4269	RNBS1-3.7	Uninsulated Ring Terminal	19A	12.5*5.5*3.4*1.7*3.7	22-16AWG(0.5-1.5mm ²)	Copper
2859	RNBS2-3.7	Uninsulated Ring Terminal	27A	12.8*6.6*4.1*2.3*3.7	16-14AWG(1.5-2.5mm ²)	Copper
7942	RNBS2-5	Uninsulated Ring Terminal	27A	16.8*8.5*4.1*2.3*5.3	16-14AWG(1.5-2.5mm ²)	Copper
10474	RNBS3-5	Uninsulated Ring Terminal	37A	18*8.0*5.1*2.9*5.3	14-12AWG(2.5-4mm ²)	Copper
11867	RNBS8-6	Uninsulated Ring Terminal	62A	23.8*12*7.2*4.5*5.3	8AWG(8mm ²)	Copper



Wire range A. W. G. mm ²	ITEM NO.	STUD SIZE		DIMENSION ^{Inch} / _{mm}						
	BRAZED SEAM	d2		W	F	L	E	D	d1	T
4A. W. G. 25mm ²	SQNBS22-5	#10	.209 5.3	.492 12.5	.531 13.5	1.260 32.00	.472 12.5	.453 11.5	.303 7.7	.067 1.7

Part No.	Product No.	Description	L*W*D*d1*d2 (mm)	Cable No.	Material
14235	SQNBS22-5	NON-INSULATED SQUARE TONGUE TERMINALS	13.5*12.5mm	4AWG	COPPER

