



DC Axial Fan

Detailed product specifications are available on: us.100y.com.tw



Volt	5V
r. p. m	12000
Current (A)	0. 18A
Watts	0. 9
Air Flow (CFM)	0. 9
Noise (dBA)	34
Ball/Sleeve	Ball



Part No.	Product No.	Manufacturer	Description	Size(mm)	Volt.	r.p.m	Current(A)	Watts	Air Flow(CFM)	Noise (dBA)	Ball/Sleeve
16837	B0502AFB1-8	SUNON	"SUNON" 5VDC Axial Fan	25*25*10	5V	12000	0.18A	0.9	0.9	34	Ball



Volt	5V
r. p. m	9000
Current (A)	0. 19A
Watts	0. 95
Air Flow (CFM)	1. 2
Noise (dBA)	31
Ball/Sleeve	Ball



Part No.	Product No.	Manufacturer	Description	Size(mm)	Volt.	r.p.m	Current(A)	Watts	Air Flow(CFM)	Noise (dBA)	Ball/Sleeve
16838	B0503AFB1-8	SUNON	"SUNON" 5VDC Axial Fan	30*30*10	5V	9000	0.19A	0.95	1.2	31	Ball



- Dimentions: 80x80x25. 4mm
- Weight: 71. 5g
- Air flow: 34CFM
- Rated voltage: DC12V (24V also available)
- Input current: 0. 20A
- Input power: 2. 4W
- Static pressure: 0. 12 (inch-H2O)
- Noise level: 30dBA
- Housing: thermoplastic UL94V-0 PBT PCB UL standard 95HB
- Lead wire: AWG #26. UL1007
- Bearing: sleeve bearing (ball bearing also available)

- Insulation resistance: 10M ohm at 500V DC between lead wire (+) and frame
- Dielectric withstand: 5mA max. at 500V Ac for 1 min between lead wire (+) and frame
- Speed: middle-2600RPM±10%
- Life expectancy: 5000 hours at 25°C (ball bearing) 2000 hours at 25°C (sleeve bearing)
- Operating temperature: satisfies specifications after exposure (10°C~65°C)
- Storage temperature: -30°C +70°C for 100 hours returns to normal room temperature for 24 hours
- Above measurement apply at 25°C +/-5°C relative humidity 65% +/-15% (RH)


Part No.	Product No.	Description	Size(mm)	Volt.	r.p.m	Current(A)	Watts	Air Flow(CFM)	Noise (dBA)	Ball/Sleeve
38996	D08G4500-6	UV LED FAN-Orange	80*80*25.4mm	DC12V	2600	0.2A	2.4W	34	30	Sleeve
38997	D08G4501-6	UV LED FAN-Blue	80*80*25.4mm	DC12V	2600	0.2A	2.4W	34	30	Sleeve
38998	D08G4503-6	UV LED FAN-Green&Blue	80*80*25.4mm	DC12V	2600	0.2A	2.4W	34	30	Sleeve
38999	D08G4506-6	UV LED FAN-Orange&Green	80*80*25.4mm	DC12V	2600	0.2A	2.4W	34	30	Sleeve
39000	D08G4508-6	UV LED FAN-Blue&Orange	80*80*25.4mm	DC12V	2600	0.2A	2.4W	34	30	Sleeve



Volt	5V	12V	12V
r. p. m	4500	5500	4500
Current (A)	0. 14	0. 06	0. 04
Watts	0. 70	0. 72	0. 48
Air Flow (CFM)	5. 2	5	3. 36
Noise (dBA)	14	19	14
Ball/Sleeve	Sleeve	Sleeve	Sleeve



DIMENSIONS: 40X40X10.5(mm)



Part No.	Product No.	Manufacturer	Description	Size(mm)	Volt.	r.p.m	Current(A)	Watts	Air Flow(CFM)	Noise (dBA)	Ball/Sleeve
1783	DF0504SM-4P*2-320mm	Dynaeon	5VDC Axial Fan	40*40*10.5	5V	4500	0.14	0.70	5.2	14	Sleeve
8756	DF1204SM-4P*2-320mm	Dynaeon	12VDC Axial Fan + 4P Plug	40*40*10.5mm	12V	4500	0.04	0.48	3.36	14	Sleeve
14725	DF124010PH-A	Dynaeon	12VDC Axial Fan +Pins	40*40*10.5	12V	5500	0.06	0.72	5	19	Ball

PERFORMANCE CURVE:




FEATURES

- Housing: thermoplastic UL94V-0 P. B. T.
- P. C. B. : UL standard 95HB
- Lead wire: AWG #24. UL1007, 300mm Length
- Bearing: ball bearing & sleeve bearing
- Insulation resistance: 10M ohm at 500V DC between lead wire (+) and frame
- Dielectric withstand: 5mA max. at 500V AC for 1 min. between lead wire (+) and frame
- Life expectancy: 50, 000 hours at 25°C. ball bearing 20, 000 hours at 25°C sleeve bearing
- Operating temperature: fan satisfy their specification after exposure (-10°C~65°C)
- Storage temperature: -30°C~+70°C for 100 hours and returned to normal room temperature for 24 hours.
- Above measurements apply at 25°C±5°C reiative humidity 65%±15% (RH)



DIMENSIONS: 80X80X25.4 (mm)



Part No.	Product No.	Manufacturer	Description	Size(mm)	Volt.	r.p.m	Current(A)	Watts	Air Flow(CFM)	Noise (dBA)	Ball/Sleeve
902	DF1208SL-4P*2-540mm	Dynaeon	12VDC Axial Fan With 4P Plug	80*80*25.4mm	12V	2200	0.12	1.44	28	24	Sleeve
6815	DF1208SM-1	Dynaeon	12VDC Axial Fan + Temperature Indicator	80*80*25.4mm	12V	2600	0.15	1.92	34	30	Sleeve
8429	DF1208SM-3	Dynaeon	12VDC Axial Fan +2.54Pin	80*80*25.4mm	12V	2600	0.15	1.68	34	30	Sleeve



T E L : Taiwan: 886-3-5753170
 F A X : Taiwan: 886-3-5753172
 E-mail : Taiwan: us_sale@100y.com.tw

Shenzhen: 86-755-83298787
 Shenzhen: 86-755-83640655
 Shenzhen: 100y@163.com

Shanghai: 86-21-54151736
 Shanghai: 86-21-64605107
 Shanghai: 100y-1@163.com