



FIRE & SECURITY & CCTV

Intruder Alarm Panels/Systems Wireless Alarm With Solar Bell Box

Detailed product specifications are available on: us.100y.com.tw



Motion detector with security Alarm & outdoor siren
● 120dB high output external

6230



Detector motion and activates alarm
Built-in Alarm up to 105dB
Programmable for
-up to 6 digit security code
-Alarm timing 30, 60 and 90 seconds
-Entry delay timing 20, 10 and instant alarm
-9V battery operation with DC adaptor jack

6231

Part No.	Product No.	Description
41141	6230	Motion Detector With Security Alarm & Outdoor Siren(515SK)
41140	6231	Motion Detector With Security Alarm (135A)



- Suitable range: family, factory, company, office...etc
- DIY design, no wiring, only 2 second setting time
- You needn't remove crust if you want change your code
- 100dB high out put external

Part No.	Product No.	Description
14040	CP2	Wireless Alarm With Solar Bell Box

Alarm switches

Detailed product specifications are available on: us.100y.com.tw



1. Open the battery cover in alarm unit to install a 12V battery (make sure the polarity is correct to the battery marking)
2. Stick the alarm unit (large unit) to the door/window frame by attached double-side tape
3. Stick the sensor unit (smaller unit) to the window/door by attached double-side type and make sure to align the arrow mark to the arrow on the battery cover of large unit Fig. 1
Note: the product featured with convertible sensor for either right or left hand side to the alarm unit (factory preset at right hand side) to convert to left hand side.
 - Open the battery cover by sliding it down
 - Pull out the "reed switch box" to the right or battery
 - Place the "reed switch box" to the left of battery and be firmly fixed in position Fig. 2
4. Turn switch to ON position, now unit is standby to work
To replace battery when alarm sounds weak

Part No.	Product No.	Description
14939	6308	Wireless Door Alarm

Detectors Smoke Detector

Detailed product specifications are available on: us.100y.com.tw



SPECIFIC

- Operating voltage: DC 9V
- Operating temperature: -10°C~50°C
- Power consume: ≤3W
- Opposite humidity: <95%

Part No.	Product No.	Description
17253	GAS	Gas Detector

Passive Infra-red

Detailed product specifications are available on: us.100y.com.tw



AUTOMATIC 500W FLOODLIGHT WITH MOVEMENT DETECTOR

- Passive inera-red detector-senses moving heat sources such as people
- Detector activates powerful 500W halogen floodlight
- Built in light sensor-detector will only operate in darkness, avoid wasteful daytime use
- Adjustable swivel heat detector
- Wide detection angle-110° or 180°
- Adjustable detection range-up to 12-15 meter
- L. E. D daylight walk test facility weatherproof

Part No.	Product No.	Description
16035	AC-632	AUTOMATIC 500W FLOODLIGHT WITH MOVEMENT DETECTOR



- Electric source/voltage: AC 110V
- Electric consume: 1W (power off); 15W (power on)
- Environmental brightness: about 10Lux~∞ could adjust
- Environmental temperature: -15°C~40°C
- Weight: about 930g

Part No.	Product No.	Description
15091	GBB-150(JSB-150G)	Automatic 500W Floodlight With Monement Detector

