



FIRE & SECURITY & CCTV

CCTV Monitors

Detailed product specifications are available on: us.100y.com.tw



- Resolution : 800 lines
- Input voltage: AC220V
- Power consumption: 27W
- DOS shell: black/white
- Dimension : 298 (W) x310 (W) x285 (H) mm
- Weight : 9. 6kg

Part No.	Product No.	Description
11196	FS-MT12B	12" B/W Monitor (With Audio)



5.5" B/W Monitir (No Audio)

Part No.	Product No.	Description
40661	HS-BM051	5.5" B/W Monitir (No Audio)

Picture Tube	7"	5 1/2"
Power Source	DC12-28V	
Input Signal/Impedance	1. 0Vp-p/75ohm Composive video signal	
Resolution	More than 700 TV lines	
System	PAL : 625 lines 50 fields/Second NTSC : 525Lines 60 fields/second	
Operating Condition	Temperature : -68°F~+131°F (-20°C~+55°C) Humidity : 30%~90%RH	
Dimensions (LxWxH)	8. 03x5. 94x8. 90 inch	5. 51x5. 24x7. 24 inch
Weight (Ne/Gross)	7. 396/9. 105 lbs	4. 167/4. 85 lbs



- Electrical source : AC96~256V, 60Hz
- Power supply : 28W
- Frequency length : 100Hz~10MHz
- Video gain : 30dB
- Linearity : Horizontal : 15% (max) , Vertical : 10% (max)
- Audio Input Signal (Optional) : 10~150mVp-p
- Audio amplifier (Optional) : 1W/8ohm
- Operating temperature : -10°C to 55°C
- Humidity : 30% to 90%RH
- Dimension : 267mmx220mmx248mm

Part No.	Product No.	Description
24644	HS-BM093-110V	9-Inch Monochrome, High Resolution Monitor(Audio Optional)
24645	HS-BM093-220V	9-Inch Monochrome, High Resolution Monitor(Audio Optional)



Suit voltage : AC96~256V, 60Hz/50Hz

Part No.	Product No.	Description
41000	HS-BM123	12" B/W Monitor(With Audio)



- Electrical source : 240V, 50Hz
- Power supply : 38W
- Frequency length : 100Hz~10MHz
- Video gain : 30dB
- Linearity : Horizontal : 15% (max) , Vertical : 10% (max)
- Audio Input Signal (Optional) : 10~150mVp-p
- Audio amplifier (Optional) : 1W/8ohm
- Operating temperature : -10°C to 55°C
- Humidity : 30% to 90%RH
- Dimension : 305mmx310mmx313mm

Part No.	Product No.	Description
27040	HS-BM151-110V	15" black and white screen



SPECIFICATION

- Resolution : Center : 500 TV lines, Corner : 400 TV lines
- Input signal : 0. 5 to 2. 0 vp-p composite video
- Input impedance : 75 ohm or higher (switch able)
- Video gain : 30dB
- Linearity : Horizontal : 10% (max) , Vertical : 10%
- Video (in/out) : BNC or F connector : Input x1/outputx1
- Audio (in/out) (optional) : RCA : inputx1/outputx1
- Audio input signal : 1vp-p
- Power consumption : 40W
- Dimension : 262 (W) x291. 5 (D) x246 (H) mm
- Operating temperature : -10 to 50°C
- Storage temperature : -20 to 70°C

FEATURE

- Convenient front panel control
- Metal cabinet
- Video looping output
- With optional audio feature
- With carrying handles at top of cabinet
- With full range 96~256C AC power input

Part No.	Product No.	Description
28429	HS-CM105	CCTV Monitors



Beautiful color, suitable for diversified cinematograph

Part No.	Product No.	Description
41678	HS-CM145-N6B	
18806	HS-CM146H	14" Color Monitor

