



# FIRE & SECURITY & CCTV

## CCTV Monitors

Detailed product specifications are available on: [us.100y.com.tw](http://us.100y.com.tw)



### SPECIFICATION

- Suit voltage: AC96~256V, 50Hz/60Hz
- Have seven state control type
- Power source: AC96~256V, 50Hz/60Hz
- Power consumption: 63W
- Video gain: 30dB
- Linearing: Horizontal: 10% (max), Vertical: 10%
- Audio input signal (Optional): 10~150mVp-p
- Audio amplifier (Optional): 1W/8 ohm
- Weight /gross weight: 14kg/15kg
- Dimension D\*W\*H: 400x362x357mm
- Operating temperature: -10°C to 55°C

Part No.	Product No.	Description
23290	HS-CM157A	15" Color Monitor



### SPECIFICATION

- System: EIA or CCIR
- Scanning System: EIA: 15.750Hz±400Hz
- Input signal (Optional): composite video 0.5~2.0Vp-p (BNC)
- Output signal: 1.0Vp-p 75 ohm. loop-through (BNC)
- Resolution: 1000 lines
- Diemension W\*D\*H: 220x60x37mm
- Weight: N. W: 5.8Kg, G. W: 6.4Kg
- Environmental temperature: -10°C~40°C (14°F~104°F)

Part No.	Product No.	Description
14424	KA-093	9" B/W Monitir (No Audio)



### SPECIFICATION

- System: NTSC or PAL
- Scanning system: NTSC: 15.750 Hz±50Hz  
PAL: 15.625Hz±50Hz
- Input signal (Optional): composit video 0.5~2.0Vp-p
- Output signal: 1.0Vp-p 75 ohms, loop-throughs
- Dimension W\*D\*H: 260x93x252mm
- Weight N. M: 7.6Kg, G. W: 8.8Kg
- Environmental temperature: -10°C~40°C (14°F~104°F)

Part No.	Product No.	Description
2775	KA-210C	10" Color Monitor



### SPECIFICATION

- System: NTSC or PAL
- Scanning system: NTSC: 15.750Hz±50Hz  
PAL: 15.625Hz±50Hz
- Input signal (Optional): composit video 0.5~2.0Vp-p (BNC)
- Output signal: 1.0Vp-p 75ohms, loop-throughs (BNC)
- Dimension W\*D\*H: 360x387x351
- Weight N. M: 12.4Kg, G. W: 14.4Kg
- Environmental temperature: -10°C~40°C (14°F~104°F)

Part No.	Product No.	Description
13055	KA-214	14" Color Monitor (No Audio)

## CCTV VCR

Detailed product specifications are available on: [us.100y.com.tw](http://us.100y.com.tw)



### Features for safe recording

- Tap end blue screen indicator  
This function informs the user that recording has stopped by providing a blue screen as soon as Auto Rewind starts when the end of a tape is reached. (ON/OFF switchable)
- Repeat recording frequency indicator

The same tape is often used repeatedly for recording with time-lapse VCRs. With the AG-RT600, the number of times a tape is used is displayed on the LCD. When a tape has been used more than 50 times, the indications flash, alerting the user to change the tape. This helps eliminate problems arising from using a worn tape.

### A variety of recording functions

- Emergency recording  
With the power switch off, or when the unit is set to the stop position, recording automatically starts in 8-hour mode as soon as an external alarm signal is received.

### Alarm recording

When an alarm signal is received during time-lapse recording, the AG-RT600 automatically switches to alarm recording in the 8-hour mode. Alarm search/alarm recall enables a quick search and check of alarm recordings

- Daylight saving time adjustment
- Auto alarm reset
- Daily and weekly timer recording
- External timer recording
- Auto repeat recording/Auto rewind
- 1-week timer backup
- Built-in time/date generator

### Other features

- HR (High-response) Mechanism assures high reliability while offering quick response
- Auto Head cleaning
- Noiseless still and forward/reverse field advance
- On-screen display
- AG-A11 Optional wired remote control
- Dual mode record lock function
- Easy-to-read LCD with backlight and hour meter
- Camera switching output, auto off output and tape end output
- Compact cabinet, only 10 5/8" wide
- Low power consumption.
- Quasi-V insertion ON/OFF

Part No.	Product No.	Manufacturer	Description
11725	AG-RT600	Panasonic	Real Motion Time Lapse Video Cassette Recorder (NTSC)

- We provide various product for your choice and help you develop infinite commercial chance!

[Http://us.100y.com.tw/](http://us.100y.com.tw/)

**Centenary Materials**

Waiting for your phone call



T E L : Taiwan: 886-3-5753170  
F A X : Taiwan: 886-3-5753172  
E-mail: Taiwan: sale@100y.com.tw

Shenzhen: 86-755-83298787  
Shenzhen: 86-755-83640655  
Shenzhen: 100y@163.com

Shanghai: 86-21-54151736  
Shanghai: 86-21-64605107  
Shanghai: 100y-1@163.com