



FIRE & SECURITY & CCTV

Detailed product specifications are available on: us.100y.com.tw

CATV Splitter



1-3 Splitter

Part No.	Product No.	Description	MHz
39619	23431B	1-3 Splitter	5-1000Mhz



- Zinc die-casting housing
- Built-in grounding block
- All ports F female connector, 75Ω
- Two pieces of screws attached
- Frequency range: 5~900MHz

Part No.	Product No.	Description	MHz
10558	244	1-4 High Quality Splitter	5-900MHZ




- Input: 75Ω quick F male
- Output: 300Ω
- Frequency range: 5~900MHz

Part No.	Product No.	Description	MHz
7608	320A	75Ω/300Ω Matching Transformer	




- Input: 75Ωx2
- Output: 75Ω

Part No.	Product No.	Description	MHz
4181	AB-28	Scanner Cable Switch	5~900MHz



STV-1782B
STV-1784



STV-1784B



STV-1786B
STV-1788B

MODEL	FREQUENCY RANGE (MHz)	INSERTION LOSS (dB)	ISOLATION (dB)	RETURN LOSS (dB)	DIMENSION (mm)	WEIGHT (g)
STV-1782B POWER PASS TO ONE PORT	5-47	4.5	11	11	54x58x26	100
	47-1000	4.7	20	12		
	1000-1750	5.3	17	11		
	1750-2050	5.8	16	10		
	2050-2300	6.8	13	10		
STV-1784B POWER PASS TO ONE PORT	5-47	8.5	17	7	76x58x26	135
	47-1000	9	20	12		
	1000-1750	10.5	16	10		
	1750-2050	11	15	10		
	2050-2300	12	13	8		
STV-1786B POWER PASS TO ONE PORT	5-47	12	20	6	120x58x26	186
	47-1000	12	20	10		
	1000-1750	14.5	18	8		
	1750-2050	16	16	10		
	2050-2300	17.5	13	7		

- Zinc die-casting housing, nickle-plated
- All ports F female connector, 75Ω
- Power passing 24VDC 0.5A max
- Built-in two grounding block
- Two pieces of screws attached
- Particularly designed for easy and convenient installation, even thicker 9mm cable

Part No.	Product No.	Description	MHz
12569	STV-1782B	1-2 Satellite Splitter	5-2300MHZ
12570	STV-1784	Satellite Splitter 1-4	5-2050MHZ
14051	STV-1784B	CCTV Directional Tap 1-4	5-2300MHZ
14052	STV-1786B	CCTV Directional Tap 1-6	5-2300MHZ
14053	STV-1788B	CCTV Directional Tap 1-8	5-2300MHZ




STV-2244P



T2342B

Part No.	Product No.	Description	MHz
10738	STV-2244P	1 to 4 Satellite Splitter	5~2300MHz
28330	T2342B	1-2 High Quality Splitter	5~1000MHz



MODEL	FREQUENCY RANGE (MHz)	INSERTION LOSS (dB)	ISOLATION (dB)	RETURN LOSS (dB)	DIMENSION (mm)	WEIGHT (g)
STV-H2246P Power pass To all ports	5-40	12.5	20	3	120x60x24	152
	40-1000	12.5	20	10		
	1000-1750	15	17	8		
	1750-2050	16	16	8		
	2050-2300	18	12	7		

Part No.	Product No.	Description	MHz
10559	STV-H2246P	Satellite Splitter 1-6	5-862MHZ

