




## Wickmann\_TE5 Series Fuses

Detailed product specifications are available on: [us.100y.com.tw](http://us.100y.com.tw)



### SPECIFICATIONS

**Materials**  
 Base/Cap: Brown thermoplastic  
 Polyamide PA 6. 6 UL 94V0  
 Round pins: copper, Sn plated

**Operating temperature**  
 -40°C to +85°C (consider de-rating)

**Climatic category**  
 -40°C/+85°C/21 days (EN 60068-1. 3)

**Stock conditions**  
 +10°C to +60°C  
 relative humidity ≤75% yearly average  
 Without dew, maximum value for 30 days-95%

**Vibration resistance**  
 24 cycles at 15 min. each (IEC 60068-2-6)  
 10-60Hz at 0.75mm amplitude  
 60-2000Hz at 10g acceleration

**Lead pull strength**  
 10N (EN 60068-2-21)

**Solderability**  
 260°C, ≤3sec. (Wave+Reflow)  
 350°C, ≤1sec. (Hand)


**Soldering Heat resistance**  
 260°C, 10sec. (IEC 60068-2-20)

**Unit Weight**  
 0.60 (approx)

Part No.	Product No.	Manufacturer	Description	Amps mA/A	Volt.	Certific
17287	TE5-T-392-1.00A	Wickmann	Wickmann_TE5 Fuse Series Miniature Fuse-Links	1.00A	250V	IEC 60127-3
17291	TE5-T-392-1.25A	Wickmann	Wickmann_TE5 Fuse Series Miniature Fuse-Links	1.25A	250V	IEC 60127-3
27069	TE5-T-392-1.60A	Wickmann	Wickmann_TE5 Fuse Series Miniature Fuse-Links	1.60A	250V	IEC 60127-3
35959	TE5-T-392-2.00A	Wickmann	Wickmann_TE5 Fuse Series Miniature Fuse-Links	2.00A	250V	IEC 60127-3
35961	TE5-T-392-2.50A	Wickmann	Wickmann_TE5 Fuse Series Miniature Fuse-Links	2.50A	250V	IEC 60127-3
17288	TE5-T-392-200mA	Wickmann	Wickmann_TE5 Fuse Series Miniature Fuse-Links	800mA	250V	IEC 60127-3
17544	TE5-T-392-3.15A	Wickmann	Wickmann_TE5 Fuse Series Miniature Fuse-Links	3.15A	250V	IEC 60127-3
35962	TE5-T-392-4.00A	Wickmann	Wickmann_TE5 Fuse Series Miniature Fuse-Links	4.00A	250V	IEC 60127-3

## Wickmann\_MP19398 Series Fuses

Detailed product specifications are available on: [us.100y.com.tw](http://us.100y.com.tw)



### SPECIFICATIONS

**Materials**  
 Base/Cap: Brown thermoplastic  
 Polyamide PA 6. 6 UL 94V0  
 Round pins: copper alloy, tin plated

**Operating temperature**  
 -40°C to +85°C (consider de-rating)

**Climatic category**  
 -40°C/+85°C/21 days (EN 60068-1. 3)

**Stock conditions**  
 +10°C to +60°C  
 relative humidity ≤75% yearly average  
 Without dew, maximum value for 30 days-95%

**Vibration resistance**  
 24 cycles at 15 min. each (IEC 60068-2-6)  
 10-60Hz at 0.75mm amplitude  
 60-2000Hz at 10g acceleration

**Lead pull strength**  
 10N (EN 60068-2-21)

**Solderability**  
 260°C, ≤3sec. (Wave+Reflow)  
 350°C, ≤1sec. (Hand)

**Soldering Heat resistance**  
 260°C, 10sec. (IEC 60068-2-20)

**Unit Weight**  
 0.60 (approx)

### FEATURES

- For worldwide applications
- Reduced PCB space requirements
- Highly defined cut-off times
- Irreversible physical separation
- Low internal resistance
- Flame resistance encapsulated casing



Part No.	Product No.	Manufacturer	Description	Amps	Volt.
10206	MP100	Wickmann	Wickmann_MP19398 Fuse Series Miniature Fuse-Links	1A	65V
27094	MP125	Wickmann	Wickmann_MP19398 Fuse Series Miniature Fuse-Links	1.25A	65V
27076	MP13	Wickmann	Wickmann_MP19398 Fuse Series Miniature Fuse-Links	125mA	65V
27095	MP160	Wickmann	Wickmann_MP19398 Fuse Series Miniature Fuse-Links	1.60A	65V
10205	MP200	Wickmann	Wickmann_MP19398 Fuse Series Miniature Fuse-Links	2A	65V
27077	MP25	Wickmann	Wickmann_MP19398 Fuse Series Miniature Fuse-Links	250mA	65V
10203	MP250	Wickmann	Wickmann_MP19398 Fuse Series Miniature Fuse-Links	2.5A	65V
10207	MP315	Wickmann	Wickmann_MP19398 Fuse Series Miniature Fuse-Links	3.15A	65V
27090	MP32	Wickmann	Wickmann_MP19398 Fuse Series Miniature Fuse-Links	315mA	65V
27089	MP40	Wickmann	Wickmann_MP19398 Fuse Series Miniature Fuse-Links	400mA	65V
27096	MP400	Wickmann	Wickmann_MP19398 Fuse Series Miniature Fuse-Links	4.00A	65V
27091	M P50	Wickmann	Wickmann_MP19398 Fuse Series Miniature Fuse-Links	500mA	65V
27092	MP63	Wickmann	Wickmann_MP19398 Fuse Series Miniature Fuse-Links	630mA	65V
27093	MP80	Wickmann	Wickmann_MP19398 Fuse Series Miniature Fuse-Links	800mA	65V

## Wickmann\_193 Series Fuses

Detailed product specifications are available on: [us.100y.com.tw](http://us.100y.com.tw)



- Material: Glass body/Nickel plated brass caps
- Operating temperature: -55°C to +125°C



Part No.	Product No.	Manufacturer	Description	Amps mA/A	Volt.	Certific
36368	193-1.00A	Wickmann	Wickmann_Fast acting glass tube fuses	1.00A	250V	VDE/SEMKO/cULus/CCC
36369	193-1.25A	Wickmann	Wickmann_Fast acting glass tube fuses	1.25A	250V	VDE/SEMKO/cULus/CCC
36370	193-1.60A	Wickmann	Wickmann_Fast acting glass tube fuses	1.60A	250V	VDE/SEMKO/cULus/CCC
36358	193-100mA	Wickmann	Wickmann_Fast acting glass tube fuses	100mA	250V	VDE/SEMKO/cULus/CCC
36359	193-125mA	Wickmann	Wickmann_Fast acting glass tube fuses	125mA	250V	VDE/SEMKO/cULus/CCC
36360	193-160mA	Wickmann	Wickmann_Fast acting glass tube fuses	160mA	250V	VDE/SEMKO/cULus/CCC

