



Bussmann_MDA Series Fuses

Detailed product specifications are available on: us.100y.com.tw



Description

- Time Delay, ceramic tube
- Optional axial lead available
- 1/4x1-1/4 (6.3mmx32mm) physical size
- Ceramic tube, nickel-plated brass endcap construction
- UL Listed product meets standard 248-14
- RoHS Compliant version available (-R option)




Agency information

- UL Listed Card: MDA 2/10-20A (Guide JDYX, File E19180)
- UL Recognized Card: MDA 25-30A (Guide JDYX2, File E 19180)
- CSA Certification Card: MDA 2/10-15 (Class No, 1422-01)

Environmental Data

- Shock: 1/100A and 8/10A-MIL-STD-202, Method 213, Test Condition I; 1A thru 30A-MIL-STD-202, Method 207, (HI Shock)
- Vibration: 1/100A and 8/10A-MIL-STD-202, Method 201; 1/4A thru 30A-MIL-STD-202, Method 204, Test Condition C (Except 5g, 500HZ)



Part No.	Product No.	Manufacturer	Description	Current (A)	Working Volt.
39125	MDA-12	Bussmann	MDA Series, Time Delay, Ceramic Tube		250V
39274	MDA-30A	Bussmann	Time Delay, Ceramic Tube	30A	250V

Bussmann_LPJ_SP Series Fuses


Detailed product specifications are available on: us.100y.com.tw



General Information

- True dual-element fuse with a minimum 10 second time-delay at 500% overload
- Long time-delay minimizes needless fuse opening due to temporary overloads and transient surges
- Can often be sized for back-up protection against motor burnout from overload or single-phasing if other overload protective devices fail
- High interrupting rating to safely interrupt overcurrents up to 300,000A
- High degree of current limitation due to the fast speed-of-response to short-circuits
- Faster response to damaging short-circuit currents than mechanical overcurrent protective devices
- Reduces let-through thermal and magnetic forces in order to protect low withstand rated components
- Proper sizing provides "no damage" type "2" coordinated protection for NEMA and IEC motor control in accordance with IEC Standard 947-1
- Dual-element fuses have lower resistance than ordinary fuses so they run cooler
- Lower watts loss reduces power consumption
- Unique dimensions assure that another class of fuse with a lesser voltage rating, interrupting rating or current-limiting ability cannot be substituted
- Space-saving package for equipment down sizing

- Ampere Rating: 1 to 60A
- Voltage Rating: 600Vac (or less) 300Vdc (or less)
- Interrupting Rating: 300,000A RMS Sym. (UL)
100,000A dc



Part No.	Product No.	Manufacturer	Description	Current (A)	Working Volt.	IR (A)
27718	LPJ-1.25SP	Bussmann	LOW-PEAK Dual-Element Time-Delay Fuse	1.25A	600V	300kA AC, 100kA DC
27719	LPJ-1.6SP	Bussmann	LOW-PEAK Dual-Element Time-Delay Fuse	1.6A	600V	300kA AC, 100kA DC
27720	LPJ-1.8SP	Bussmann	LOW-PEAK Dual-Element Time-Delay Fuse	1.8A	600V	300kA AC, 100kA DC
27735	LPJ-10SP	Bussmann	LOW-PEAK Dual-Element Time-Delay Fuse	10A	600V	300kA AC, 100kA DC
27736	LPJ-12SP	Bussmann	LOW-PEAK Dual-Element Time-Delay Fuse	12A	600V	300kA AC, 100kA DC
27737	LPJ-15SP	Bussmann	LOW-PEAK Dual-Element Time-Delay Fuse	15A	600V	300kA AC, 100kA DC
27754	LPJ-17.5SP	Bussmann	LOW-PEAK Dual-Element Time-Delay Fuse	17.5A	600V	300kA AC, 100kA DC
27717	LPJ-1SP	Bussmann	LOW-PEAK Dual-Element Time-Delay Fuse	1A	600V	300kA AC, 100kA DC
27722	LPJ-2.25SP	Bussmann	LOW-PEAK Dual-Element Time-Delay Fuse	2.25A	600V	300kA AC, 100kA DC
27723	LPJ-2.5SP	Bussmann	LOW-PEAK Dual-Element Time-Delay Fuse	2.5A	600V	300kA AC, 100kA DC
27724	LPJ-2.8SP	Bussmann	LOW-PEAK Dual-Element Time-Delay Fuse	2.8A	600V	300kA AC, 100kA DC
27755	LPJ-20SP	Bussmann	LOW-PEAK Dual-Element Time-Delay Fuse	20A	600V	300kA AC, 100kA DC
27756	LPJ-25SP	Bussmann	LOW-PEAK Dual-Element Time-Delay Fuse	25A	600V	300kA AC, 100kA DC
27721	LPJ-2SP	Bussmann	LOW-PEAK Dual-Element Time-Delay Fuse	2A	600V	300kA AC, 100kA DC
27726	LPJ-3.2SP	Bussmann	LOW-PEAK Dual-Element Time-Delay Fuse	3.2A	600V	300kA AC, 100kA DC
27727	LPJ-3.5SP	Bussmann	LOW-PEAK Dual-Element Time-Delay Fuse	3.5A	600V	300kA AC, 100kA DC
13019	LPJ-30SP	Bussmann	LOW-PEAK Dual-Element Time-Delay Fuse	30A	600V	200kA AC, 100kA DC
27757	LPJ-35SP	Bussmann	LOW-PEAK Dual-Element Time-Delay Fuse	35A	600V	300kA AC, 100kA DC
27725	LPJ-3SP	Bussmann	LOW-PEAK Dual-Element Time-Delay Fuse	3A	600V	300kA AC, 100kA DC
27729	LPJ-4.5SP	Bussmann	LOW-PEAK Dual-Element Time-Delay Fuse	4.5A	600V	300kA AC, 100kA DC
27758	LPJ-40SP	Bussmann	LOW-PEAK Dual-Element Time-Delay Fuse	40A	600V	300kA AC, 100kA DC
27759	LPJ-45SP	Bussmann	LOW-PEAK Dual-Element Time-Delay Fuse	45A	600V	300kA AC, 100kA DC
27728	LPJ-4SP	Bussmann	LOW-PEAK Dual-Element Time-Delay Fuse	4A	600V	300kA AC, 100kA DC
27731	LPJ-5.6SP	Bussmann	LOW-PEAK Dual-Element Time-Delay Fuse	5.6A	600V	300kA AC, 100kA DC
27760	LPJ-50SP	Bussmann	LOW-PEAK Dual-Element Time-Delay Fuse	50A	600V	300kA AC, 100kA DC
27730	LPJ-5SP	Bussmann	LOW-PEAK Dual-Element Time-Delay Fuse	5A	600V	300kA AC, 100kA DC
27761	LPJ-60SP	Bussmann	LOW-PEAK Dual-Element Time-Delay Fuse	60A	600V	300kA AC, 100kA DC
27732	LPJ-6SP	Bussmann	LOW-PEAK Dual-Element Time-Delay Fuse	6A	600V	300kA AC, 100kA DC
27733	LPJ-7SP	Bussmann	LOW-PEAK Dual-Element Time-Delay Fuse	7A	600V	300kA AC, 100kA DC
17871	LPJ-8SP	Bussmann	LOW-PEAK Dual-Element Time-Delay Fuse	8A	600V	200kA AC, 100kA DC
27734	LPJ-9SP	Bussmann	LOW-PEAK Dual-Element Time-Delay Fuse	9A	600V	300kA AC, 100kA DC

