



Other Type Fuses

Detailed product specifications are available on: us.100y.com.tw



FEATURES

- Accurate current rating
- Fast acting
- Small-standard 0402, 0603, 0805, 1206 and 0612 chip sizes
- Taped and reeled
- Completely compatible with all soldering systems used for SMT
- Lead free series (F0402E, F0603E)

| Part No. | Product No. | Manufacturer |
|----------|----------------|--------------|
| 41201 | F0603E2R00FSTR | AVX |

FEATURES

- Suitable for thin devices with thickness of 0.6mm
- No smoke or flame in overload condition
- Excellent in endurance against soldering-heat

APPLICATIONS

- PC Applications: laptop computer, word processor, CD-ROM drive
- Portable communication machinery: PDA, Mobile phone and battery charger
- AV Applications: DVC, Digital camera, CD player
- Amusement machine: game equipment, handy game equipment
- LCD/Secondary li-ion battery

| Part No. | Product No. | Description | A/Volt. |
|----------|--------------|-------------|---------|
| 21808 | FHC3232AD-TP | Fuse | 1A/ V |



Fuse

| Part No. | Product No. | Description | A/Volt. | Size |
|----------|-------------|-------------|------------|--------|
| 30962 | FUSE0.5A | Fuse | 500mA/600V | 25*6mm |
| 28530 | FUSE0.5A | Fuse | 500mA/600V | 28*6mm |



Fast Acting Fuse

| Part No. | Product No. | Description | A/Volt. | Size |
|----------|-------------|------------------|--------------|----------|
| 10112 | MIFI 0.25A | Fast Acting Fuse | 0.25A/250VAC | 6.3*30mm |



FEATURES/BENEFITS

- Easy to read imprint label for quick recognition and replacement
- Low cost for high protection value

APPLICATIONS

- Feeders
- Branch circuits
- Resistive heating
- Residential and small commercial installations

| Part No. | Product No. | Manufacturer | Description | A/Volt. | Size |
|----------|-------------|--------------|-------------------|----------|---------|
| 4100 8 | OT25 | Ferraz Sh. | FS_CLASS K-5 Fuse | 25A/250V | 14*51mm |
| 41009 | OT3 | Ferraz Sh. | FS_CLASS K-5 Fuse | 3A/250V | 14*51mm |



Physical characteristics

lead material: R30-090~250: Tin-plated copper-clad steel, 0.205mm² (24AWG), Φ 0.51mm (0.020 in)
R30-300~900: Tin-plated copper, 0.52mm² (20AWG), Φ 0.81mm (0.032 in)

| Part No. | Product No. | Manufacturer | Description | A/Volt. | Size |
|----------|-------------|--------------|-----------------|----------|-----------------|
| 43157 | R30-250 | Sea-land | Resettable Fuse | 2.5A/30V | 11.4*18.3*5.1mm |



Physical characteristics

lead material: R30-090~250: Tin-plated copper-clad steel, 0.205mm² (24AWG), Φ 0.51mm (0.020 in)
R30-300~900: Tin-plated copper, 0.52mm² (20AWG), Φ 0.81mm (0.032 in)

| Part No. | Product No. | Manufacturer | Description | I max. (A) | Ih(A) | Vdc (max.) |
|----------|-------------|--------------|-----------------|------------|-------|------------|
| 37336 | R30-500 | Sea-land | Resettable Fuse | 40A | 5A | 30Vdc |



FEATURES

- Radial leaded devices
- Cured, flame retardant epoxy polymer insulating material meets UL 94V-0 requirements
- Bulk packaging, or tape and reel available on most models

APPLICATIONS

Almost anywhere there is a low voltage power supply, up to 60V and a load to be protected, including:

- Industrial controls
- Automotive electronics
- Medical products

| Part No. | Product No. | Manufacturer | Description | AWG | I max. (A) | Ih(A) | RiI/Rat (Ω) | Vdc (max.) | A/Volt. | Size |
|----------|-------------|--------------|-----------------|-------|------------|-------|----------------------|------------|-----------|-----------------|
| 25707 | R60-110 | Sea-land | Resettable Fuse | 20AWG | 40A | 1.1A | 0.15/0.38 | 60Vdc | | 12.95*18.0*5308 |
| 43209 | R60-375 | Sea-land | Resettable Fuse | | | | | | 3.75A/60V | 28.5*33.5*10.2 |



Ceramic Tube Fuse



| Part No. | Product No. | Manufacturer | Description | A/Volt. | Size |
|----------|-------------|--------------|-------------------|-----------|-------|
| 12679 | TFU-50-05 | TEND | Ceramic Tube Fuse | 5A/600V | 14*50 |
| 12678 | TFU-50-20 | TEND | Ceramic Tube Fuse | 20A/600 V | 14*50 |

