





IWASAKI Projection Lamps

Detailed product specifications are available on: us.100y.com.tw




Type	Reference or Substitute Lamp	Volts (V)	Watts (W)	Approx Initial Lumens (lm)	Colour Temp (k)	Rated Av. life (hrs)	Dimensions (mm)			Base	Filament	Fig. No.
							M. D.	M.O.L	L.C.L			
FDX 12V 100W	FDX	12	100	2800	3350	70	11.0	44	30	GY6.35	C-Bar-6	4

Part No.	Product No.	Manufacturer	Description	Voltage (V)	Watts (W)	Color(K)	Filament Design	Ave. Life (hr)	ANSI
31661	IWASAKI-FDX12V100W	IWASAKI	IWASAKI Projection Lamp	12V	100W	3350K	GY6.35	70hr.	FDX




Type	Reference or Substitute Lamp	Volts (V)	Watts (W)	Approx Initial Lumens (lm)	Colour Temp (k)	Rated Av. life (hrs)	Dimensions (mm)			Base	Filament	Fig. No.
							M. D.	M.O.L	L.C.L			
JC 12V 100W/G2	FCR A1/215	12	100	2800	3350	70	11.0	44	30	GY6.35	C-Bar-6	2

Part No.	Product No.	Manufacturer	Description	Voltage (V)	Watts (W)	Color(K)	Filament Design	Ave. Life (hr)	ANSI
31671	IWASAKI-JC12V100W/G2	IWASAKI	IWASAKI Projection Lamp	12V	100W	3350K	GY6.35	70hr.	FCR A1/215




Type	Reference or Substitute Lamp	Volts (V)	Watts (W)	Approx Initial Lumens (lm)	Colour Temp (k)	Rated Av. life (hrs)	Dimensions (mm)			Base	Filament	Fig. No.
							M. D.	M.O.L	L.C.L			
JC 12V 100W 10H/G2	—	12	100	2200	3100	1000	11.0	44	30	GY6.35	C-Bar-6	10

Part No.	Product No.	Manufacturer	Description	Voltage (V)	Watts (W)	Color(K)	Filament Design	Ave. Life (hr)
31793	IWASAKI-JC12V100W10H/G2	IWASAKI	IWASAKI Projection Lamp	12V	100W	3100K	GY6.35	1000hr.




Type	Reference or Substitute Lamp	Volts (V)	Watts (W)	Approx Initial Lumens (lm)	Colour Temp (k)	Rated Av. life (hrs)	Dimensions (mm)			Base	Filament	Fig. No.
							M. D.	M.O.L	L.C.L			
JC 12V 100W20H/G1	—	12	100	2000	3000	2000	11.0	44	30	G6.35	C-Bar-6	7

Part No.	Product No.	Manufacturer	Description	Voltage (V)	Watts (W)	Color(K)	Filament Design	Ave. Life (hr)
31794	IWASAKI-JC12V100W20H/G1	IWASAKI	IWASAKI Projection Lamp	12V	100W	3000K	G6.35	2000hr.




Type	Reference or Substitute Lamp	Volts (V)	Watts (W)	Approx Initial Lumens (lm)	Colour Temp (k)	Rated Av. life (hrs)	Dimensions (mm)			Base	Filament	Fig. No.
							M. D.	M.O.L	L.C.L			
JC 12V 100W20H/G2	—	12	100	2000	3000	2000	11.0	44	30	G6.35	C-Bar-6	10

Part No.	Product No.	Manufacturer	Description	Voltage (V)	Watts (W)	Color(K)	Filament Design	Ave. Life (hr)
31795	IWASAKI-JC12V100W20H/G2	IWASAKI	IWASAKI Projection Lamp	12V	100W	3000K	GY6.35	2000hr.



Type	Reference or Substitute Lamp	Volts (V)	Watts (W)	Approx Initial Lumens (lm)	Colour Temp (k)	Rated Av. life (hrs)	Dimensions (mm)			Base	Filament	Fig. No.
							M. D.	M.O.L	L.C.L			
JC12V100W20H/G2S	M28	12	100	2000	3000	2000	11.0	44	30	G6.35S	C-Bar-6	6

Part No.	Product No.	Manufacturer	Description	Voltage (V)	Watts (W)	Color(K)	Filament Design	Ave. Life (hr)
31797	IWASAKI-JC12V100W20H/G2S	IWASAKI	IWASAKI Projection Lamp	12V	100W	3000K	GY6.35S	2000hr.



Type	Reference or Substitute Lamp	Volts (V)	Watts (W)	Approx Initial Lumens (lm)	Colour Temp (k)	Rated Av. life (hrs)	Dimensions (mm)			Base	Filament	Fig. No.
							M. D.	M.O.L	L.C.L			
JC12V20W20H/G1	—	12	20	350	2850	2000	11.0	44	30	G6.35	C-6	1

Part No.	Product No.	Manufacturer	Description	Voltage (V)	Watts (W)	Color(K)	Filament Design	Ave. Life (hr)
31778	IWASAKI-JC12V20W20H/G1	IWASAKI	IWASAKI Projection Lamp	12V	20W	2850K	G6.35	2000hr.

