





# IWASAKI Projection Lamps

Detailed product specifications are available on: [us.100y.com.tw](http://us.100y.com.tw)




Type	Reference or Substitute Lamp	Volts (V)	Watts (W)	Approx Initial Lumens (lm)	Colour Temp (k)	Rated Av. life (hrs)	Dimensions (mm)			Base	Filament	Fig. No.
							M. D.	M.O.L.	L.C.L.			
JC12V50W20H/G2S	M32	12	50	850	3000	2000	11.0	44	30	GY6.35S	C-Bar-6	6

Part No.	Product No.	Manufacturer	Description	Voltage (V)	Watts (W)	Color(K)	Filament Design	Ave. Life (hr)
31789	IWASAKI-JC12V50W20H/G2S	IWASAKI	IWASAKI_Projection Lamp	12V	50W	3000K	GY6.35S	2000hr.




Type	Reference or Substitute Lamp	Volts (V)	Watts (W)	Approx Initial Lumens (lm)	Colour Temp (k)	Rated Av. life (hrs)	Dimensions (mm)			Base	Filament	Fig. No.
							M. D.	M.O.L.	L.C.L.			
JC15V50W/G1	BRJ A1/234	15	150	4700	3400	70	11.0	44	30	G6.35	C-Bar-6	1

Part No.	Product No.	Manufacturer	Description	Voltage (V)	Watts (W)	Color(K)	Filament Design	Ave. Life (hr)	ANSI
31672	IWASAKI-JC15V150W/G1	IWASAKI	IWASAKI_Projection Lamp	15V	150W	3400K	G6.35	70hr.	BRJ A1/234




Type	Reference or Substitute Lamp	Volts (V)	Watts (W)	Approx Initial Lumens (lm)	Colour Temp (k)	Rated Av. life (hrs)	Dimensions (mm)			Base	Filament	Fig. No.
							M. D.	M.O.L.	L.C.L.			
JC24V150W/G1	A1/216	24	150	4700	3400	70	13.5	50	32	G6.35	C-Bar-6	4

Part No.	Product No.	Manufacturer	Description	Voltage (V)	Watts (W)	Color(K)	Filament Design	Ave. Life (hr)	ANSI
31674	IWASAKI-JC24V150W/G1	IWASAKI	IWASAKI_Projection Lamp	24V	150W	3400K	G6.35	70hr.	A1/216




Type	Reference or Substitute Lamp	Volts (V)	Watts (W)	Approx Initial Lumens (lm)	Colour Temp (k)	Rated Av. life (hrs)	Dimensions (mm)			Base	Filament	Fig. No.
							M. D.	M.O.L.	L.C.L.			
JC24V150W10H/G1	—	24	150	3450	3100	1000	13.5	50	30	G6.35	C-Bar-6	12

Part No.	Product No.	Manufacturer	Description	Voltage (V)	Watts (W)	Color(K)	Filament Design	Ave. Life (hr)
31803	IWASAKI-JC24V150W10H/G1	IWASAKI	IWASAKI_Projection Lamp	24V	150W	3100K	G6.35	1000hr.




Type	Reference or Substitute Lamp	Volts (V)	Watts (W)	Approx Initial Lumens (lm)	Colour Temp (k)	Rated Av. life (hrs)	Dimensions (mm)			Base	Filament	Fig. No.
							M. D.	M.O.L.	L.C.L.			
JC24V150W1H/G1	FDV	24	150	4300	3250	100	13.5	50	30	G6.35	C-Bar-6	5

Part No.	Product No.	Manufacturer	Description	Voltage (V)	Watts (W)	Color(K)	Filament Design	Ave. Life (hr)	ANSI
31677	IWASAKI-JC24V150W1H/G1	IWASAKI	IWASAKI_Projection Lamp	24V	150W	3250K	G6.35	100hr.	FDV




Type	Reference or Substitute Lamp	Volts (V)	Watts (W)	Approx Initial Lumens (lm)	Colour Temp (k)	Rated Av. life (hrs)	Dimensions (mm)			Base	Filament	Fig. No.
							M. D.	M.O.L.	L.C.L.			
JC24V150W20H/G1	—	24	150	3150	3000	2000	13.5	50	30	G6.35	C-Bar-6	12

Part No.	Product No.	Manufacturer	Description	Voltage (V)	Watts (W)	Color(K)	Filament Design	Ave. Life (hr)
31804	IWASAKI-JC24V150W20H/G1	IWASAKI	IWASAKI_Projection Lamp	24V	150W	3000K	G6.35	2000hr.



Type	Reference or Substitute Lamp	Volts (V)	Watts (W)	Approx Initial Lumens (lm)	Colour Temp (k)	Rated Av. life (hrs)	Dimensions (mm)			Base	Filament	Fig. No.
							M. D.	M.O.L.	L.C.L.			
JC24V150W2H/G1	—	24	150	4350	3300	200	13.5	50	30	G6.35	C-Bar-6	5

Part No.	Product No.	Manufacturer	Description	Voltage (V)	Watts (W)	Color(K)	Filament Design	Ave. Life (hr)
31678	IWASAKI-JC24V150W2H/G1	IWASAKI	IWASAKI_Projection Lamp	24V	150W	3300K	G6.35	200hr.



Type	Reference or Substitute Lamp	Volts (V)	Watts (W)	Approx Initial Lumens (lm)	Colour Temp (k)	Rated Av. life (hrs)	Dimensions (mm)			Base	Filament	Fig. No.
							M. D.	M.O.L.	L.C.L.			
JC24V200W20H/G1	—	24	200	4400	3000	2000	13.5	50	30	G6.35	C-Bar-6	3

Part No.	Product No.	Manufacturer	Description	Voltage (V)	Watts (W)	Color(K)	Filament Design	Ave. Life (hr)
31808	IWASAKI-JC24V200W20H/G1	IWASAKI	IWASAKI_Projection Lamp	24V	200W	3000K	G6.35	2000hr.

