





IWASAKI Projection Lamps

Detailed product specifications are available on: us.100y.com.tw




Type	Reference or Substitute Lamp	Volts (V)	Watts (W)	Approx Initial Lumens (lm)	Colour Temp (k)	Rated Av. life (hrs)	Dimensions (mm)			Base	Filament	Fig. No.
							M. D.	M.O.L	L.C.L			
JC24V250W/G1	EHJ A1/223	24	250	8250	3400	70	13.5	55	33	G6.35	C-Bar-6	6

Part No.	Product No.	Manufacturer	Description	Voltage (V)	Watts (W)	Color(K)	Filament Design	Ave. Life (hr)	ANSI
31680	IWASAKI-JC24V250W/G1	IWASAKI	IWASAKI_Projection Lamp	24V	250W	3400K	G6.35	70hr.	EHJ A1/223




Type	Reference or Substitute Lamp	Volts (V)	Watts (W)	Approx Initial Lumens (lm)	Colour Temp (k)	Rated Av. life (hrs)	Dimensions (mm)			Base	Filament	Fig. No.
							M. D.	M.O.L	L.C.L			
JC24V250W20H/G1	M36	24	250	5500	3000	2000	13.5	55	33	G6.35	C-Bar-6	4

Part No.	Product No.	Manufacturer	Description	Voltage (V)	Watts (W)	Color(K)	Filament Design	Ave. Life (hr)
31810	IWASAKI-JC24V250W20H/G1	IWASAKI	IWASAKI_Projection Lamp	24V	250W	3000K	G6.35	2000hr.
31809	IWASAKI-JC24V250W3H/G1	IWASAKI	IWASAKI_Projection Lamp	24V	250W	3300K	G6.35	300hr.




Type	Reference or Substitute Lamp	Volts (V)	Watts (W)	Approx Initial Lumens (lm)	Colour Temp (k)	Rated Av. life (hrs)	Dimensions (mm)			Base	Filament	Fig. No.
							M. D.	M.O.L	L.C.L			
JC24V250WR/G1	—	24	250	8250	3400	50	13.5	55	33	G6.35	C-Bar-6	6

Part No.	Product No.	Manufacturer	Description	Voltage (V)	Watts (W)	Color(K)	Filament Design	Ave. Life (hr)
31683	IWASAKI-JC24V250WR/G1	IWASAKI	IWASAKI_Projection Lamp	24V	250W	3400K	G6.35	50hr.




Type	Reference or Substitute Lamp	Volts (V)	Watts (W)	Approx Initial Lumens (lm)	Colour Temp (k)	Rated Av. life (hrs)	Dimensions (mm)			Base	Filament	Fig. No.
							M. D.	M.O.L	L.C.L			
JC24V300W/G2	—	24	300	9900	3400	50	13.5	55	33	GY6.35	C-Bar-6	7

Part No.	Product No.	Manufacturer	Description	Voltage (V)	Watts (W)	Color(K)	Filament Design	Ave. Life (hr)
31686	IWASAKI-JC24V300W/G2	IWASAKI	IWASAKI_Projection Lamp	24V	300W	3400K	GY6.35	50hr.




Type	Reference or Substitute Lamp	Volts (V)	Watts (W)	Approx Initial Lumens (lm)	Colour Temp (k)	Rated Av. life (hrs)	Dimensions (mm)			Base	Filament	Fig. No.
							M. D.	M.O.L	L.C.L			
JC24V50W20H/G1	—	24	50	850	2950	2000	11.0	44	30	G6.35	C-Bar-6	7

Part No.	Product No.	Manufacturer	Description	Voltage (V)	Watts (W)	Color(K)	Filament Design	Ave. Life (hr)
31790	IWASAKI-JC24V50W20H/G1	IWASAKI	IWASAKI_Projection Lamp	24V	50W	2950K	G6.35	2000hr.




Type	Reference or Substitute Lamp	Volts (V)	Watts (W)	Approx Initial Lumens (lm)	Colour Temp (k)	Rated Av. life (hrs)	Dimensions (mm)			Base	Filament	Fig. No.
							M. D.	M.O.L	L.C.L			
JC36V400W/G1	EVD A1/239	36	400	14000	3400	50	16	60	36	G6.35	C-Bar-6	8

Part No.	Product No.	Manufacturer	Description	Voltage (V)	Watts (W)	Color(K)	Filament Design	Ave. Life (hr)	ANSI
31687	IWASAKI-JC36V400W/G1	IWASAKI	IWASAKI_Projection Lamp	36V	400W	3400K	G6.35	36hr.	EVD A1/239



Type	Reference or Substitute Lamp	Volts (V)	Watts (W)	Approx Initial Lumens (lm)	Colour Temp (k)	Rated Av. life (hrs)	Dimensions (mm)			Base	Filament	Fig. No.
							M. D.	M.O.L	L.C.L			
JCD150W-S/G1	—	100, 120	150	4050	3250	50	13.5	50	30	G6.35	CC-6	1

Part No.	Product No.	Manufacturer	Description	Voltage (V)	Watts (W)	Color(K)	Filament Design	Ave. Life (hr)
31655	IWASAKI-JCD150W-S/G1	IWASAKI	IWASAKI_Projection Lamp	100V/120V	150W	3250K	G6.35	50hr.



Type	Reference or Substitute Lamp	Volts (V)	Watts (W)	Approx Initial Lumens (lm)	Colour Temp (k)	Rated Av. life (hrs)	Dimensions (mm)			Base	Filament	Fig. No.
							M. D.	M.O.L	L.C.L			
JCD150WL/G1	—	100, 120	150	3300	3100	300	13.5	50	30	G6.35	CC-6	1

Part No.	Product No.	Manufacturer	Description	Voltage (V)	Watts (W)	Color(K)	Filament Design	Ave. Life (hr)
31811	IWASAKI-JCD150WL/G1	IWASAKI	IWASAKI_Projection Lamp	100/120V	150W	3100K	G6.35	300hr.

