





# IWASAKI\_Projection Lamps

Detailed product specifications are available on: [us.100y.com.tw](http://us.100y.com.tw)




Type	Reference or Substitute Lamp	Volts (V)	Watts (W)	Approx Initial Lumens (lm)	Colour Temp (k)	Rated Av. life (hrs)	Dimensions (mm)			Base	Filament	Fig. No.
							M. D.	M.O.L	L.C.L			
JCD200W-S/G1	—	220/230	200	4700	3100	50	21.0	63	40	G6.35	CC-13	3
	—	240/250	200	4700	3100	50	21.0	63	40	G6.35	CC-13	3

Part No.	Product No.	Manufacturer	Description	Voltage (V)	Watts (W)	Color(K)	Filament Design	Ave. Life (hr)
31656	IWASAKI-JCD200W-S/G1	IWASAKI	IWASAKI_Projection Lamp	220V/230V/240V/250V	200W	3100K	G6.35	50hr.




Type	Reference or Substitute Lamp	Volts (V)	Watts (W)	Approx Initial Lumens (lm)	Colour Temp (k)	Rated Av. life (hrs)	Dimensions (mm)			Base	Filament	Fig. No.
							M. D.	M.O.L	L.C.L			
JCD200WL/G1	—	100, 120	200	4400	3100	300	15.5	50	33	G6.35	CC-6	1

Part No.	Product No.	Manufacturer	Description	Voltage (V)	Watts (W)	Color(K)	Filament Design	Ave. Life (hr)
31812	IWASAKI-JCD200WL/G1	IWASAKI	IWASAKI_Projection Lamp	100/120V	200W	3100K	G6.35	300hr.




Type	Reference or Substitute Lamp	Volts (V)	Watts (W)	Approx Initial Lumens (lm)	Colour Temp (k)	Rated Av. life (hrs)	Dimensions (mm)			Base	Filament	Fig. No.
							M. D.	M.O.L	L.C.L			
JCD200WL/G1	—	220/230	200	4000	3000	150	15.5	63	40	G6.35	CC-13	2
	—	240/250	200	4000	3000	150	15.5	63	40	G6.35	CC-13	2

Part No.	Product No.	Manufacturer	Description	Watts (W)	Color(K)	Filament Design	Ave. Life (hr)
31813	IWASAKI-JCD200WL/G1	IWASAKI	IWASAKI_Projection Lamp	200W	3000K	G6.35	150hr.




Type	Reference or Substitute Lamp	Volts (V)	Watts (W)	Approx Initial Lumens (lm)	Colour Temp (k)	Rated Av. life (hrs)	Dimensions (mm)			Base	Filament	Fig. No.
							M. D.	M.O.L	L.C.L			
JCD24V100W20H/G1	—	24	100	1800	3000	2000	11.0	44	30	G6.35	CC-6	9

Part No.	Product No.	Manufacturer	Description	Voltage (V)	Watts (W)	Color(K)	Filament Design	Ave. Life (hr)
31801	IWASAKI-JCD24V100W20H/G1	IWASAKI	IWASAKI_Projection Lamp	24V	100W	3000K	G6.35	2000hr.




Type	Reference or Substitute Lamp	Volts (V)	Watts (W)	Approx Initial Lumens (lm)	Colour Temp (k)	Rated Av. life (hrs)	Dimensions (mm)			Base	Filament	Fig. No.
							M. D.	M.O.L	L.C.L			
JCD24V55W10H/G1	—	24	55	990	3000	1000	11.0	40	27.8	G6.35	CC-8	8

Part No.	Product No.	Manufacturer	Description	Voltage (V)	Watts (W)	Color(K)	Filament Design	Ave. Life (hr)
31791	IWASAKI-JCD24V55W10H/G1	IWASAKI	IWASAKI_Projection Lamp	24V	55W	3000K	G6.35	1000hr.



Type	Reference or Substitute Lamp	Volts (V)	Watts (W)	Approx Initial Lumens (lm)	Colour Temp (k)	Rated Av. life (hrs)	Dimensions (mm)			Base	Filament	Fig. No.
							M. D.	M.O.L	L.C.L			
JCD24V75W20H/G1	—	24	75	1350	3000	2000	11.0	44	30	G6.35	CC-6	9

Part No.	Product No.	Manufacturer	Description	Voltage (V)	Watts (W)	Color(K)	Filament Design	Ave. Life (hr)
31792	IWASAKI-JCD24V75W20H/G1	IWASAKI	IWASAKI_Projection Lamp	24V	75W	3000K	G6.35	2000hr.



Type	Reference or Substitute Lamp	Volts (V)	Watts (W)	Approx Initial Lumens (lm)	Colour Temp (k)	Rated Av. life (hrs)	Dimensions (mm)			Base	Filament	Fig. No.
							M. D.	M.O.L	L.C.L			
JCD250W-S/G1	—	100, 120	250	7000	3300	50	16.0	50	33	G6.35	CC-6	2

Part No.	Product No.	Manufacturer	Description	Voltage (V)	Watts (W)	Color(K)	Filament Design	Ave. Life (hr)
31657	IWASAKI-JCD250W-S/G1	IWASAKI	IWASAKI_Projection Lamp	100V/120V	250W	3300K	G6.35	50hr.

