





IWASAKI_Projection Lamps

Detailed product specifications are available on: us.100y.com.tw


| Type | Reference or Substitute Lamp | Volts (V) | Watts (W) | Colour Temp (k) | Rated Av. life (hrs) | Dimensions (mm) | | | | Filament | Fig. No. |
|----------|------------------------------|-----------|-----------|-----------------|----------------------|-----------------|---------|----------|--------------|----------|----------|
| | | | | | | M. D. | L. L. a | M.O.L. C | C to B. E. C | | |
| JCD650WC | | 220/230 | 650 | 3200 | 100 | 14.0 | 26 | 79.3 | 76.3 | CC-8 | 1 |
| | | 240 | 650 | 3200 | 100 | 14.0 | 26 | 79.3 | 76.3 | CC-8 | 1 |
| JCD650WS | | 220/230 | 650 | 3400 | 25 | 14.0 | 26 | 79.3 | 79.3 | CC-8 | 1 |
| | | 240 | 650 | 3400 | 25 | 14.0 | 26 | 79.3 | 79.3 | CC-8 | 1 |

| Part No. | Product No. | Manufacturer | Description | Voltage (V) | Watts (W) | Color(K) | Ave. Life (hr) |
|----------|------------------|--------------|-------------------------|--------------|-----------|----------|----------------|
| 31759 | IWASAKI-JPD650WC | IWASAKI | IWASAKI_Projection Lamp | 220/230/240V | 650W | 3200K | 100hr. |
| 31760 | IWASAKI-JPD650WS | IWASAKI | IWASAKI_Projection Lamp | 220/230/240V | 650W | 3400K | 25hr. |



| Type | Reference or Substitute Lamp | Volts (V) | Watts (W) | Colour Temp (k) | Rated Av. life (hrs) | Dimensions (mm) | | | | Filament | Fig. No. |
|--------------|------------------------------|-----------|-----------|-----------------|----------------------|-----------------|---------|----------|--------------|----------|----------|
| | | | | | | M. D. | L. L. a | M.O.L. C | C to B. E. C | | |
| JCD650WS/DWY | DWY P1/9 | 115/120 | 650 | 3400 | 25 | 14.0 | 25 | 79.3 | 76.3 | CC-8 | 1 |

| Part No. | Product No. | Manufacturer | Description | Voltage (V) | Watts (W) | Color(K) | Ave. Life (hr) |
|----------|----------------------|--------------|-------------------------|-------------|-----------|----------|----------------|
| 31771 | IWASAKI-JPD650WS/DWY | IWASAKI | IWASAKI_Projection Lamp | 115/120V | 650W | 3400K | 25hr. |



| Type | Reference or Substitute Lamp | Volts (V) | Watts (W) | Colour Temp (k) | Rated Av. life (hrs) | Dimensions (mm) | | | | Filament | Fig. No. |
|--------------|------------------------------|-----------|-----------|-----------------|----------------------|-----------------|---------|----------|--------------|----------|----------|
| | | | | | | M. D. | L. L. a | M.O.L. C | C to B. E. C | | |
| JCD800WC/DXX | DXX P2/13 | 220/230 | 800 | 20000 | 75 | 14.0 | 29 | 79.3 | 76.3 | CC-8 | 1 |
| | | 240 | 800 | 20000 | 75 | 14.0 | 29 | 79.3 | 76.3 | CC-8 | 1 |

| Part No. | Product No. | Manufacturer | Description | Voltage (V) | Watts (W) | Color(K) | Ave. Life (hr) | ANSI |
|----------|----------------------|--------------|-------------------------|--------------|-----------|----------|----------------|------|
| 31761 | IWASAKI-JPD800WC/DXX | IWASAKI | IWASAKI_Projection Lamp | 220/230/240V | 800W | 3200K | 75hr. | DXX |



| Type | Reference or Substitute Lamp | Volts (V) | Watts (W) | Colour Temp (k) | Rated Av. life (hrs) | Dimensions (mm) | | Base | Filament | Fig. No. |
|-----------------|------------------------------|-----------|-----------|-----------------|----------------------|-----------------|--------|--------|----------|----------|
| | | | | | | M. D. | M.O.L. | | | |
| JCR12V50W20H/G1 | — | 12 | 50 | 3000 | 2000 | 50.0 | 42.0 | GZ6.35 | C-8 | 3 |

| Part No. | Product No. | Manufacturer | Description | Voltage (V) | Watts (W) | Color(K) | Filament Design | Ave. Life (hr) | Dia. * Mol (mm) |
|----------|-----------------|--------------|-------------------------------------|-------------|-----------|----------|-----------------|----------------|-----------------|
| 1374 | JCR12V50W20H/G1 | IWASAKI | IWASAKI_EYE Projection Halogen Lamp | 12V | 50W | 3000K | MR16 GZ6.35 | 2000 | 50*42mm |

OSRAM-SYLVANIA_Projection Lamps

Detailed product specifications are available on: us.100y.com.tw

- Base: GY6.35-Prefocus, 2-pin; round 3.2mm & 2.4mm 9.53mm centered, Ceramic base
- Glass: T-6
- Filament: C-13D
- Average Life: 75hours

| Part No. | Product No. | Manufacturer | Description | Voltage (V) | Watts (W) | Lm | Filament Design | Ave. Life (hr) | Dia. * Mol (mm) |
|----------|------------------------|--------------|---------------------------------|-------------|-----------|-------|-----------------|----------------|-----------------|
| 5431 | SYLVANIA-JCP-100V/650W | SYLVANIA | OSRAM-SYLVANIA_Projection Lamps | 100V | 650W | 18750 | GY6.35 | 75h | 19.5*76 |

PHILIPS_Fluorescent Tube

Detailed product specifications are available on: us.100y.com.tw

- Average life under specified test conditions with lamps turned off and restarted no more frequently than once every 3 operating hours, lamp life is appreciably longer if lamps are started less frequently
- Approximate initial lumens. The lamp lumen output is based upon lamp performance after 100 hours of operating life, when the output is measured during operation on a reference ballast under standard laboratory conditions.
- Design lumens are the approximate lamp lumen output at 40% of the lamp's rated average life. This output is based upon measurements obtained during lamp operation on a reference ballast under standard laboratory conditions.

| Part No. | Product No. | Manufacturer | Description | Watts (W) | Color(K) | Dia. * Mol (mm) |
|----------|-------------|--------------|------------------|-----------|----------|-----------------|
| 43108 | PL-36W | PHILIPS | Fluorescent Lamp | 36W | 4100 | 380mm |



FEATURES

- Low electric power consumption
- Could absorb impurity in the lamp and make lamp brighter
- The lamp couldn't become black

| Part No. | Product No. | Manufacturer | Description | Watts (W) | Color(K) | Lm |
|----------|-------------|--------------|---------------------------|-----------|----------|-------|
| 28073 | TL18W/D | PHILIPS | Compact Fluorescent Lamps | 18W | 1050LM | 6200K |

