

# Power Supplies & UPS

## Uninterruptible Power Supplies Off-Line UPS

Detailed product specifications are available on: [us.100y.com.tw](http://us.100y.com.tw)



**Output:**  
Output Capability power: 300W/500VA  
Output: 120V

**Input:**  
Input voltage: 120V  
Input frequency: 60Hz+/-3Hz

Part No.	Product No.	Description	Size
42751	BE500TW	APC Back-UPS ES 500VA	175x277x84mm



High Convert efficiency    Long working time    Insure computer Power cut off

Part No.	Product No.	Description	Output Waveform	Convert Time	communcion	Size
15753	UPS-1000AP	Off Line UPS 1000VA	Sine Wave 1150V/220V+/-5%	2/4 ms(Include Testing Time)		130/382/201mm
14118	UPS-BNT-500	Off Line UPS -500VA 110VAC in/110VAC out	Sine Waves 115V/220V+/-5%	2/4 ms(Include Testing Time)	No	97*320*135mm



Input capability: 1000AV  
Output voltage: Rating voltage+/-5% (single-phase 100V/110/115V/120V or 220V/230V/240)  
Weight: 15.0 (33.0 pound)

Part No.	Product No.	Description	Output Waveform	communcion	Size
29329	UPS-KIN-1000AP-220	Off Line UPS -1000VA	110V ±5% Sine Waves	RS232	130 x 382 x 201mm



**AC INPUT**  
AC Input capacity on battery: 525VA  
AC Input Voltage : 100V/110V/115V/120V/220V/230/240V+/-25% at line input

**AC OUTPUT**  
AC output voltage : Simulated sine wave at 100V/110V/115V/120V/220V/230V/240V +/-5%  
AC Output Transfer : 2/4 milliseconds, including detection time

**PROTECTION**  
Protection Overload : UPS automatic shutdown if overload over 110% of nominal at 60 seconds and 130% at 3 seconds.  
Physical Dimension mm : 97 x 320 x 135  
Physical Dimension inch : 3.8" x 12.6" x 5.3"

Part No.	Product No.	Description
26225	UPS-KIN-525AP-220	Off Line UPS -500VA 220VAC in/220VAC out



Rating capability: 1000VA/600W    UPS Output capability: 1000VA  
Rating voltage: 110V    Temperature: 0~35°C  
Input voltage range: 88V~132V    Size: 120x300x190 (WxDxH) mm

Part No.	Product No.	Description	Output Waveform	Convert Time	Size
17301	V1000	Off-Line UPS	Simulate Sine Wave	4-10ms	120(W)*300(D)*190(H)mm

## On-Line UPS

Detailed product specifications are available on: [us.100y.com.tw](http://us.100y.com.tw)



- S1010-110-110**
- CPU Controlled Smart UPS
  - Input Power Factor Correction
  - Self Diagnostic
  - Green Mode Function
  - Back-up Mode Test Function
  - True RS232 Interface
  - Integrated Compact Size
  - By Pass Load Protection
  - Long Back-up Time Series Available

Part No.	Product No.	Description	Output Waveform	Convert Time	communcion	Size
14064	S1010-110-110	On Line UPS-1KVA UPS IN:110V OUT:110V	50Hz/60Hz(auto t racking)	Line fails or recovers:0 UPS to BYPASS:<4 milli seconds	RS232	152*400*220(mm)/17kg

- We provide a wide range of products to development and maintenance engineers in all type of business
- If you cannot find the components you want on the catalogue, please call us.



Taiwan: 886-3-5753170  
Shanghai: 021-54151736    Shenzhen: 0755-83298787

**Centenary Materials**  
Waiting for your phone call



T E L : Taiwan: 886-3-5753170  
F A X : Taiwan: 886-3-5753172  
E-mail: Taiwan: sale@100y.com.tw

Shenzhen: 86-755-83298787  
Shenzhen: 86-755-83640655  
Shenzhen: 100y@163.com

Shanghai: 86-21-54151736  
Shanghai: 86-21-64605107  
Shanghai: 100y-1@163.com