


Power Supplies & UPS

60-200W Triple Output Switching Power Supply

Detailed product specifications are available on: us.100y.com.tw



FEATURES:

- Low cost, high reliability.
- Compact size, light weight
- 105°C output capacitor.
- 100% full load burn-in test.
- International AC input range.
- Built in EMI filter, low ripple noise
- High efficiency, low working temperature.
- Soft-start circuit, limiting AC surge current.
- Short circuit, overload protected

INPUT VOLTAGE RANGE : 85 ~ 132VAC / 170~264VAC Selected by switch
47 ~ 63Hz; 240~370VDC
AC CURRENT : 2. 5A/115VAC 1. 25A/230VAC
INRUSH CURRENT(max.): COLD START 30A/115VAC 60A/230V
LEAKAGE CURRENT : <0. 5mA/240VAC
WORKING TEMP. HUMIDITY : -10 ~ +60°C(Refer to output load derating curve)
20%~90% RH
SAFETY STANDARDS : MEET U1012 Requirement (not apply for the mark)
WITHSTAND VOLTAGE : I/P-O/P: 1. 5KVAC I/P-FG: 1.5KVAC
O/P-FG: 0.5KVAC

Part No.	Product No.	Manufacturer	Description	Output Volt./Current	Tol.(±)	Output Volt./Current	Tol.(±)	Tol.(±)	Output Volt./Current
11680	T-100D	MEAN WELL	100W Triple Output Switching Power Supply	5VDC/2~12A	+/-2%	12VDC/0.1~2A	+/-6%	+/-6%	24VDC/0.2~2A




FEATURES:

- Low cost, high reliability.
- Compact size, light weight
- 105°C output capacitor.
- 100% full load burn-in test.
- International AC input range.
- High efficiency, low working temperature.
- Soft-start circuit, limiting AC surge current.
- Short circuit, overload , over voltage protected

INPUT VOLTAGE RANGE : 88 ~ 132VAC / 176~264VAC Selected by switch
47 ~ 63Hz; 120~370VDC
AC CURRENT : 2. 8A/115VAC 1. 7A/230VAC
INRUSH CURRENT(max.): COLD START 25A/115VAC 50A/230V
LEAKAGE CURRENT : <3. 5mA/240VAC
WORKING TEMP. HUMIDITY : -10 ~ +60°C(Refer to output load derating curve)
SAFETY STANDARDS : UL 1950, TUV EN60950 Approved
WITHSTAND VOLTAGE : I/P-O/P: 3KVAC I/P-FG: 1.5KVAC O/P-FG: 0.5KVAC

Part No.	Product No.	Manufacturer	Description	Output Volt./Current	Tol.(±)	Output Volt./Current	Tol.(±)	Tol.(±)	Output Volt./Current
12314	T-115	MEAN WELL	115W Triple Output Switching Power Supply	+5V/0~10A	+/-2%	3.3V/0~12A	+/-2%	+/-26%	12V/0~2.0A



T-120 Series

FEATURES:

- AC input range selected by switch
- 100% full load burn-in test.
- Protections: short circuit/Over load/over voltage
- Fixed switching frequency at 25KHz
- 2 years warranty



INPUT VOLTAGE RANGE : 88 ~ 132VAC / 176~264VAC Selected by switch
240~370VDC
AC CURRENT : 2. 8A/115VAC 1. 6A/230VAC
INRUSH CURRENT(max.): COLD START 35A
LEAKAGE CURRENT : <3. 5mA/240VAC
WORKING TEMP. HUMIDITY : -10 ~ +60°C(Refer to output load derating curve)
SAFETY STANDARDS : UL 60950, TUV EN60950 Approved
WITHSTAND VOLTAGE : I/P-O/P: 3KVAC I/P-FG: 1.5KVAC O/P-FG: 0.5KVAC



Part No.	Product No.	Manufacturer	Description	Output Volt./Current	Tol.(±)	Output Volt./Current	Tol.(±)	Tol.(±)	Output Volt./Current
30308	T-120A	MEAN WELL	MEAN WELL_120W Triple Output Switching Power Supply	-5V/0.2~1.0A	±6%	12V/0.5~5.0A	±6%	±2%	5V/2.0~12A
30310	T-120B	MEAN WELL	MEAN WELL_120W Triple Output Switching Power Supply	-12V/0.2~1.0A	±6%	12V/0.5~5.0A	±6%	±2%	5V/2.0~12A
29061	T-120D	MEAN WELL	120W Triple Output Switching Power Supply	5V/2~12A	±2%	12V/0.2~5A	±6%	±6%	24V/0.2~2A



FEATURES:

- AC input range selected by switch
- 100% full load burn-in test.
- Protections: short circuit/Over load/over voltage
- Cooling by free air convection
- Approvals: UL/ CUL/ TUV/ CB/ CE
- 2 years warranty



AC input voltage range : 88~132VAC / 176~264VAC selectable by switch
DC adjustment range: CH1 : -5~+10% rated output voltage
Over load protection : 105%~135% shut off, AC recycle to re-start
Over voltage protection : CH1 : 115%~135% rated output voltage
Withstand voltage : I/P-O/P: 3KVAC, I/P-FG: 1. 5KVAC, 1minute
Working temperature : 0~50°C@100%, -10°C@80%, 60°C@40% load
(D-20) /60% (T-120, Q-120)
Safety standards : UL60950-1, TUV EN 60950-1 approved
Connection : 8P/9. 5mm pitch terminal block

Part No.	Product No.	Manufacturer	Description	Output Volt./Current	Tol.(±)	Output Volt./Current	Tol.(±)	Tol.(±)	Output Volt./Current
26784	T-120C	MEAN WELL	120W Triple Output Switching Power Supply	+5V/2.0~12A	+/-2%	15V/0.5~5.0A	+10%,-5%	+10%,-5%	-15V/2.0~1.0A

● If you cannot find the components you want on the catalogue, please call us.



Taiwan : 886-3-5753170

Shanghai : 021-54151736 Shenzhen : 0755-83298787

Centenary Materials

Waiting for your phone call



T E L : Taiwan : 886-3-5753170
F A X : Taiwan : 886-3-5753172
E-mail : Taiwan : sale@100y.com.tw

Shenzhen : 86-755-83298787
Shenzhen : 86-755-83640655
Shenzhen : 100y@163.com

Shanghai : 86-21-54151736
Shanghai : 86-21-64605107
Shanghai : 100y-1@163.com