



Power Supplies & UPS

Other Type Switching Power Supply

Detailed product specifications are available on: us.100y.com.tw



FEATURES:

- 0.01% high resolution
- Constant voltage and constant current operation
- Low ripple and noise
- Overload and reverse polarity protection
- 3½ Digit 0.5" LED displays showing voltage and current
- Built-in overvoltage and overcurrent trip crowbar
- Ten-turn potentiometer
- Suitable for material and product aging



Part No.	Product No.	Manufacturer	Description	Output Volt./Current
15094	GPR-100H05D	GW Instek	Switching Power Supply	1000V/0.5A



FEATURES:

- 0.01% High regulation
- Constant voltage and constant current operation
- Low ripple and noise
- Overload and reverse polarity protection
- 3 ½ digits 0.5" LED display
- Application for material and products aging
- Built-in over voltage and over current tripped crowbar
- Ten-turn potentiometer



Part No.	Product No.	Manufacturer	Description	Output Volt./Current
13258	GPR-10HH10D	GW Instek	Switching Power Supply	1000Vdc/1A



FEATURES:

- Meet 1U rack mount system
 - Universal AC input / Full range
 - Active power factor >=94%
 - 94% Protections: Short circuit/Over load/Over voltage
 - Forced air cooling by built-in DC fan
 - With power good and fail signal output
 - Built-in remote ON-OFF control
 - Remote DC sense +5V and +3.3V
 - With +5VSB: 0 ~ 2.0A max.
 - 100% full load burn-in test
 - High efficiency
 - 2 years warranty
- INPUT VOLTAGE RANGE: 90 ~ 264VAC
 AC CURRENT(Typ.): 4.6A/115VAC 2.3A/230VAC
 INRUSH CURRENT(Typ.): 40A/115VAC 80A/230VAC
 LEAKAGE CURRENT(max.): 3mA/240VAC
 WORKING TEMP.: -10 ~ +60°C(Refer to output load derating curve)
 SAFETY STANDARDS: UL60950-1,TUV EN60950-1Approved
 WITHSTAND VOLTAGE: I/P-O/P:1.5KVAC I/P-FG:1.5KVAC
 DIMENSION: 260*83*40mm (L*W*H)



Part No.	Product No.	Manufacturer	Description
47731	IPC-300A	MEAN WELL	300W Industrial 1U ATX 12V/P4 PC POWER SUPPLY



- ZVT technology to reduce power dissipation and improve efficiency
 - Various output configuration is selectable
 - Built in active PFC, PF>0.95
 - Universal AC input/ full range
 - Remote Control on every individual output module
 - Remote Sense on every individual output module(MS-75,150,300)
 - Built in parallel function(MS-300)
 - Protections: Short circuit/Over load/Over voltage for all output modules
 - Additional 12V/0.1A auxiliary output for remote control
 - Cooling by built-in DC fan with fan alarm function
 - 3 years warranty
- WORKING TEMP.: -20 ~ +70°C(Refer to output load derating curve)
 SAFETY STANDARDS: UL60950-1,TUV EN60950-1Approved
 WITHSTAND VOLTAGE: I/P-O/P:3KVAC I/P-FG:1.5KVAC O/P-FG:0.5KVAC
 DIMENSION: PFC-450: 254*127*63.5mm (L*W*H)
 PFC-650: 278*127*63.5mm (L*W*H)
 PFC-1000: 278*177.8*63.5mm (L*W*H)



Part No.	Product No.	Manufacturer	Description	Output Volt./Current	Output Volt./Current
45524	MP1K0-2C2HEE#	MEAN WELL	1000W Modular Power		
44892	MP1K0-2CEEHM	MEAN WELL	1000W Modular Power		
39006	MP450-2CENN	MEAN WELL	450W Modular Power	5V/50A, 12V/13A	12V/6.3A, 12V/6.3A
42774	MP650-2CEEF	MEAN WELL	Digital Meter Adjustable Switching Power Supply	240VAC/9A	
42775	MP650-CEEFF	MEAN WELL	Digital Meter Adjustable Switching Power Supply	240VAC/9A	

• If you cannot find the components you want on the catalogue, please call us.



Taiwan: 886-3-5753170
 Shanghai: 021-54151736 Shenzhen: 0755-83298787

Centenary Materials
 Waiting for your phone call



T E L : Taiwan: 886-3-5753170
 F A X : Taiwan: 886-3-5753172
 E-mail: Taiwan: sale@100y.com.tw

Shenzhen: 86-755-83298787
 Shenzhen: 86-755-83640655
 Shenzhen: 100y@163.com

Shanghai: 86-21-54151736
 Shanghai: 86-21-64605107
 Shanghai: 100y-1@163.com