



Power Supplies & UPS

Other Type Switching Power Supply

Detailed product specifications are available on: us.100y.com.tw



- Model: PS-AL-3000P4 II
- Suitable for CPU and mainframe board (AMD K7)

Part No.	Product No.	Manufacturer	Description	Output Volt./Current	Tol.(±)	Output Volt./Current
14311	P4-3000TC	ICute	Switching Power Supply	(+3.3V/14A)(+5V/30A)(+12V/15A)	(-5V/0.5A)(-12V/0.5A)(+5Vsb/1.5A)	300Wmax



- Temperature coefficient: < 100ppm/°C
- Dimensions: 310mm x 250mm x133mm/12.2"x9.8"x5.2"
- Weight: 3.8kg/8.4lbs

Part No.	Product No.	Manufacturer	Description	Output Volt./Current	Output Volt./Current
14773	PROVA 8000	PROVA	Stylization Switching Power Supply	0~40V/5A +2 Support(5V/2A,3.3V/3A)	0~40V/5A,0~40V/5A +2 support



- AC input range selected by switch
- With +5VSB: 0~2.0A max.
- Power good signal output
- Power fail signal output
- Power ON-OFF switch
- Approvals: TUV/UL/CSA/CB/CE/FCC
- Forced air cooling by built-in DC fan
- 100% full load burn-in test
- 1 year warranty



Part No.	Product No.	Manufacturer	Description	Output Volt./Current	Tol.(±)	Output Volt./Current	Tol.(±)
32946	PSIV-400-2	MEAN WELL	300W ATX-12V PC Power Supply	+3.3V/5.6~28A	+/-5%	+5V/6.0~30A	+/-5%



- 0.01% high regulation
- Constant voltage and constant current operation
- Overload and reverse polarity protection
- Size: 128 (W) x145 (H) x285 (L) mm



Part No.	Product No.	Manufacturer	Description	Output Volt./Current
12012	SPS-1820	GW Instek	Digital Meter Adjustable Switching Power Supply	18V/20A
13740	SPS-606	GW Instek	Adjustable Switching Power Supply	60V/6A



- Constant voltage and constant current operation
- Load regulation: ≤0.01%+3mV
- Line regulation: ≤0.01%+3mV
- Recovery Time: ≤100us
- Temp. coefficient: ≤300ppm
- Load regulation: ≤0.2%+3mV
- Line regulation: ≤0.2%+3mV
- Dimensions: 245 (W) x140 (H) x345 (D) mm

Part No.	Product No.	Manufacturer	Description	Output Volt./Current
47921	TP2303	TWINTEX	TP-2000 DC POWER SUPPLY	0~30V/3A

Digital Linear Power Supply

Detailed product specifications are available on: us.100y.com.tw



- Output voltage: Zero to rated continuously variable with front panel coarse and fine voltage knobs
- Output current: Zero to rated current continuously variable with front panel current knob
- Line regulation: CV±0.01%+2mV; CC±0.01%+2mA
- Load regulation: CV±0.01%+2mV; CC≤10mA @ 100W; <15mA @ above 100W
- Operating range: 0 to 40°C ambient temperature
- Overload protection: automatic crossover from CV to CC mode
- Series connection: Different models can be chained to increase output up to 240Vdc
- Parallel Connection: Another same model can be paralleled to increase output to 24 Amps

Part No.	Product No.	Manufacturer	Description	ACVin	DCVout/Current(A)
45321	3185D	TOPWARD	Digital Linear Power Supply	100/120/220/240V ±10% ,50/60 Hz	0-18V/0-5A
38039	33010D	TOPWARD	Digital Linear Power Supply	100/120/220/240V ±10% ,50/60 Hz	0-30V/0-10A
31846	3303D	TOPWARD	Digital Linear Power Supply	100/120/220/240V ±10% ,50/60 Hz	0-30V/0-3A

