



Power Supplies & UPS

AC to DC Unregulated Wall Adaptor

Detailed product specifications are available on: us.100y.com.tw

Part No.	Product No.	Manufacturer	Description	Power (W)	Vin	Vout / Current
32064	ES25E05-P1J	MEAN WELL	MEAN WELL_25W AC-DC Single Output Wall-mounted type		90-264Vac	5V/4.00A
31956	ES25U05-P1J	MEAN WELL	MEAN WELL_25W AC-DC Single Output Wall-mounted type		90-264Vac	5V/4.00A
32015	ES25U07-P1J	MEAN WELL	MEAN WELL_25W AC-DC Single Output Wall-mounted type		90-264Vac	7.5V/2.80A
32017	ES25U09-P1J	MEAN WELL	MEAN WELL_25W AC-DC Single Output Wall-mounted type		90-264Vac	9V/2.50A
32018	ES25U12-P1J	MEAN WELL	MEAN WELL_25W AC-DC Single Output Wall-mounted type		90-264Vac	12V/2.08A
32019	ES25U15-P1J	MEAN WELL	MEAN WELL_25W AC-DC Single Output Wall-mounted type		90-264Vac	15V/1.67A
32020	ES25U18-P1J	MEAN WELL	MEAN WELL_25W AC-DC Single Output Wall-mounted type		90-264Vac	18V/1.40A
32021	ES25U24-P1J	MEAN WELL	MEAN WELL_25W AC-DC Single Output Wall-mounted type		90-264Vac	24V/1.04A
32022	ES25U28-P1J	MEAN WELL	MEAN WELL_25W AC-DC Single Output Wall-mounted type		90-264Vac	28V/0.90A
32023	ES25U36-P1J	MEAN WELL	MEAN WELL_25W AC-DC Single Output Wall-mounted type	25W	90-264Vac	36Vdc/0.70A
32024	ES25U48-P1J	MEAN WELL	MEAN WELL_25W AC-DC Single Output Wall-mounted type		90-264Vac	48V/0.52A



FEATURES:

- Compact size, light weight
- Over load protection
- DC output plug option
- Short circuit protection
- Low cost/high reliability
- 100% full load burn-in test
- 1 year warranty

Input

Input range : 90-240VAC (Full range) ,47-63Hz
 Input current (rms) :160mA@90VAC. 80mA@264VAC MAX
 Efficiency : >80%@full load, 115VAC (DC Conversion)

Output

Voltage (Vo) :+5V~+12V
 Voltage regulation :±8%@constant voltage mode
 Current limit :±8%@constant current mode
 Maximum power (Po) :5W

Environmental

Operating temperature :0°C to +40°C ambient
 Storage temperature : -10°C to +70°C
 Humidity :20%~90%RH

Part No.	Product No.	Description
24404	FA033-1000	DC output plug option



FEATURES:

- Compact size, light weight
- Over load protection
- DC output plug option
- Short circuit protection
- Low cost/high reliability
- 100% full load burn-in test
- 1 year warranty

Input

Input range : 90-240VAC (Full range) ,47-63Hz
 Input current (rms) :160mA@90VAC. 80mA@264VAC MAX
 Efficiency : >80%@full load, 115VAC (DC Conversion)

Output

Voltage (Vo) :+5V~+12V
 Voltage regulation :±5%@constant voltage mode
 Current limit :±5%@constant current mode
 Maximum power (Po) :15W

Environmental

- Operating temperature :0°C to +40°C ambient
- Storage temperature : -10°C to +70°C
- Humidity :20%~90%RH

Part No.	Product No.	Description	Vin	Vout / Current
32117	FA050-2000	AC to DC Unregulated Wall Adaptor	AC100-240V	DC5V 2A
40632	FA050-2000 2P+2.1	AC to DC Unregulated Wall Adaptor	AC100-240V	DC5V 2A



FEATURES:

- Compact size, light weight
- Over load protection
- DC output plug option
- Short circuit protection
- Low cost/high reliability
- 100% full load burn-in test
- 1 year warranty

Input

Input range : 100-240VAC (Full range) ,47-63Hz
 Input current (rms) :160mA@90VAC. 80mA@264VAC MAX
 Efficiency : >80%@full load, 115VAC (DC Conversion)

Output

Voltage (Vo) :+5V~+12V
 Voltage regulation :±8%@constant voltage mode
 Current limit :±8%@constant current mode
 Maximum power (Po) :12W

Environmental

Operating temperature :0°C to +40°C ambient
 Storage temperature : -10°C to +60°C
 Humidity :20%~90%RH

Part No.	Product No.	Description	Vin	Vout / Current
17845	FA060-1500	AC to DC Unregulated Wall Adaptor	AC100-240V	DC6V 1.5A
24350	FA090-1200	DC output plug option		



FA120-1000	
Input	AC 100-240V
Output	DC 12V
Output current	1. A
Maximum output power	3. 3W
Dimensions	46x35x21mm
Weight	70g

- Small Volume (4. 6x3. 5x2. 1 centimetre)
- Light weight, take easy
- High load (Max 1100mA)
- Steady voltage, and have protect action



Apply for scanner, telephone, personal stereo, transducer, PDA.....

Part No.	Product No.	Description	Vin	Vout / Current
18601	FA120-1000	AC to DC Unregulated Wall Adaptor	AC100-240V	DC12V 1A



T E L : Taiwan : 886-3-5753170
 F A X : Taiwan : 886-3-5753172
 E-mail : Taiwan : sale@100y.com.tw

Shenzhen : 86-755-83298787
 Shenzhen : 86-755-83640655
 Shenzhen : 100y@163.com

Shanghai : 86-21-54151736
 Shanghai : 86-21-64605107
 Shanghai : 100y-1@163.com