



Power Supplies & UPS

AC to DC Regulated Wall Adaptor

Detailed product specifications are available on: us.100y.com.tw



FEATURES:

- Output Power Range : 10W ~ 15W
- Operation Temperature : 0°C ~ 40°C
- Storage Temperature : -40 °C ~ 85°C
- Protection Mode: Short Circuit Protection, Over Voltage Protection, Over Load Protection
- AV Input Plug Available : Wall Mount Type With USA/Japan, European, UK, Australia
- Dimension : 55x48x28mm
- No load standby power: 0. 1~0. 6Wmax

Part No.	Product No.	Description	Vin	Vout / Current	CSA/CUL Approved
47823	AD-12V1A	sunfone_AC to DC Unregulated Wall Adaptor	100~240VAC	12VDC/1.2A	CUL



- | | | |
|---|--|---|
| AD-3000
Input voltage: AC110V
Output voltage: DC3V
Output current: 350mA
Power: 1W | AD-6000
Input voltage: AC110V
Output voltage: DC6V
Output current: 350mA
Power: 2. 1W | AD-9000
Input voltage: AC110V
Output voltage: DC9V
Output current: 350mA
Power: 3. 15W |
|---|--|---|

Part No.	Product No.	Description	Power (W)	Vin	Vout / Current	CSA/CUL Approved
7722	AD-3000	AC to DC Regulated Wall Adaptor	1W	AC110V	3VDC/350mA	CNS Approve
6646	AD-6000	AC to DC Regulated Wall Adaptor	2.1W	110V 60Hz	6VDC/350mA	CNS Approve
6645	AD-9000	AC to DC Regulated Wall Adaptor	3.15W	110V 60Hz	9VDC/350mA	CNS Approve



FEATURES:

- Universal AC input/ Full range
- 3 pole AC inlet IEC320-C14
- Class I power (with earth pin)
- Full output 3~48V safety approval
- Protections: short circuit/ Over load/ over voltage
- RCC control circuit and regulated
- Fully enclosed plastic case
- LED for power on
- Approvals: UL/ CUL/ TUV/ CCC/ CB/ CE
- 1 year warranty

VOLTAGE RANGE : 90~264VAC/135~370VDC
 AC CURRENT : 0.5A/100VAC
 INRUSHCURRENT(max.) : 40A/230VAC
 LEAKAGECURRENT(max.) : 0.75mA/240VAC
 WORKINGTEMP. : 0~+50°C(Refer to output load derating curve)
 SAFETYSTANDARDS : UL60950-1,CSAC22.2,TUVEN60950-1Approved
 WITH STANDVOLTAGE : I/P-O/P:3KVAC,I/P-FG:1.5KVAC
 DIMENSION : 93*54*36mm(L*W*H)

Part No.	Product No.	Manufacturer	Description	Power (W)	Vin	Vout / Current	CSA/CUL Approved
33784	ES18A12-P1J	MEAN WELL	18W AC-DC Single Output Adaptor	18W	90 ~ 264VAC 135~370VDC	12V/1.50A	UL/ CUL/TUV/CCC/CB/CE



AC to DC Regulated Wall Adaptor

Part No.	Product No.	Description	Vin	Vout / Current
41830	FA075-1300	AC to DC Regulated Wall Adaptor	AC100~240V/350mA	DC7.5V/1200mA



FEATURES:

- Universal AC input / Full range pole
- 2 pole USA plug
- Class II power (without earth pin)
- Full output 3~48V safety approval
- Protections: Short circuit/ Over load/ Over voltage
- RCC control circuit and regulated
- Pass LPS for 9~48V output
- Fully enclosed plastic case
- Approvals: UL/ CUL/ CB/ CE
- 1 year warranty

VOLTAGE RANGE : 90 ~ 264VAC/135~370VDC
 AC CURRENT : 0.5A/ 100VAC
 INRUSH CURRENT (max.) : 20A/ 115VAC
 LEAKAGE CURRENT (max.) : 0.25mA/ 240VAC
 WORKING TEMP. : 0~+40°C(Refer to output load derating curve)
 SAFETY STANDARDS : UL60950, CSA22.2Approved
 WITHSTAND VOLTAGE : I/P-O/P:3KVAC
 DIMENSION : 80*53*39mm (L*W*H)



Part No.	Product No.	Description	Power (W)	Vin	Vout / Current	CSA/CUL Approved
21196	G15U-0P2J	7.2 ~ 15WAC-DC Wall Mount Adaptor	12W	90 ~ 264VAC 135~370VDC	3.3V/2.18A	UL/ CUL/ CB/ CE
21197	G15U-1-1P2J	7.2 ~ 15WAC-DC Wall Mount Adaptor	12W	90 ~ 264VAC 135~370VDC	7.5V/1.6A	UL/ CUL/ CB/ CE
21198	G15U-2P2J	7.2 ~ 15WAC-DC Wall Mount Adaptor	12W	90 ~ 264VAC 135~370VDC	9V/1.66A	UL/ CUL/ CB/ CE
21199	G15U-3P2J	7.2 ~ 15WAC-DC Wall Mount Adaptor	12W	90 ~ 264VAC 135~370VDC	12V/1.25A	UL/ CUL/ CB/ CE
21200	G15U-4P2J	7.2 ~ 15WAC-DC Wall Mount Adaptor	12W	90 ~ 264VAC 135~370VDC	15V/1A	UL/ CUL/ CB/ CE
21201	G15U-5P2J	7.2 ~ 15WAC-DC Wall Mount Adaptor	12W	90 ~ 264VAC 135~370VDC	18V/0.83A	UL/ CUL/ CB/ CE
21202	G15U-6P2J	7.2 ~ 15WAC-DC Wall Mount Adaptor	12W	90 ~ 264VAC 135~370VDC	24V/0.62A	UL/ CUL/ CB/ CE
21203	G15U-8P2J	7.2 ~ 15WAC-DC Wall Mount Adaptor	12W	90 ~ 264VAC 135~370VDC	48V/0.31A	UL/ CUL/ CB/ CE

• We provide a wide range of products to development and maintenance engineers in all type of business

Centenary Materials



T E L : Taiwan : 886-3-5753170
 F A X : Taiwan : 886-3-5753172
 E-mail : Taiwan : sale@100y.com.tw

Shenzhen : 86-755-83298787
 Shenzhen : 86-755-83640655
 Shenzhen : 100y@163.com

Shanghai : 86-21-54151736
 Shanghai : 86-21-64605107
 Shanghai : 100y-1@163.com