



Power Supplies & UPS

AC to AC Unregulated Wall Adaptor

Detailed product specifications are available on: us.100y.com.tw

AC to AC Unregulated Wall Adaptor



1-2-100W



2-1-180W

Part No.	Product No.	Description	Power (W)	Vin	Vout / Current
5746	1-2-100W	AC to AC Unregulated Wall Adaptor	100W	110V	220V
5399	2-1-180W	AC to AC Unregulated Wall Adaptor	180W	AC220V	AC110V

AA600W

Output voltage: 100V

Input voltage: 110V

Output power: 600W

Input: 50/60Hz

Suitable for Video, electrograph etc



AA120W



AA600W

Part No.	Product No.	Description	Power (W)	Vin	Vout / Current
42770	AA120W	AC to AC Unregulated Wall Adaptor	120W	AC110V	AC100V
5755	AA600W	AC to AC Unregulated Wall Adaptor	600W	110V	100V

Size: 360 (W) x150 (H) x266 (D) mm

Weight: 10.0kg



Part No.	Product No.	Description	Vin	Vout / Current
6224	AC110V/24V/1A	AC to AC Unregulated Wall Adaptor	AC110V	AC24V/1A



AC110V/AC9V ADAPTOR



AC9V-2A
AC12V1A AC220V/24V/1A



AC220V/24V/1A

AC to DC Unregulated Wall Adaptor

Part No.	Product No.	Description	Power (W)	Vin	Vout / Current
41392	AC110V/AC9V ADAPTOR	AC to DC Unregulated Wall Adaptor		AC120V~60Hz	AC 9V 200mA
6223	AC12V1A	AC to AC Unregulated Wall Adaptor		AC110V	AC12V/1A
23909	AC220V/24V/1A	AC to AC Unregulated Wall Adaptor		AC220V	AC24V/1A
40388	AC220V/24V/1A	AC to AC Unregulated Wall Adaptor		AC220V	AC24V/1A
16943	AC9V-2A	AC to AC Unregulated Wall Adaptor	18W	110Vac	9V/2A



80x55x32mm

- Universal AC input/full range
- 2 pole USA plug
- Class II power (without earth pin)
- Protections: short circuit/over load/over voltage
- RCC control, low cost for high quantity
- Approvals: UL/CSA/CE/FCC
- 1 year warranty



AC input voltage range: 90~264VAC/0.5A
 AC inrush current: cold start, <20A peak@115VAC
 Over load protection: hiccup mode, auto-recovery
 Over voltage protection: clamp by zener diode >110%
 Setup, hold up time: 200ms, 8ms at full load and 115VAC
 Withstand voltage: I/P-O/P: 3KVAC, 1 minute
 Working temperature: 0~40°C@100%, 50°C@70% load
 Safety standards: UL 1950, CSA 22.2 approved
 EMC standards: FCC, part 15, class B
 Length of output cable: 180cm of SPT-1, 18AWGx2C
 Standard plug of DC output: 2.1øx5.5øx11cm, center~+ "

Part No.	Product No.	Manufacturer	Description	Power (W)	Vin	Vout / Current
20773	L15D05B-P1J	MEAN WELL	AC to AC Unregulated Wall Adaptor	UL/CAS/FCC	90~264VAC/0.5A	5V/2.0A



80x55x32mm

- FEATURES:**
- 2 pole USA plug
 - Class II power (without earth pin)
 - Universal AC input / Full range
 - Protections: Short circuit/ Over load/ Over voltage
 - Topology: R.C.C. Circuit
 - 100% full load burn-in test
 - Fully enclosed plastic case
 - Approvals: UL/ CSA/ FCC/ CE
 - 1 year warranty



INPUT VOLTAGE RANGE: 90 ~ 264VAC 135~370VDC
 AC CURRENT: 0.5A/ 115VAC
 INRUSH CURRENT (max.): 20A/ 115VAC
 LEAKAGE CURRENT (max.): 0.25mA/ 240VAC
 OVER LOAD: 150~250% rated output power
 Protection type : Hiccup mode, recovers automatically after fault condition is removed
 WORKING TEMP.: 0~+70°C(Refer to output load derating curve)
 SAFETY STANDARDS: UL1950, CSA22.2Approved
 WITHSTAND VOLTAGE: I/P-O/P:3KVAC
 DIMENSION: 80*55*32mm (L*W*H)
 PACKING: 220g ; 70pcs / 17kg / CARTON

Part No.	Product No.	Manufacturer	Description	Power (W)	Vin	Vout / Current
21204	L15D12B-P1J	MEAN WELL	AC to AC Unregulated Wall Adaptor	UL/CAS/FCC	90~264VAC/0.5A	12V/1.25A
21206	L15D24B-P1J	MEAN WELL	AC to AC Unregulated Wall Adaptor	UL/CAS/FCC	90~264VAC/0.5A	24V/0.5A

