




Relays & Solenoids

DELCON_Solid State Relay

Detailed product specifications are available on: us.100y.com.tw



- Plug-in input relay for 220...240 VAC voltages
- 50 mA maximum load current
- 0...60 VDC load voltage
- Works without logic supply (4 pole)
- For PLC input signal conditioning

- Immune to disturbances on signal lines
- Shielded signal cabling not required
- cULus tested (UL and CSA)
- CE (EMC and LVD)
- Integrated status LED




Block diagram



Temperature range:
 Storage: -40°C...+70°C
 Operation: -25°C...+70°C

Part No.	Product No.	Manufacturer	Description	Vrms
36930	SLI 230CR	DELCON	Input Plug-in Relay 230 VAC	220-240VAC




- Plug-in input relay for 220...240 VAC voltages
- 100 mA maximum load current
- 0...60 VDC load voltage
- Secondary is conducting without input signal (NC)
- For PLC input signal conditioning

- Immune to disturbances on signal lines
- Shielded signal cabling not required
- cULus tested (UL and CSA)
- CE (EMC and LVD)
- Integrated status LED




Block diagram



Temperature range:
 Storage: -40°C...+70°C
 Operation: -25°C...+70°C

Part No.	Product No.	Manufacturer	Description	Vrms
36932	SLI 230CRI	DELCON	Input Plug-in Relay 230VAC, Normally Closed	220-240VAC



- Plug-in input relay for 220...240 VAC voltages
- 50 mA load current (limited at 24 VDC)
- 0...24 VDC load voltage (maximum 60 VDC)
- Works without logic supply (4 pole)
- For PLC input signal conditioning

- Immune to disturbances on signal lines
- Shielded signal cabling not required
- cULus tested (UL and CSA)
- CE (EMC and LVD)
- Integrated status LED




Block diagram



Temperature range:
 Storage: -40°C...+70°C
 Operation: -25°C...+70°C

Part No.	Product No.	Manufacturer	Description	Vrms
36937	SLI 230CRR	DELCON	Input Plug-in Relay 230VAC, Current Limiting Secondary	2 0-240VAC




- Plug-in input relay for 24 VDC voltage
- 50 mA maximum load current
- 0...60 VDC load voltage
- Switches up to 1 kHz signals
- Works without logic supply (4 pole)
- For PLC input signal conditioning

- Immune to disturbances on signal lines
- Shielded signal cabling not required
- cULus tested (UL and CSA)
- CE (EMC and LVD)
- Integrated status LED




Temperature range:
 Storage: -40°C...+70°C
 Operation: -25°C...+70°C

Block diagram



Part No.	Product No.	Manufacturer	Description	Vrms
36938	SLI 24CR	DELCON	Input Plug-in Relay 24 VDC	24VDC



- Plug-in fast input relay for 24 VDC voltage
- Switching frequency up to 10 kHz
- 50 mA maximum load current
- 0...60 VDC load voltage
- Works without logic supply (4 pole)
- For PLC input signal conditioning

- Immune to disturbances on signal lines
- Shielded signal cabling not required
- cULus tested (UL and CSA)
- CE (EMC and LVD)
- Integrated status LED



Temperature range:
 Storage: -40°C...+70°C
 Operation: -25°C...+70°C

Block diagram



Part No.	Product No.	Manufacturer	Description	Vrms
36940	SLI 24CRF	DELCON	Input Plug-in Relay 24VDC, Fast	24VDC

