




Relays & Solenoids

DELCON_Solid State Relay

Detailed product specifications are available on: us.100y.com.tw




- Plug-in input relay for 24 VDC voltage
- 100 mA maximum load current
- 0...60 VDC load voltage
- Secondary is conducting without input signal (NC)
- Works without logic supply (4 pole)

- For PLC input signal conditioning
- Immune to disturbances on signal lines
- Shielded signal cabling not required
- CE (EMC and LVD)
- Integrated status LED




Block diagram



Temperature range:
 Storage: -40°C...+70°C
 Operation: -25°C...+70°C

Part No.	Product No.	Manufacturer	Description	Vrms
36942	SLI 24CRI	DELCON	Input Plug-in Relay 24VDC, Normally Closed	24VDC




- Plug-in input relay for 24 VDC voltage
- Minimum input current 15 mA
- 50 mA maximum load current
- 0...60 VDC load voltage
- Switches up to 1 kHz signals
- Works without logic supply (4 pole)

- For PLC input signal conditioning
- Immune to disturbances on signal lines
- Shielded signal cabling not required
- cULus tested (UL and CSA)
- CE (EMC and LVD)
- Integrated status LED




Block diagram



Temperature range:
 Storage: -40°C...+70°C
 Operation: -25°C...+70°C

Part No.	Product No.	Manufacturer	Description	Vrms
36943	SLI 24CRL	DELCON	Input Plug-in Relay 24 VDC, Increased Input Current	24VDC




- Plug-in input relay for 220...250 VDC voltages
- 50 mA maximum load current
- 0...60 VDC load voltage
- Works without logic supply (4 pole)
- For PLC input signal conditioning

- Internal transient protection in input side
- Shielded signal cabling not required
- cULus tested (UL and CSA)
- CE (EMC and LVD tested)
- Integrated status LED




Block diagram



Temperature range:
 Storage: -40°C...+70°C
 Operation: -25°C...+70°C

Part No.	Product No.	Manufacturer	Description	Vrms
36944	SLI 250CH	DELCON	Input Plug-in Relay 250 VDC, Transient Protection	220-250VDC




- Plug-in input relay for 220...250 VDC voltages
- 50 mA maximum load current
- 0...60 VDC load voltage
- Switches up to 500 Hz signals
- Works without logic supply (4 pole)
- For PLC input signal conditioning

- Immune to disturbances on signal lines
- Shielded signal cabling not required
- cULus tested (UL and CSA)
- CE (EMC and LVD)
- Integrated status LED




Block diagram



Temperature range:
 Storage: -40°C...+70°C
 Operation: -25°C...+70°C

Part No.	Product No.	Manufacturer	Description	Vrms
36945	SLI 250CR	DELCON	Input Plug-in Relay 250 VDC	220-250VDC




- Plug-in input relay for 220...250 VDC voltages
- 100 mA maximum load current
- 0...60 VDC load voltage
- Secondary is conducting without input signal (NC)
- Works without logic supply (4 pole)

- For PLC input signal conditioning
- Immune to disturbances on signal lines
- Shielded signal cabling not required
- CE (EMC and LVD)
- Integrated status LED



Block diagram



Temperature range:
 Storage: -40°C...+70°C
 Operation: -25°C...+70°C

Part No.	Product No.	Manufacturer	Description	Vrms
36946	SLI 250CRI	DELCON	Input Plug-in Relay 250 VDC, Normally Closed	220-250VDC

