


# Semiconductors-Discretes

## DACO Standard Rectifiers

Detailed product specifications are available on: [us.100y.com.tw](http://us.100y.com.tw)

Case style P600



Dimensions in inches and (millimeters)

Part No.	Product No.	Manufacturer	Description	Iav (A)	Vrrm
34397	P600B	VISHAY	GENERAL PURPOSE PLASTIC RECTIFIER	1mA	100V
34401	P600D	VISHAY	GENERAL PURPOSE PLASTIC RECTIFIER	1mA	200V
34407	P600K	VISHAY	GENERAL PURPOSE PLASTIC RECTIFIER	1mA	800V
34408	P600M	VISHAY	GENERAL PURPOSE PLASTIC RECTIFIER	1mA	1000V

## Silicon Rectifiers

Detailed product specifications are available on: [us.100y.com.tw](http://us.100y.com.tw)

<p><b>DO-41</b></p>	<p><b>DO-15</b></p> <table border="1"> <thead> <tr> <th>Dim</th> <th>Min</th> <th>Max</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>25.4</td> <td>—</td> </tr> <tr> <td>B</td> <td>6.50</td> <td>7.62</td> </tr> <tr> <td>C</td> <td>0.71</td> <td>0.864</td> </tr> <tr> <td>D</td> <td>2.60</td> <td>3.80</td> </tr> </tbody> </table> <p>All Dimensions in mm</p>	Dim	Min	Max	A	25.4	—	B	6.50	7.62	C	0.71	0.864	D	2.60	3.80	<p><b>AXIAL LEAD</b> CASE 59-10 ISSUE S</p> <table border="1"> <thead> <tr> <th rowspan="2">DIM</th> <th colspan="2">INCHES</th> <th colspan="2">MILLIMETERS</th> </tr> <tr> <th>MIN</th> <th>MAX</th> <th>MIN</th> <th>MAX</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>0.161</td> <td>0.206</td> <td>4.10</td> <td>5.20</td> </tr> <tr> <td>B</td> <td>0.079</td> <td>0.106</td> <td>2.00</td> <td>2.70</td> </tr> <tr> <td>D</td> <td>0.028</td> <td>0.034</td> <td>0.71</td> <td>0.86</td> </tr> <tr> <td>F</td> <td>—</td> <td>0.050</td> <td>—</td> <td>1.27</td> </tr> <tr> <td>K</td> <td>1.000</td> <td>—</td> <td>25.40</td> <td>—</td> </tr> </tbody> </table>	DIM	INCHES		MILLIMETERS		MIN	MAX	MIN	MAX	A	0.161	0.206	4.10	5.20	B	0.079	0.106	2.00	2.70	D	0.028	0.034	0.71	0.86	F	—	0.050	—	1.27	K	1.000	—	25.40	—	<p><b>AXIAL LEAD</b> CASE 267-05 ISSUE G</p> <table border="1"> <thead> <tr> <th rowspan="2">DIM</th> <th colspan="2">INCHES</th> <th colspan="2">MILLIMETERS</th> </tr> <tr> <th>MIN</th> <th>MAX</th> <th>MIN</th> <th>MAX</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>0.287</td> <td>0.374</td> <td>7.30</td> <td>9.50</td> </tr> <tr> <td>B</td> <td>0.189</td> <td>0.209</td> <td>4.80</td> <td>5.30</td> </tr> <tr> <td>D</td> <td>0.047</td> <td>0.051</td> <td>1.20</td> <td>1.30</td> </tr> <tr> <td>K</td> <td>1.000</td> <td>—</td> <td>25.40</td> <td>—</td> </tr> </tbody> </table>	DIM	INCHES		MILLIMETERS		MIN	MAX	MIN	MAX	A	0.287	0.374	7.30	9.50	B	0.189	0.209	4.80	5.30	D	0.047	0.051	1.20	1.30	K	1.000	—	25.40	—
Dim	Min	Max																																																																															
A	25.4	—																																																																															
B	6.50	7.62																																																																															
C	0.71	0.864																																																																															
D	2.60	3.80																																																																															
DIM	INCHES		MILLIMETERS																																																																														
	MIN	MAX	MIN	MAX																																																																													
A	0.161	0.206	4.10	5.20																																																																													
B	0.079	0.106	2.00	2.70																																																																													
D	0.028	0.034	0.71	0.86																																																																													
F	—	0.050	—	1.27																																																																													
K	1.000	—	25.40	—																																																																													
DIM	INCHES		MILLIMETERS																																																																														
	MIN	MAX	MIN	MAX																																																																													
A	0.287	0.374	7.30	9.50																																																																													
B	0.189	0.209	4.80	5.30																																																																													
D	0.047	0.051	1.20	1.30																																																																													
K	1.000	—	25.40	—																																																																													
<p><b>DO-201AD</b></p> <table border="1"> <thead> <tr> <th>Dim</th> <th>Min</th> <th>Max</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>25.4</td> <td>—</td> </tr> <tr> <td>B</td> <td>8.60</td> <td>9.50</td> </tr> <tr> <td>C</td> <td>1.20</td> <td>1.30</td> </tr> <tr> <td>D</td> <td>5.0</td> <td>5.60</td> </tr> </tbody> </table> <p>All Dimensions in mm</p>	Dim	Min	Max	A	25.4	—	B	8.60	9.50	C	1.20	1.30	D	5.0	5.60	<p><b>DO-35</b></p>		<p><b>AXIAL LEAD BUTTON</b> CASE 194-04 ISSUE H</p> <table border="1"> <thead> <tr> <th rowspan="2">DIM</th> <th colspan="2">INCHES</th> <th colspan="2">MILLIMETERS</th> </tr> <tr> <th>MIN</th> <th>MAX</th> <th>MIN</th> <th>MAX</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>0.332</td> <td>0.342</td> <td>8.43</td> <td>8.69</td> </tr> <tr> <td>B</td> <td>0.234</td> <td>0.246</td> <td>5.94</td> <td>6.25</td> </tr> <tr> <td>D</td> <td>0.060</td> <td>0.053</td> <td>1.27</td> <td>1.35</td> </tr> <tr> <td>K</td> <td>0.990</td> <td>1.010</td> <td>25.15</td> <td>25.65</td> </tr> </tbody> </table>	DIM	INCHES		MILLIMETERS		MIN	MAX	MIN	MAX	A	0.332	0.342	8.43	8.69	B	0.234	0.246	5.94	6.25	D	0.060	0.053	1.27	1.35	K	0.990	1.010	25.15	25.65																																		
Dim	Min	Max																																																																															
A	25.4	—																																																																															
B	8.60	9.50																																																																															
C	1.20	1.30																																																																															
D	5.0	5.60																																																																															
DIM	INCHES		MILLIMETERS																																																																														
	MIN	MAX	MIN	MAX																																																																													
A	0.332	0.342	8.43	8.69																																																																													
B	0.234	0.246	5.94	6.25																																																																													
D	0.060	0.053	1.27	1.35																																																																													
K	0.990	1.010	25.15	25.65																																																																													

Part No.	Product No.	Manufacturer	Description	Iav (A)	Pins/Package	Vrrm
8049	1N400	LITE-ON	General purpose plastic rectifier	1A	DO-41	100V
39174	1N4001	GOODWORK	1.0AMP SILICON RECTIFIER	1.0	DO-41	50
39407	1N4002	GOOD-ARK	"GD"1.0AMP SILICON RECTIFIER	1.0	DO-41	100
7584	1N4003	LITE-ON	General purpose plastic rectifier	1A	DO-41	200V
32203	1N4004	CHENG-YI	1.0AMP SILICON RECTIFIER	1.0	DO-41	400
8558	1N4004		General purpose plastic rectifier	1A	DO-41	400V
39405	1N4004	GOOD-ARK	"GD"1.0AMP SILICON RECTIFIER	1.0	DO-41	400
24070	1N4006	ON-Semi.	Axial Lead Standard Recovery Rectifier	30A	Axial Lead	800V
4040	1N4007		General Purpose Rectifiers	1A	DO-41	1000V
8478	1N5392	LITE-ON	General Purpose Rectifier	1.5A	DO-15	100V
8479	1N5397		General purpose plastic rectifier	1.5A	DO-15	600V
7750	1N5402	LITE-ON	Standard Recovery Rectifier	3A	DO-201AD	200V
23169	1N5402-TB		SILICON RECTIFIER	200A	DO-201AD	200V
8477	1N5404		Standard Recovery Rectifier	3A	DO-201AD	400V
8127	1N5408	LITE-ON	General Purpose Plastic Rectifiers	3A	DO-201AD	1000V
49279	1N965B	POWER INT.	FAIRCHILD_Zener		DO-35	
35595	1SR139-400	ROHM	Rectifier diode	1.0A	DO-41	400V
35598	1SR139-600	ROHM	Rectifier diode	1.0A	DO-41	600V
40907	BAT54WS	PANJIT	PHOTON COUPLED ISOLATOR Ga As INFRARED EMITTING DIODE & LIGHT ACTIVATED SCR	6mA	SMD	1.5V
22501	BY255/T		MEDIUM CURRENT PLASTIC RECTIFIER	100Amps	DO-201AD	1300V
45040	D3SB60		General Purpose Rectifiers	4A	CASE	600V
22590	HER107		HIGH EFFICIENCY RECTIFIER	30Amps	DO-41	800V
8480	LT6A04	LITE-ON	Plastic silicon rectifier	6A	R-6	400V
35480	MR750	ON-Semi.	High Current Lead Mounted Rectifiers	6.0A	Axial Lead	50V
35481	MR751	ON-Semi.	High Current Lead Mounted Rectifiers	6.0A	Axial Lead	100V
35482	MR752	ON-Semi.	High Current Lead Mounted Rectifiers	6.0A	Axial Lead	200V

