


Drivers & Interface IC

Line Driver and Receivers RS-232 Line Drives & Receivers

Detailed product specifications are available on: us.100y.com.tw



Part No.	Product No.	Manufacturer	Description	Pins/Package	Supply voltage	Operating Temp
32621	ADM1385ARS	ADI	Low Power, +3.3 V, RS-232 Line Drivers/Receivers	20P/SSOP	+3.3 V	-40°C to +85°C
32622	ADM202EAN	ADI	EMI Compliant, 615 kV ESD Protected, RS-232 Line Drivers/Receivers	16P/DIP	+5 V ± 10%	-40°C to +85°C
32624	ADM208EAN	ADI	EMI/EMC Compliant, 615 kV ESD Protected, RS-232 Line Drivers/Receivers	24P/DIP	5V	-40°C to +85°C
32625	ADM232AAN	ADI	High Speed, +5 V, 0.1 μF CMOS RS-232 Drivers/Receivers	16P/DIP	+5V	-40°C to +85°C
32626	ADM232LJN	ADI	+5 V Powered CMOS RS-232 Drivers/Receivers	16P/DIP	+5V	0°C to +70°C
41429	ADM3202ARNZ	ADI	Low Power, +3.3 V, RS-232 Line Drivers/Receivers	16P/TSSOP	+3.3 V	-40°C to +85°C
32627	ADM3202ARU	ADI	Low Power, +3.3 V, RS-232 Line Drivers/Receivers	16P/TSSOP	+3.3 V	-40°C to +85°C
3899	DS1488M	N.S	Quad Line Driver	14P/SOIC	15V	0°C to +75°C
19322	DS1488N	N.S	Quad Line Driver	14P/DIP	-15 to +15V	0°C to +75°C
3900	DS1489AM	N.S	Quad Line Receiver SMD	14P/SOIC	10V	0°C to +75°C
19323	DS1489AN	N.S	Quad Line Receiver	14P/DIP	10V	0°C to +75°C
41427	DS1489N	N.S	Quad Line Receiver	14P/DIP	10V	0°C to +75°C
42587	DS14C535MSAX	N.S	+5V Supply EIA/TIA-2323x5 Driver/Receiver	28 SSOP	?0.3V to +6V	
33016	DS14C88N	N.S	QUAD CMOS Line Driver	14P/DIP	±4.5V to ±12.6V	0°C to +75°C
33017	DS14C89AM	N.S	Quad CMOS Receiver	14P/SOIC	4.5V-5.5V	0°C to +75°C
33018	DS14C89AN	N.S	Quad CMOS Receiver	14P/DIP	4.5V-5.5V	0°C to +75°C
33030	DS275	DALLAS	Line-Powered RS-232 Transceiver Chip	8-pin DIP	4.5V-5.5V	0°C to 70°C
33031	DS275S	DALLAS	Line-Powered RS-232 Transceiver Chip	8-pin SOIC	4.5V-5.5V	0°C to 70°C
33032	DS276	DALLAS	Low Power Transceiver Chip	8-Pin DIP	2.7V-5.5V	0°C to 70°C
33033	DS276S	DALLAS	Low Power Transceiver Chip	8-Pin SOIC	3V-5.5V	0°C to 70°C
23549	DS75154N	N.S	Quad Line Receiver	16P/DIP	4.5-5.5V	-65~150°C
45297	DS90LV019TM	N.S	3.3V or 5V LVDS Driver/Receiver	M14A	5.5	-40~85°C
31960	GD75232	T.I.	MULTIPLE RS-232 DRIVERS AND RECEIVERS	SMD		
19311	HIN202ECBN	Intersil	+5V Powered RS-232 Transmitters/Receivers with 0.1 Microfarad External Capacitors	SMD	5V	0~70°C
19310	HIN213ECA-T	Intersil	+5V Powered RS-232 Transmitters/Receivers with 0.1 Microfarad External Capacitors	SSOP		
40160	HIN232CBZ-T	Intersil	+5V Powered RS-232 Transmitters/Receiver-Pb Free	16P/SOIC	5V	0~70 °C
11379	HIN232CPZ	Intersil	+5V Powered RS-232 Transmitters/Receiver-Pb Free	16P/DIP	5V	0 to 70
33608	ICL232CPE	Intersil	+5V Powered, Dual RS-232 Transmitter/Receiver	16 Ld PDIP	5V	0°C to +70°C
40188	ICL3232CP	Intersil	RS-232 Transmitters/Receiver	16P/DIP	+3V~ +5.5V	0 ~70
24095	ICL3232CV	Intersil	RS-232 Transmitters/Receiver	16P/TSSOP	+3V~ +5.5V	0 ~70
49824	LT1137ACSW	Linear-Tech.	5V RS232 Driver/receiver with small capacitor	28P/SO	5V	0°C ~ +70°C
7727	LT1281ACN	Linear-Tech.	Low Power 5V RS232 Dual Driver/Receiver with 0.1μF Capacitors	16P/DIP	5V	0°C to 70°C
34897	MAX1488ECPD	MAXIM	±15kV ESD-Protected, Quad, Low-Power RS-232 Line Driver	14 Plastic DIP	14V	0°C to +70°C
34898	MAX1489ECPD	MAXIM	±15kV ESD-Protected, Quad, Low-Power RS-232 Line Receiver	14 Plastic DIP	7V	0°C to +70°C
34908	MAX202CPE	MAXIM	+5V, RS-232 Transceivers with 0.1μF External Capacitors	16P/DIP	5V	0~70°C
22705	MAX202CSE-T	MAXIM	+5V, RS-232 Transceivers with 0.1μF External Capacitors	16P/DIP	-0.3~6V	0~70°C
42258	MAX202CWE	MAXIM	+5V, RS-232 Transceivers with 0.1μF External Capacitors	16 Wide SO	5V	0°C to +70°C
34909	MAX202ECPE	MAXIM	±15kV ESD-Protected, +5V RS-232 Transceivers	16 Plastic DIP	5V	0°C to +70°C
34910	MAX202ECSE	MAXIM	±15kV ESD-Protected, +5V RS-232 Transceivers	16P/SO	5V	0°C to +70°C
42270	MAX202ECSE+	MAXIM	±15kV ESD-Protected, +5V RS-232 Transceivers	16 Narrow SO	5V	0°C to +70°C
47663	MAX202EESE	MAXIM	+5V, RS-232 Transceivers with 0.1μF External Capacitors	16P-SO	5V	-40~85°C
33321	MAX202ESE	MAXIM	+5V, RS-232 Transceivers with 0.1μF External Capacitors	16P/SO	-0.3~6V	0~70°C
34912	MAX205ECPG	MAXIM	±15kV ESD-Protected, +5V RS-232 Transceivers	24P/DIP	5V	0°C to +70°C
34913	MAX206ECAG	MAXIM	±15kV ESD-Protected, +5V RS-232 Transceivers	24 SSOP	5V	0°C to +70°C
34914	MAX206ECNG	MAXIM	±15kV ESD-Protected, +5V RS-232 Transceivers	24P/DIP	5V	0°C to +70°C
34923	MAX208CNG	MAXIM	+5V RS-232 Transceivers with 0.1μF External Capacitors	24P/DIP	5V	0°C to +70°C
34915	MAX208ECAG	MAXIM	±15kV ESD-Protected, +5V RS-232 Transceivers	24 SSOP	5V	0°C to +70°C
34918	MAX208ECNG	MAXIM	±15kV ESD-Protected, +5V RS-232 Transceivers	24P/DIP	5V	0°C to +70°C
42260	MAX211CAI	MAXIM	+5V, RS-232 Transceivers with 0.1μF External Capacitors	28 SSOP	5V	0°C to +70°C
34919	MAX211ECWI	MAXIM	±15kV ESD-Protected, +5V RS-232 Transceivers	28P/SO	5V	0°C to +70°C
42262	MAX213CAI+T	MAXIM	+5V, RS-232 Transceivers with 0.1μF External Capacitors	28 SSOP	5V	0°C to +70°C
42263	MAX213EAI-T	MAXIM	+5V, RS-232 Transceivers with 0.1μF External Capacitors	28 SSOP	5V	-40°C to +85°C
42267	MAX213ECAI+	MAXIM	±15kV ESD-Protected, +5V RS-232 Transceivers	28 SSOP	5V	0°C to +70°C
49603	MAX231CPD	MAXIM	+5V Powered Isolated RS-232 Drivers/Receivers	14/DIP	5-13.2V	0°C to +70°C
40100	MAX232ACSE	MAXIM	+5V-Powered, Multichannel RS-232 Drivers/Receivers	16P Narrow SO	5V	0°C to 70°C
42233	MAX232CPE+	MAXIM	+5V-Powered, Multichannel RS-232 Drivers/Receiver-Pb Free	16 Plastic DIP	-0.3V to +6V	0°C to +70°C
22763	MAX232CSE+T	MAXIM	+5V-Powered, Multichannel RS-232 Drivers/Receiver	16P NARROW SOP	-0.3~6V	0~70°C
34925	MAX232CWE	MAXIM	+5V-Powered, Multichannel RS-232 Drivers/Receiver	16P/SO	5V	0°C to +70°C
42240	MAX232CWE-T	MAXIM	+5V-Powered, Multichannel RS-232 Drivers/Receivers	16 Wide SO	-0.3V to +6V	0°C to +70°C
34921	MAX232ECPE	MAXIM	±15kV ESD-Protected, +5V RS-232 Transceivers	16P/DIP	5V	0°C to +70°C

