

# Soldering & Desoldering

## HAKKO\_Soldering Iron + Available Tip Shape

Detailed product specifications are available on: [us.100y.com.tw](http://us.100y.com.tw)



Part No.	Product No.	Description	Solder Type	Length(mm)
14070	B1784	907/980 Nut	900M,933,935M,907,913,980,981,984,985,951	Outside Diameter :13mm Inside Daimeter:8.5mm




Model No: BSB4



C1313



Model No: EB4/EB6  
Total length (mm) : EB4: 70mm



Model No: BSB6

Part No.	Product No.	Manufacturer	Description	Solder Type	Length(mm)
3258	BSB4		Soldering Iron Tip	HAKKO-507,508	70mm
8797	BSB6		Soldering Iron Tip	HAKKO 509	90mm
16551	C1313	HAKKO	Soldering Iron Stand For 950		
7882	EB4		Soldering Iron Tip	HAKKO 501G,502G	70mm
8798	EB6		Soldering Iron Tip	HAKKO 503G	90mm



**FEATURES:**

- ON / OFF switch
- Quick-change composite tip (PN: T11-B style)
- Maintains soldering temperature of 600° F
- Separate battery magazine for easy replacement of batteries
- Long-life battery power
- Alkaline batteries ~70 minutes
- Ni-MH batteries ~120 minutes

Part Number	FX-901/P
Power Consumption	Alkaline batteries (AA) 6V (6W) N-MH batteries (AA) 4.8V (5W)
Battery	Type AA x 4 (not included)
Outer Dimensions (w/o cap)	212 (L) x 40 (W) x 23 (D) mm (8.3 x 1.6 x 0.9 inch)
Weight (w/o batteries)	76 g (0.17 lb.)

Part No.	Product No.	Manufacturer
28353	FX-901	HAKKO



Power consumption: 75W  
 Temperature range: 200~450°C (400~840°F)  
 The stability of temperature: ±5°C (±9°F) (not use)  
 console:  
 Bulk: 80 (W) x130 (H) x131 (D) mm  
 Weight: 1.2kg  
 soldering iron:  
 Power consumption: 70W  
 Length (no wire) : 188mm (add 2- 4D soldering iron head)  
 Weight (no wire) : 30g (add 2- 4D soldering iron head)

Part No.	Product No.	Manufacturer	Description	Output power W	Solder Type	The range of control temperature °C	Static-proof Y/N	Suitable voltage
35308	FX-951	HAKKO	HAKKO_FX-951 Standard Soldering Iron for Lead-free Soldering	75W	FM-2025	200 ~ 450°C	Y	110V



- Power Source 100VAC50/60Hz
- Power Consumption 140W
- Control Temperature Range 200-450°C
- Temperature Precision Ripple temperature at idle 5°C

Part No.	Product No.	Manufacturer	Description	Output power W	Solder Type	Length(mm)	The range of control temperature °C	Static-proof Y/N
35528	FX-952	HAKKO	HAKKO 952ESD	140W	FM-2025	188mm	200 ~ 450°C	Y



- Trigger operation for easy one-hand soldering.
- Quick solder wire replacement with a simple upward push of the trigger.
- Solder feed control for precise adjustment of the amount of solder wire feed to the tip. <Min: 3mm Max: 8mm>
- Simple heating element replacement procedure requires no special skills.

Part No.	Product No.	Manufacturer	Description	Output power W	Handpiece (mm)	Suitable voltage
39108	HAKKO-585FP	HAKKO	HAKKO_MG 585FP Sold ering Gun	60W	6mm	110V

• We provide a wide range of products to development and maintenance engineers in all type of business

Taiwan: 886-3-5753170

Shanghai: 021-54151736 Shenzhen: 0755-83298787

**Centenary Materials**

Waiting for your phone call



T E L : Taiwan: 886-3-5753170  
 F A X : Taiwan: 886-3-5753172  
 E-mail: Taiwan: [us\\_sale@100y.com.tw](mailto:us_sale@100y.com.tw)

Shenzhen: 86-755-83298787  
 Shenzhen: 86-755-83640655  
 Shenzhen: [100y@163.com](mailto:100y@163.com)

Shanghai: 86-21-54151736  
 Shanghai: 86-21-64605107  
 Shanghai: [100y-1@163.com](mailto:100y-1@163.com)