

Soldering & Desoldering

HAKKO_Soldering + Available Tip Shape

Detailed product specifications are available on: us.100y.com.tw



DESCRIPTION:

This iron is best used for micro soldering with the HAKKO 926, 927, 936 and 937 soldering stations. Choice of non-ESD and ESD-safe.

| Part No. | Product No. | Description | Solder Type | Length(mm) | Suitable voltage | Weight |
|----------|-------------|--------------------|-----------------|------------|------------------|--------|
| 12667 | 900S ESD | Soldering Iron Tip | 900S-ESD Series | 176mm | 24V | 25g |



| Part No. | Product No. | Manufacturer | Description | Solder Type | Handpiece (mm) | Length(mm) |
|----------|-------------|--------------|--------------------|-------------|----------------|------------|
| 11204 | 900S-T-1C | HAKKO | Soldering Iron Tip | 900S Series | 1mm | 42mm |



| Part No. | Product No. | Manufacturer | Description | Output power W | Solder Type | Length(mm) | Suitable voltage | Weight |
|----------|-------------|--------------|----------------------|----------------|--------------|------------|------------------|--------|
| 8062 | 907ESD | HAKKO | HAKKO Soldering Iron | 50W | HAKKO 936ESD | 190mm | 24V | 44g |



Standard Tip: 900M-T-B
Tip to Ground Resistance: Under 2 ohm
Tip to Ground Potential: Under 2mV
Heating element: Ceramic heater

| Part No. | Product No. | Manufacturer | Description | Length(mm) | Weight |
|----------|-------------|--------------|----------------------------------|------------|--------|
| 12898 | 907M | HAKKO | 936 Series Soldering Iron Pencil | 190mm | 44g |




A1379



A1384



A1390



Description:
For 950 SMD Hot Tweezer Handpiece
Type: SOP 4L
Use with models 926, 927, 928, 936, 937, 939, 702, 703, 703B



| Part No. | Product No. | Manufacturer | Description | Output power W | Solder Type | Handpiece (mm) | Length(mm) | Suitable voltage | Static-proof Y/N | The range of control temperature °C |
|----------|-------------|--------------|---------------------------------|----------------|-------------|----------------|------------|------------------|------------------|-------------------------------------|
| 16058 | A1379 | HAKKO | Desoldering Attachment 1L | | HAKKO-950 | 1.0*1.0*13.0 | 65mm | | Y | |
| 43011 | A1384 | HAKKO | Tip SOP/4L | 50W | | | 8 | AC24V | Y | 200-400 |
| 16980 | A1390 | HAKKO | Desoldering Attachment /SOP 4L | | HAKKO-950 | 4.0*1.0*8.0 | 64.5mm | | Y | |
| 34220 | A1392 | HAKKO | Desoldering Attachment /SOP 15L | | HAKKO-950 | 15.0*1.0*8.0 | | | Y | |



B1786



C1312



| Part No. | Product No. | Manufacturer | Description | Output power W | Solder Type | Handpiece (mm) | Length(mm) | Suitable voltage | Static-proof Y/N | Weight | The range of control temperature °C |
|----------|-------------|--------------|-------------------------------|----------------|---------------------------------|----------------|------------|------------------|------------------|--------|-------------------------------------|
| 13138 | B1786 | HAKKO | 936-ESD-P Heater Pipe | | HAKKO-936-ESD-P | | 45mm | | | | |
| 16550 | C1312 | HAKKO | HAKKO 950 ESD SMD Hot Tweezer | 50W | 700,701,702,926,927,928,936,937 | 2mm | 186mm | AC24V | Y | 93g | 200~400°C |



- **Quick Heating**
Begin soldering in only ten seconds!
- **Faster Thermal Recovery**
Greater thermal capacity and rapid transmission to the tip means faster thermal recovery.
- **Stable Temperature Control**
The temperature control sensor is built into the heating element for faster, more stable temperature control.
- **High Insulation**
High InsulationThe highly insulated ceramic heater never overheats. An insulation factor of over 100MΩ can be maintained even during actual use.
- **Improved Work Efficiency**
The compact, lightweight design with high cooling efficiency at the handle permits fatigue-free soldering over long periods for maximum work efficiency.

