

Soldering & Desoldering

Fume Absorption / Extractor

Detailed product specifications are available on: us.100y.com.tw



- Technical data MG-100S
- Noise level: 52 dB(A)
- Voltage: 100-240V 50/60Hz
- Effect: 100 Watt
- Fuse: 2 x 6.3AT

- Maximum suction capacity: 100 m³/h
- Micro filter - Separation degree, DOP: >99,97%
- Gas filter: Yes
- Warranty (except for filters): 1 year

Part No.	Product No.	Manufacturer	Description	Voltage	Max.air volume	Size	Weight	Noise dB(A) at 1M
16565	MG-100S	FILTRONIC	Filtronic_High airflow filter system-Bench top Arm-extraction	100-240V 50/60Hz	100 m3/hr	610(H)*460(W)*210(D)mm	17.5kg	52dB



- Power: 115Vac 50/60Hz
- The capability of absorb smoge quantity: 105-126CFM



Part No.	Product No.	Manufacturer	Description	Voltage	Max.air volume	Size	Weight
7555	SA-9-115	OK	Smoke Absorber / Fume Absorber	115VAC 50/60Hz	150-126CFM	21*15*20mm	1Kg



Replacement filter set, 3 pcs



Part No.	Product No.	Manufacturer	Description	Noise dB(A) at 1M
11255	SAF-1	OK	Active Carbon Filtler	(L)135mm*(W)135mm




Part No.	Product No.
40641	SH-001

Soldering Iron Power Controller


Detailed product specifications are available on: us.100y.com.tw



- Rating voltage: 110V
- Max. output: 100%
- Min. input: 50%
- The number of W for Suitable solder <20W




Part No.	Product No.	Manufacturer	Description	W	Rating voltage	Max.output	Min.input
2130	SAT-1	OK	Soldering Iron Power Controller	<20W	110V	100%	50%



- Protect solder, Prolong the life of soldering

The adjust button of set watt

Part No.	Product No.	Description	W	Rating voltage	The range of control temperature °C	Power consumption
6574	ST-521	Soldering Iron Power Controller	30W-40W Max	110V/60Hz	>200°C	<0.8W



The adjust button of set watt

Part No.	Product No.	Description	W	Rating voltage	The range of control temperature °C	Power consumption	Suitable solder type
2492	ST-522	Soldering Iron Power Controller	20W-60W Max	110V/60Hz	>20-45W200°C >45-60W300°C	0.8W	Ceramic Soldering Iron

