

# Soldering & Desoldering

## Solderite\_Soldering Equipment Series

Detailed product specifications are available on: [us.100y.com.tw](http://us.100y.com.tw)



- Power: 3W
- Input voltage: 6V
- Speed of send tin: 0-36mm/s
- Dia. soldering tin thread:  $\Phi 0.2$ - $\Phi 2.5$ mm

Part No.	Product No.	Description	Output power W
47429	LB-300	Solderite_Sending Tin Device	3W



### Control equipment

Input voltage: SGS-3505/LB-3605: AC180-240V, 50/60Hz  
 SGS-3515/LB-3615: AC90-125V, 50/60Hz  
 Power consume: SGS-3505/3515: 20W (average); 120W (max)  
 LB-3605/3615: 20W (Average); 150W (max)  
 Output voltage: DC 0-33.5V

### Soldering Iron

Output power: SGI-902S: 90W (max)  
 LBI-1902S: 130W (max)  
 Input voltage: DC 0-33.5V

Part No.	Product No.	Description	Volt.	Length of soldering head(mm)	Temp range °C	ESD Y/N	Output power W	Weight
47395	LB-3615	Solderite_Soldering Station	AC110V	145mm	250-500 °C	Y	150W	0.76kg



- Power consume: 8W (average) / 18W (max)
- Temperature of soldering head: 200-480°C (392-896°F)
- Length: 162mm (6-4/10")
- Temperature of environment: 0-40°C

Part No.	Product No.	Description	Temp range °C	Output power W
47417	SGI-600PRO	Solderite_Solder pen	200-480 °C	8~18W



- Output power: 8W (SGI-700) / 12W (SGI-700R)
- Dimensions: 175mm

Part No.	Product No.	Description	Output power W	Weight
47421	SGI-700	Solderite_Cordless Soldering Iron Not Cold Heat	8W	66g



### Control equipment

Input voltage: SGS-2005L/LB-2105: AC180-240V, 50/60Hz  
 SGS-2015L/LB-2115: AC90-125V, 50/60Hz  
 Power consume: SGS-2005L/2015L: 20W (average); 105W (max)  
 LB-2105/2115: 20W (average); 150W (max)  
 Output voltage: DC 0-30V

### Soldering Iron

Output power: SGI-902S: 90W (max)  
 LBI-1902S: 130W (max)  
 Input voltage: DC 0-30V

Part No.	Product No.	Description	Volt.	Length of soldering head(mm)	Temp range °C	ESD Y/N	Output power W	Weight
47401	SGS-2015L	Solderite_Soldering Station	AC110V	150mm	250-500 °C	Y	105W	0.72kg



### Control equipment

Input voltage: SGS-2505/LB-3105: AC180-240V, 50/60Hz  
 SGS-2515/LB-3115: AC90-125V, 50/60Hz  
 Power consume: SGS-2505/2515: 20W (average); 105W (max)  
 LB-2605/2615: 20W (average); 150W (max)  
 Output voltage: DC 0-30V

### Soldering Iron

Output power: SGI-902S: 90W (max)  
 LBI-1902S: 130W (max)  
 Input voltage: DC 0-30V

Part No.	Product No.	Description	Volt.	Length of soldering head(mm)	Temp range °C	ESD Y/N	Output power W	Weight
47375	SGS-2505	Solderite_Soldering Station	AC220V	150mm	250-500 °C	Y	105W	0.72kg
47383	SGS-2515	Solderite_Soldering Station	AC110V	150mm	250-500 °C	Y	105W	0.72kg

- We provide a wide range of products to development and maintenance engineers in all type of business
- If you cannot find the components you want on the catalogue, please call us.



Taiwan: 886-3-5753170

Shanghai: 021-54151736 Shenzhen: 0755-83298787

## Centenary Materials

Waiting for your phone call



T E L : Taiwan: 886-3-5753170  
 F A X : Taiwan: 886-3-5753172  
 E-mail: Taiwan: [us\\_sale@100y.com.tw](mailto:us_sale@100y.com.tw)

Shenzhen: 86-755-83298787  
 Shenzhen: 86-755-83640655  
 Shenzhen: [100y@163.com](mailto:100y@163.com)

Shanghai: 86-21-54151736  
 Shanghai: 86-21-64605107  
 Shanghai: [100y-1@163.com](mailto:100y-1@163.com)