

# Speakers & Microphones

## Wireless Megaphone

Detailed product specifications are available on: [us.100y.com.tw](http://us.100y.com.tw)



Part No.	Product No.	Description
27107	TC-313	MINI Charge educate amplifier

## Microphones

Detailed product specifications are available on: [us.100y.com.tw](http://us.100y.com.tw)

### Omnidirectional Electret Condenser Microphone Cartridges



Part No.	Product No.	Description	SPEC
10456	FM-6B2	Mircophone Cartridges	φ 6.0*5/0.5mA



- Dimensions outer size x Depth±0.2mm: 9.8\*6.7
- Sensitivity (0db=1V/Par, 1K Hz, ±3db): -36, -40, -44
- Directivity: Omni-directional
- Operating voltage std. (max) V: 3(9)
- Current consumption mA. (max.): 0.8
- Frequency range Hz: 50~16000
- S/N Ratio db: Min. 60

Part No.	Product No.	Description	SPEC
3508	PVM-4FT	Mircophone Cartridges	φ 9.8*6.7/0.8mA


## Speakers

### Round Alnico Type Speakers

Detailed product specifications are available on: [us.100y.com.tw](http://us.100y.com.tw)




Part No.	Product No.	Description	Impedance Ω±15%	Nini-Watts Nor.(mW)
47870	3" bugle	Round Alnico Type Speakers 8Ω 0.5W	8	0.5W




Article No:	36CP04H
Rated impedance (Ω)	4
Rated power (W)	2.0
max power (W)	4.0
Resonant frequency (Hz)	330±66
Frequency range (Hz)	150~20k
Sound pressure level (dB)	92±3
Materials:	Metal

Part No.	Product No.	Manufacturer	Description	Dia.*Depth	Impedance Ω±15%	Nini-Watts Nor.(mW)	Nini-Watts Max.(mW)	Frequency Range(Hz)
18347	36CP08H	FCE	Round Alnico Type Speakers 8Ω 2.0W	Φ36x16.2H mm	8	2.0W	4.0W	150~20K



Article No:	38CP08
Rated impedance (Ω)	8
Rated power (W)	0.25
max power (W)	0.50
Resonant frequency (Hz)	800±150
Frequency range (Hz)	600~7K
Sound pressure level (dB)	81±3
Materials:	Metal

Part No.	Product No.	Manufacturer	Description	Dia.*Depth	Impedance Ω±15%	Nini-Watts Nor.(mW)	Nini-Watts Max.(mW)	Frequency Range(Hz)
14082	38CP08	FCE	Round Alnico Type Speakers 8Ω 0.25W	Φ38*9.0H mm	8	0.25W	0.50W	600~7000



Article No:	40CP08H
Rated impedance (Ω)	8
Rated power (W)	2.0
max power (W)	4.0
Resonant frequency (Hz)	230±46
Frequency range (Hz)	130~20K
Sound pressure level (dB)	84±3
Materials:	Metal

Part No.	Product No.	Manufacturer	Description	Dia.*Depth	Impedance Ω±15%	Nini-Watts Nor.(mW)	Nini-Watts Max.(mW)	Frequency Range(Hz)
18348	40CP08H	FCE	2.0W Pager Cone Speaker	Φ40x17.6mm	8Ω	2.0W	4.0W	130~20K



T E L : Taiwan: 886-3-5753170  
 F A X : Taiwan: 886-3-5753172  
 E-mail: Taiwan: [us\\_sale@100y.com.tw](mailto:us_sale@100y.com.tw)

Shenzhen: 86-755-83298787  
 Shenzhen: 86-755-83640655  
 Shenzhen: [100y@163.com](mailto:100y@163.com)

Shanghai: 86-21-54151736  
 Shanghai: 86-21-64605107  
 Shanghai: [100y-1@163.com](mailto:100y-1@163.com)