

Switches & Control Gear

Piano Type DIP Switches (In-Line Switches)

Detailed product specifications are available on: us.100y.com.tw



PROD NO.	NO. OF POS	DIMA	
RPL-03	03	9. 06	0. 357
RPL-04	04	11. 34	0. 446
RPL-05	05	13. 88	0. 546
RPL-06	06	16. 42	0. 646
RPL-08	08	21. 5	0. 846
RPL-10	10	26. 58	1. 046

Part No.	Product No.	Description	No. of pos.
22093	RPL-03B	Piano Type DIP Switches	3P
3384	RPL-04B	Piano Type DIP Switches	4P
22094	RPL-05B	Piano Type DIP Switches	5P
2199	RPL-06B	Piano Type DIP Switches	6P
6819	RPL-08B	Piano Type DIP Switches	8P
2201	RPL-10B	Piano Type DIP Switches	10P
2202	YDP-12	Piano Type DIP Switches	12P
51559	YDPL-12	Piano Type DIP Switches	12P

Rotary DIP Switches

Detailed product specifications are available on: us.100y.com.tw



SPECIFICATIONS

Operating voltage: 24V DC max
 Switch: 100mA max
 Carrying current: 0. 5A max
 Contact resistance: 100mΩ max
 Insulation resistance: 1, 000mΩ max
 Dielectric strength: 300V AC for 1 minute
 Operating temperature: -10°C to 70°C
 Soldering temperature: 25±5°C for 5 seconds
 Life: 10, 000 step operations minimum

MATERIALS:

- HOUSING, Knob: Thermoplastic
- Printed circuit boards: Hard gold plated over nickel plated on epoxy fiberglass
- Contacts/Terminations: Precious metal on phosphor bronze

Part No.	Product No.	Description	Position
10747	900A-R2-T1-M1-112	Rotary Dip Switches	6P
10746	900A-R2-T1-M2-14	Rotary Dip Switches	6P
5679	900A-R2B-T112	Rotary Dip Switches	6P



SPECIFICATIONS

Operating voltage: 24V DC max
 Switch: 100mA max
 Carrying current: 0. 5A max
 Contact resistance: 100mΩ max
 Insulation resistance: 1, 000mΩ max
 Dielectric strength: 300V AC for 1 minute
 Operating temperature: -10°C to 70°C
 Soldering temperature: 25±5°C for 5 seconds
 Life: 10, 000 step operations minimum

Part No.	Product No.	Description	Position	Code Type
21768	Y900A-R1T21212	Rotary Dip Switches	0-9	900A
21769	Y900A-R1T21412	Rotary Dip Switches	0-9,A-F	900A

Foot Switches

Detailed product specifications are available on: us.100y.com.tw



Sort	Style	Load	Mini switch style	Wire sort/length	Contact	Operative pressure	Shell material
Standard	TFS-101	10A 250VAC	Import V style switch	0. 75mm ² , 3C/0.5M , 1M-3M	1A1B	3. 5kg	Plastic/aluminum mental
	TFS-102	15A 250VAC	TM 1704	0.75mm ² , 3C/1M , 1M-3M	1A1B	"	"
Mini & fixed piece	TFS-201	10A 250VAC	Import V style switch	0.5mm ² , 3C/1M~3M	1A1B	"	"
Cover style	TFS-302	15A 250VAC	TM 1704	Add cable fixed nob no cable	1A1B	3. 5kg	Plastic/aluminum mental
Big style	TFS-402	15A 250VAC	TM 1704		2A2B	"	"
Full cover style	TFS-402	15A 250VAC	TM 1704*2		1A1B	3kg	aluminum mental



Part No.	Product No.	Manufacturer	Description	Contact Rating	Contact Type
39036	TFS-101	TEND	Foot Switches	250Vac/10A	OFF/ON
42222	TFS-102	TEND	Foot Switches	250v/15A	OFF/ON



T E L : Taiwan : 886-3-5753170
 F A X : Taiwan : 886-3-5753172
 E-mail : Taiwan : us_sale@100y.com.tw

Shenzhen : 86-755-83298787
 Shenzhen : 86-755-83640655
 Shenzhen : 100y@163.com

Shanghai : 86-21-54151736
 Shanghai : 86-21-64605107
 Shanghai : 100y-1@163.com